## **Accepted Manuscript**

Effect of rectangular hot water tank position and aspect ratio on thermal stratification enhancement

stratification enhancement

Burak Kurşun, Korhan Ökten

PII: S0960-1481(17)30974-6

DOI: 10.1016/j.renene.2017.10.013

Reference: RENE 9301

To appear in: Renewable Energy


Received Date: 26 July 2017

Revised Date: 02 October 2017

Accepted Date: 04 October 2017

Please cite this article as: Burak Kurşun, Korhan Ökten, Effect of rectangular hot water tank position and aspect ratio on thermal stratification enhancement, *Renewable Energy* (2017), doi: 10.1016/j.renene.2017.10.013

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



### **ACCEPTED MANUSCRIPT**

#### Highlights

- The inclined placement of the rectangular hot water tank increases the thermal stratification.
- The change in aspect ratio increase the thermal stratification enhancement for the vertical position of the tank.
- The change in tank position and aspect ratio causes exergy destruction at negligible level.
- Reducing the tank aspect ratio also decreases the thermal storage capacity.

#### Download English Version:

# https://daneshyari.com/en/article/4925931

Download Persian Version:

https://daneshyari.com/article/4925931

<u>Daneshyari.com</u>