Accepted Manuscript

Research Paper

A novel heat transfer model of a phase change material using in solar power plant

Qianjun Mao, Hongzhang Chen, Yazhou Zhao, Hongjun Wu


PII: S1359-4311(17)35279-1

DOI: https://doi.org/10.1016/j.applthermaleng.2017.10.038

Reference: ATE 11236

To appear in: Applied Thermal Engineering

Received Date: 12 August 2017 Revised Date: 7 October 2017 Accepted Date: 7 October 2017



Please cite this article as: Q. Mao, H. Chen, Y. Zhao, H. Wu, A novel heat transfer model of a phase change material using in solar power plant, *Applied Thermal Engineering* (2017), doi: https://doi.org/10.1016/j.applthermaleng. 2017.10.038

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

ACCEPTED MANUSCRIPT

A novel heat transfer model of a phase change material using in solar power plant

Qianjun Mao a,*, Hongzhang Chen a, Yazhou Zhao b, Hongjun Wuc, *

E-mail addresses: maoqianjun@163.com (Q. Mao) or hjwu@nepu.edu.cn (H. Wu)

Abstract: Concentrating solar power (CSP) plant coupling with thermal energy storage is a popular technology in the recent years. The storage technology is the wave of the future in solar utilization field. A lot of scholars focus on studying of heat transfer performance by the experimental or simulating method. In this paper, a novel heat transfer model of three-dimensional unsteady state heat conduction in cylindrical coordinate has been proposed based on the theoretical analysis. The most difficulty problem during the solution is the materials, which is molten salt based on some real cases, that is a phase change material (PCM) with the melting point of 494 K. The computer code of this model is written by C language in MATLAB software. The results show that the charge time is 25200 s (about 7 hours). Also, the characteristic of melting progress of the PCM has been obtained based on this program. The aim of this paper is to develop a new heat transfer model and provide a good reference to utilize solar energy.

Keywords: Concentrating solar power plant; Mathematical model of heat transfer; three-dimensional unsteady state; Cylindrical coordinate.

^aSchool of Urban Construction, Wuhan University of Science and Technology, Wuhan 430081, China

^b Institute of Geology and Geophysics, Chinese Academy of Science, Beijing 100029, China

^c School of Chemical Engineering, Northeast Petroleum University, Daqing 163318, China

^{*} Corresponding author. Tel./fax:+86 27 68893616

Download English Version:

https://daneshyari.com/en/article/4990360

Download Persian Version:

https://daneshyari.com/article/4990360

<u>Daneshyari.com</u>