Contents lists available at ScienceDirect

Separation and Purification Technology

journal homepage: www.elsevier.com/locate/seppur



Check fo

Helium3 isotope separation and lambda front observation

Wojciech Kempiński^{a,*}, Szymon Łoś^a, Zbigniew Trybuła^a, Maciej Chorowski^b, Jarosław Poliński^b, Jakub Niechciał^{a,b}, Tomasz Jaskólski^c, Katarzyna Chołast^c, Andrzej Kociemba^c

 $^{
m a}$ Institute of Molecular Physics, Polish Academy of Sciences, M. Smoluchowskiego 17, 60-179 Poznań, Poland ^b Wrocław University of Technology, Wybrzeże Wyspiańskiego 27, 50-560 Wrocław, Poland

^c Polish Oil and Gas Company – Odolanów, Krotoszyńska 148, 64-430 Odolanów, Poland

ARTICLE INFO	A B S T R A C T
Keywords: He3 isotope Front lambda Heat exchanger	We present the method of the liquid helium enrichment with He3 isotope based on a special solution of the helium bath cryostat (25 l LHe) equipped with the heat exchanger and entropy filter to stimulate quantum filtration process in low temperature region. The cryostat design makes it possible to increase the initial concentration of He3 more than one order of magnitude. While the temperature of lambda point was achieved close to the capillary-equipped heat exchanger, the movement of lambda front within the liquid helium is observed. A consistent description of the various stages of the cryostat operation with cooling process above the lambda transition, during the long period of lambda front movement and in a superfluid region, with the acquisitioning of He3 isotope in all of these regions, is devoted to the design of a helium isotope flow-separator on an industrial context.

1. Introduction

Strong fluctuations on the He3 isotope market appeared in the period of last decade [1,2]. After the attacks on September 11, 2001 demand for neutron detectors strongly increased and He3 isotope starts to be of the great importance due to its sensitivity to the radioactive materials. He3 availability is also important from the point of view of the future clean energy production - nuclear fusion in the D-He3 system can play the crucial role. Therefore serious plan to utilize He3 from the Moon and planets such as Jupiter or Saturn are developed [3,4]. In contrast to experimental works, where the filtration and/or rectification methods have been described [5-9], theoretical studies are dedicated rather to the specific membranes, which can help to separate He4 and He3 isotopes [10-15]. In practice, due to the He3 isotope market demand, patents are also a goal [16,17]. One of the most important methods to acquire He3 here on Earth is separation of this isotope from the liquid He4/He3 mixture using two processes - filtration based on entropy filter or rectification procedure. Both methods should be the most profitable if performed directly at a helium plant [1,5]. Many cryogenic applications are connected with exploitation of a bath cryostats. These cryostats are usually dedicated to work at temperatures near 4.2 K (liquid helium boiling temperature) and below, down to 1 K. In this case the system needs to be cooled down at least to the lambda point ($T_{\lambda} = 2.18$ K). There are essentially two ways to reach this

temperature level. Both are well known: reducing vapor pressure above the liquid helium surface, usually with a simple rotary pump ("pumping procedure") or using various kinds of heat exchangers. Some solutions were designed for superconducting magnets. These cryostats are called lambda point refrigerators and are used to cool down the superconducting magnets to approximately 2.2 K using the needle valve to control the liquid helium flow around the lambda plate (refrigerating copper coils) [18]. In these refrigerators lambda plate is located in the top of the superconducting magnet to use the convection of helium according to its density which increases with decreasing temperature until the lambda point is reached [19]. During the helium pumping, more than 30% of helium is lost, together with the He3 isotope. Simultaneously the He3 evaporation from the mixture strongly increases [20]. It is because the difference between partial pressures of He3 and He4 components increases as the temperature is going down - below 1 K this difference reaches three orders of magnitude [21,22]. In our experiment a special solution using the liquid nitrogen shielded bath cryostat, together with the heat exchanger is used. This solution enabled us to observe the moving lambda front within the volume of liquid helium without removing the He3 isotope during the cooling procedure. It means that in this experiment the whole liquid helium bath can be subjected to the He3 filtration procedure. This method gives the possibility to perform the He3 isotope enrichment in a quite effective way. To find the best power range necessary to activate the

* Corresponding author.

E-mail address: wojkem@ifmpan.poznan.pl (W. Kempiński).

https://doi.org/10.1016/j.seppur.2018.08.003

Received 6 May 2018; Received in revised form 1 August 2018; Accepted 4 August 2018 Available online 04 August 2018

1383-5866/ © 2018 Published by Elsevier B.V.

entropy filter for the filtration process, with the use of the helium fountain effect of superfluid helium, the standard double glass Dewar container was used.

2. Results and discussion

Schematic presentation of the glassy cryostat is shown in Fig. 1. It operates in the power range of 100 mW-1000 mW giving the smooth, laminar flow of the He4 isotope through the capillary fountain system. Using the instrumentation presented in Fig. 1 we also calibrated the quadrupole mass spectrometer (QMS 700) produced by Pfeiffer Vacuum GmbH which allows for detection of 10^{-3} ppm of He3 (QMS 700 parameters are: mass range 1–128 amu, sensitivity - single ion 10^{-19} A, resolution - one neutron). This part of the experiment confirms that the pumping procedure at the temperature level of 1.5 K removes He3 efficiently. This effect (as mentioned before) is connected with the increasing difference between the partial pressures of He4 and He3 at temperatures below 2K. In order to observe the difference in concentration of He3 during the filtration process, two samples had to be collected: the first one before the mixture enters the entropy filter and the second one behind the filter. Decrease of the He3 isotope concentration during overfilling of the burette is shown in Fig. 2 - albeit the He3 level behind the filter still is lower than in front of them, filtration process occurs, but not effectively.

In order to avoid the above mentioned loss of the He3 isotope, the 25 L bath cryostat with the heat exchanger was constructed. Schematic presentation of this apparatus is shown in Fig. 3. Cooling power of the heat exchanger was kept at the level of 700 mW. Cooling process was realized with the capillary of 0.01 mm diameter with a steel wire slightly thinner than the capillary inside. It allowed for the stabilization of the helium transfer during the cooling process at the very low level. Helium evaporated in the coper coil which worked as the Joule-Thomson valve. This system reduced the helium consumption by approximately 10% during the process of cooling to the lambda transition. Heat exchanger was located at the bottom of the cryostat - opposite side to the lambda point refrigerators described by Belshaw [18]. As the He4 density reaches maximum close to the lambda point [19], the convection drives the temperature changes in the whole helium volume. Thus the gradients of density and temperature appear (in the opposite direction than in the lambda point refrigerators). It allows the observation of the front lambda moving up the cryostat.

Extremely high thermal conductivity of the superfluid helium (below lambda point it reaches values more than five orders of magnitude larger than that of helium above T_{λ} [21]) ensured us that the temperatures below T_{λ} could only occur after the whole helium volume was cooled to the lambda point. The lambda front movement was observed via the set of thermometers located at different heights inside the cryostat. Thermometers where mounted at the points crucial for the cryostat operation. Front lambda movement is shown in Fig. 4. This figure also presents the schematic thermometers location, i.e. at the heat exchanger capillary (blue¹), entropy filter (magenta), the green thermometer is located behind the entropy filter - there is fountain effect (inside a steel pipe) and additional point located in the intermediate position (red). The last T indication comes from the equilibrium pressure inside cryostat (orange).

The first part of the experiment (time interval 10–15 ks) shows the front lambda ($T_{\lambda} = 2.18$ K) moving up the cryostat. The effect could be traced as the thermometers reached T_{λ} one by one, starting from the bottom one (blue). Rapid temperature drops to T_{λ} observed for all thermometers were the result of the strongly increasing thermal transport in the vicinity of thermometers - the Joule heat, generated by the wires and thermometers themselves, was efficiently removed at T_{λ} .



Fig. 1. Glassy cryostat system with the entropy filter inside. Helium during the filtration process was removed from the test-tube.



Fig. 2. Decrease of He3 concentration during the filtration process carried out in the glassy cryostat in which the whole volume of helium were connected to the pomp system.

Due to the extremely high thermal conductivity of the superfluid helium the system had to wait for the lambda transition to occur in its whole volume (up to the helium surface), before further cooling was possible. This stage was recorded by measuring the pressure above the helium surface (orange line in Fig. 4). The final drop was the result of thermal equilibration of the gas and liquid phases (above T_{λ} disturbed

 $^{^{1}}$ For interpretation of color in Fig. 4, the reader is referred to the web version of this article.

Download English Version:

https://daneshyari.com/en/article/7043427

Download Persian Version:

https://daneshyari.com/article/7043427

Daneshyari.com