
Author's Accepted Manuscript

THE DEVELOPMENT OF IMAGE PROCESSING TECHNIQUE TO STUDY THE INTERFACIAL BEHAVIOR OF AIR-WATER SLUG TWO-PHASE FLOW IN HORIZONTAL PIPES

Arif Widyatama, Okto Dinaryanto, Indarto, Deendarlianto



PII: S0955-5986(16)30241-2

DOI: https://doi.org/10.1016/j.flowmeasinst.2017.12.015

Reference: JFMI1399

To appear in: Flow Measurement and Instrumentation

Received date: 21 November 2016 Revised date: 25 October 2017 Accepted date: 28 December 2017

Cite this article as: Arif Widyatama, Okto Dinaryanto, Indarto and Deendarlianto, THE **DEVELOPMENT** OF **IMAGE PROCESSING** TECHNIQUE TO STUDY THE INTERFACIAL BEHAVIOR OF AIR-WATER SLUG TWO-PHASE FLOW IN HORIZONTAL PIPES, Flow Measurement and Instrumentation, https://doi.org/10.1016/j.flowmeasinst.2017.12.015

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting galley proof before it is published in its final citable form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

ACCEPTED MANUSCRIPT

THE DEVELOPMENT OF IMAGE PROCESSING TECHNIQUE TO STUDY THE INTERFACIAL BEHAVIOR OF AIR-WATER SLUG TWO-PHASE FLOW IN HORIZONTAL PIPES

Arif Widyatama ^{1,2}, Okto Dinaryanto ^{1,3}, Indarto ^{1,2}, Deendarlianto ^{1,2*}

¹Department of Mechanical & Industrial Engineering, Faculty of Engineering, Universitas Gadjah Mada, Jl. Grafika
No. 2, Yogyakarta, 55281, Indonesia.

ABSTRACT

The aim of the present paper is to propose an image processing technique in order to study the interfacial behavior of air-water slug two-phase flow in horizontal pipes. Here, the experiments were performed in two sets of transparent acrylic pipes with inner pipe diameters of 16 mm and 50 mm. To observe the interfacial behavior of slug flow, the liquid and gas superficial velocities were set to 0.2 - 0.77 m/s and 0.7 - 2.83 m/s, respectively. Visualization studies by using high speed video camera combined with image processing techniques were since it offered numerous advantages. Moreover, a sequential procedure was implemented for processing of each image. This technique has succeeded to enhance the image contrast and remove the uneven background. Next, a number of steps applied to binary image were also performed in order to remove the dispersed bubble attached on bubble tail which becomes one of the biggest challenges for the visualization studies of slug flow. As a result, the developed image processing technique was able to minimize the errors in order to produce the accurate measurement. Moreover, the processed image have been utilized to gather the quantitative information. It reveals the comprehensive characteristics of slug flow in horizontal pipes. Finally, a good agreement between the present and previous works proves the reliability of the developed technique.

Keyword: Image processing technique, slug flow, visualization study, slug parameter

² Center for Energy Studies, Universitas Gadjah Mada, Sekip Blok K 1A, Yogyakarta, 55281, Indonesia.

³ Department of Mechanical Engineering, Sekolah Tinggi Teknologi Adisutjipto, Blok R Lanud Adisutjipto, Yogyakarta, 55198, Indonesia.

Download English Version:

https://daneshyari.com/en/article/7114027

Download Persian Version:

https://daneshyari.com/article/7114027

<u>Daneshyari.com</u>