Accepted Manuscript

Title: Experimental validation of satellite micro-jitter management strategy in energy harvesting and vibration isolation

Author: Seong-Cheol Kwon<ce:author id="aut0010" biographyid="vt0010" orcid="0000-0003-2161-7272"> Hyun-Ung Oh



PII:	S0924-4247(16)30415-0
DOI:	http://dx.doi.org/doi:10.1016/j.sna.2016.08.030
Reference:	SNA 9808
To appear in:	Sensors and Actuators A
Received date:	21-4-2016
Revised date:	29-8-2016
Accepted date:	29-8-2016
Accepted date:	29-8-2010

Please cite this article as: Seong-Cheol Kwon, Hyun-Ung Oh, Experimental validation of satellite management micro-jitter strategy in energy harvesting and vibration isolation, Physical Sensors and Actuators: А http://dx.doi.org/10.1016/j.sna.2016.08.030

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

ACCEPTED MANUSCRIPT

Experimental Validation of Satellite Micro-jitter Management Strategy in Energy Harvesting and Vibration Isolation

Seong-Cheol Kwon¹

e-mail: mine1147@hanmail.net

and

Hyun-Ung Oh¹ (Corresponding Author)

e-mail: ohu129@chosun.ac.kr

¹Space Technology Synthesis Laboratory, Department of Aerospace Engineering, Chosun

University, 375 Seosuk-dong, Dong-gu, Gwangju 501-759, Republic of Korea

<u>Highlights</u>

- This study suggested a complex system to manage the micro-jitter induced by the spaceborne cooler operation in on-orbit
- The complex system can guarantee dual strategy in both the energy harvesting and the micro-jitter isolation capability
- The harvested recycling energy from the complex system was used to measure the cooler-induced micro-jitter level without requiring external power
- The effectiveness of the proposed complex system has been evaluated through incorporating numerical simulation and experiment

Abstract

Satellite on-board appendages that have mechanical moving parts induce undesirable microjitters during their on-orbit operations, which may seriously affect the image quality of the observation satellite. Therefore, the micro-jitter has always been treated as an isolation Download English Version:

https://daneshyari.com/en/article/7134340

Download Persian Version:

https://daneshyari.com/article/7134340

Daneshyari.com