

Accepted Manuscript

Performance evaluation methodology for multistage launch vehicles with high-fidelity modeling

Marco Pallone, Mauro Pontani, Paolo Teofilatto



PII: S0094-5765(17)30192-3

DOI: [10.1016/j.actaastro.2018.06.012](https://doi.org/10.1016/j.actaastro.2018.06.012)

Reference: AA 6930

To appear in: *Acta Astronautica*

Received Date: 10 February 2017

Accepted Date: 5 June 2018

Please cite this article as: M. Pallone, M. Pontani, P. Teofilatto, Performance evaluation methodology for multistage launch vehicles with high-fidelity modeling, *Acta Astronautica* (2018), doi: 10.1016/j.actaastro.2018.06.012.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Performance evaluation methodology for multistage launch vehicles with high-fidelity modeling

Marco Pallone^{1,*}, Mauro Pontani¹, Paolo Teofilatto¹,

^a*University of Rome "la Sapienza", via Salaria 851/831, 00138 Rome (Italy)*

Abstract

Multistage launch vehicles of reduced size, such as "Super Strypi" or "Sword", are currently investigated for the purpose of providing launch opportunities for microsatellites. Currently, microsatellites are launched according to timing and orbit requirements of the main payload. The limited costs of microsatellites and their capability to be produced and ready for use in short time make them particularly suitable for ready-on-demand requests, such as facing an emergency. As a result, launch vehicles for the exclusive use of microsatellites would be very useful. This work considers the Scout rocket, a four-stage launch vehicle of reduced size used in the past. Its aerodynamics and propulsion are modeled with high fidelity, through interpolation of reliable, accurate available data. For the purpose of reducing the rocket complexity and size, as well as the launch cost per kg of payload, simplification of the rocket subsystems is advisable, and this includes also the guidance system and the related algorithm. In fact, open-loop guidance was actually employed during real Scout flights. In this research, open-loop guidance is investigated, under the assumption that the aerodynamic angle of attack is constant for each of the first three stages. Instead, for the upper stage the terminal optimal ascent path leading to orbit injection is determined through the use of a specific implementation of firework algorithm, in conjunction with the Euler-Lagrange equations and the Pontryagin minimum principle. Firework algorithms represent a recently-introduced heuristic technique inspired by the firework explosions in the night sky. The concept that underlies this method

*Corresponding author, Phone number:+39 328 8057179

Email addresses: `pallone.1420138@studenti.uniroma1.it` (Marco Pallone),
`mauro.pontani@uniroma1.it` (Mauro Pontani), `paolo.teofilatto@uniroma1.it`
(Paolo Teofilatto)

Download English Version:

<https://daneshyari.com/en/article/8055427>

Download Persian Version:

<https://daneshyari.com/article/8055427>

[Daneshyari.com](https://daneshyari.com)