

Accepted Manuscript

A spectral method to find communities in bipartite networks

Liang Feng, Cangqi Zhou, Qianchuan Zhao

PII: S0378-4371(18)31150-6
DOI: <https://doi.org/10.1016/j.physa.2018.09.022>
Reference: PHYSA 20083

To appear in: *Physica A*

Received date: 17 April 2018
Revised date: 6 August 2018

Please cite this article as: L. Feng, et al., A spectral method to find communities in bipartite networks, *Physica A* (2018), <https://doi.org/10.1016/j.physa.2018.09.022>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



Highlights

- Optimizing Barber's bipartite modularity is represented as a spectral problem.
- A new method is proposed to obtain the community structure of bipartite network.
- The new method helps to alleviate the resolution-limit issue.

Download English Version:

<https://daneshyari.com/en/article/10140580>

Download Persian Version:

<https://daneshyari.com/article/10140580>

[Daneshyari.com](https://daneshyari.com)