



Contents lists available at ScienceDirect

# Advanced Powder Technology

journal homepage: [www.elsevier.com/locate/apt](http://www.elsevier.com/locate/apt)



## Original Research Paper

# Theoretical analysis of natural convection boundary layer heat and mass transfer of nanofluids: Effects of size, shape and type of nanoparticles, type of base fluid and working temperature

Abolfazl Zaraki <sup>a</sup>, Mohammad Ghalambaz <sup>b,\*</sup>, Ali J. Chamkha <sup>c</sup>, Mehdi Ghalambaz <sup>b</sup>, Danilo De Rossi <sup>a</sup>

<sup>a</sup> Research Center "E. Piaggio", University of Pisa, Italy

<sup>b</sup> Department of Mechanical Engineering, Dezful Branch, Islamic Azad University, Dezful, Iran

<sup>c</sup> Mechanical Engineering Department, Prince Mohammad Bin Fahd University (PMU), P.O. Box 1664, Al-Khobar 31952, Saudi Arabia

### ARTICLE INFO

#### Article history:

Received 17 September 2014  
Received in revised form 18 February 2015  
Accepted 26 March 2015  
Available online xxx

#### Keywords:

Size of nanoparticles  
Shape of nanoparticles  
Working temperature  
Drift-flux model

### ABSTRACT

The problem of natural convection boundary layer heat transfer of nanofluids is theoretically analyzed. Different aspects of nanoparticles, such as size, shape and constructive material, as well as the type of the base fluid and the working temperature, are examined. The drift-flux model of nanofluids, including the effects of Brownian motion, thermophoresis, and the local volume fraction of nanoparticles, is adopted to model the boundary layer heat and mass transfer of nanofluids. Following the state-of-the-art, the thermo-physical properties are extracted from five different synthesized types of nanofluids. A new non-dimensional parameter, the enhancement ratio, indicating the ratio of the convective heat transfer coefficient of the nanofluid to the base fluid, is introduced. The effect of the nanoparticles on the enhancement of natural convective heat transfer of nanofluids is discussed. The main findings of this study are as follows: (i) the type of the nanoparticles and the base fluid are the most important parameters affecting the heat transfer of nanofluids; (ii) in some cases, the presence of nanoparticles in the base fluid deteriorates the heat transfer rate; and (iii) the rise of the working temperature reduces the efficiency of the nanofluid, which is a crucial issue in applications of nanofluids as coolants.

© 2015 The Society of Powder Technology Japan. Published by Elsevier B.V. and The Society of Powder Technology Japan. All rights reserved.

## 1. Introduction

Nanofluids are a new type of engineered heat transferred fluids, containing nano-sized solid nanoparticles that are being used to enhance the heat transfer [1]. The thermal conductivity and the dynamic viscosity of nanofluids are the most important thermo-physical properties, which affect the convective heat transfer performance of nanofluids [2]. The experiments show that the thermal conductivity and the dynamic viscosity of nanofluids are functions of the size, the shape, and the constructive materials of nanoparticles, as well as the type of the base fluid and the working temperature of the nanofluid [3–7]. There are also other affective parameters such as the method of synthesis of the nanofluids, the sonication time, which affect the thermo-physical properties and the heat transfer performance of nanofluids [4,6,8]. In addition,

there are mass transfer mechanisms, such as Brownian motion and thermophoresis effects, which influence the convective heat transfer performance of nanofluids [9,10].

There are many experimental reports, which have measured the thermal conductivity or the dynamic viscosity of synthesized nanofluids. In order to theoretically analysis the convective heat transfer of nanofluids, the thermal conductivity and the dynamic viscosity of a nanofluid as functions of the volume fraction of nanoparticles are required simultaneously. However, only few studies have reported the data of the thermal conductivity and the dynamic viscosity of a nanofluid, simultaneously [11–15]. Some of these studies are as follows:

Chandrasekar et al. [11] measured the thermal conductivity and the dynamic viscosity of water–Al<sub>2</sub>O<sub>3</sub> nanofluids. They dispersed powders of 43 nm spherical alumina nanoparticles in the water, and then sonicated the nanofluid for 6 h. The thermal conductivity was measured using the hot wire method, and the dynamic viscosity was measured using the Brookfield cone and plate viscometer. The measurements were performed at room temperature. The results indicated the Newtonian behaviors of the samples. It was

\* Corresponding author. Tel.: +98 916 644 2671.

E-mail addresses: [a.zaraki@centropiaggio.unipi.it](mailto:a.zaraki@centropiaggio.unipi.it) (A. Zaraki), [mghalambaz@iaud.ac.ir](mailto:mghalambaz@iaud.ac.ir) (M. Ghalambaz), [achamkha@pmu.edu.sa](mailto:achamkha@pmu.edu.sa) (A.J. Chamkha), [ghalambaz.mehdi@gmail.com](mailto:ghalambaz.mehdi@gmail.com) (M. Ghalambaz), [d.derossi@centropiaggio.unipi.it](mailto:d.derossi@centropiaggio.unipi.it) (D. De Rossi).

**Nomenclature**

$c$	specific heat in constant pressure (J/kg K)	$x$	Cartesian coordinate in horizontal direction (m)
$D_B$	Brownian diffusion coefficient (m <sup>2</sup> /s)	$y$	Cartesian coordinate in vertical direction (m)
$D_T$	thermophoretic diffusion coefficient (m <sup>2</sup> /s)		
$f$	rescaled nanoparticle volume fraction, nanoparticle concentration	<i>Greek symbols</i>	
$g$	gravitational acceleration (m/s <sup>2</sup> )	$\mu$	thermal viscosity (kg s/m)
$h$	thermal convective coefficient (W/m <sup>2</sup> K)	$\alpha$	thermal diffusivity (m <sup>2</sup> /s)
$j_p$	drift flux of nanoparticles	$\beta$	thermal expansion coefficient (1/K)
$k$	thermal conductivity coefficient (W/m K)	$\eta$	dimensionless distance
$Le$	Lewis number	$\theta$	non dimensional temperature
$N_b$	Brownian motion parameter	$\rho$	density (kg/m <sup>3</sup> )
$N_c$	conductivity parameter	$\phi$	volume fraction of nanoparticles
$N_r$	buoyancy ratio	$\psi$	stream function
$N_t$	thermophoresis parameter		
$Nu$	Nusselt number	<i>Subscript</i>	
$N_v$	viscosity parameter	$\infty$	outside the boundary layer
$P$	pressure (Pa)	$bf$	base fluid
$Pr$	Prandtl number	$nf$	nanofluid
$Ra$	Rayleigh number	$p$	nanoparticles
$S$	dimensionless stream function	$w$	wall
$T$	temperature (°C)	<i>Superscript</i>	
$u$	non dimensional velocity component in $x$ -direction (m/s)	'	differentiation respect to $\eta$
$v$	non dimensional velocity component in $y$ -direction (m/s)		

also found that the increase of the volume fraction of nanoparticles increased the thermal conductivity and the dynamic viscosity of the nanofluid.

Duangthongsuk and Wongwises [12] measured the thermal conductivity and the dynamic viscosity of water-based nanofluids, synthesized by 21 nm spherical nanoparticles of TiO<sub>2</sub>. The thermal conductivity and the dynamic viscosity of the samples were measured by using the hot wire method and the rotational rheometer at three selected working temperatures of 15 °C, 25 °C and 35 °C. The results of this study also indicate the Newtonian behavior of the samples. The results revealed that the thermal conductivity of the nanofluid was a decreasing function of the working temperature while the dynamic viscosity of the nanofluid was an increasing function of the working temperature.

Jeong et al. [13] studied the effect of the shapes of nanoparticles on the thermal conductivity and the dynamic viscosity of nanofluids. The authors synthesized two types of water-based nanofluids using nanopowers of rectangular (150 nm) and spherical (40 nm) zinc-oxide nanoparticles. The nanoparticles were well dispersed in the base fluid by the aid of the ultrasonic method. The dynamic viscosity and the thermal conductivity of the samples were measured at room temperature using the hot wire method and Ubbelohde viscometer, respectively. The results indicated that the thermal conductivity and the dynamic viscosity of the nanofluid containing rectangular nanoparticles were higher than those containing the spherical nanoparticles. However, the size of the spherical nanoparticles was much smaller than that of the rectangular ones.

Esfe et al. [14] examined the thermal conductivity and the dynamic viscosity of manganese-oxide water-based nanofluids at the room temperature. The nanofluid was synthesized using a powder of 40 nm spherical nanoparticles. The nanoparticles were dispersed in the water using the ultrasonic waves. The thermal conductivity and the dynamic viscosity of the samples were measured by using the hot wire method and Brookfield viscometer, respectively. The results showed that the increase of the volume

fraction of the nanoparticles increased the thermal conductivity and the dynamic viscosity of the nanofluid.

Agarwal et al. [15] studied the influence of the size of nanoparticles on the thermal conductivity and the dynamic viscosity of nanofluids. They synthesized two types of kerosene–Al<sub>2</sub>O<sub>3</sub> nanofluids using powders of spherical alumina nanoparticles with two sizes of 21 nm and 44 nm. The nanoparticles were well dispersed in the kerosene utilizing the ultrasonic waves. The thermal conductivity and the dynamic viscosity of the nanofluids were measured at room temperature using the hot wire and the Brookfield viscometer, respectively. The results indicated that the thermal conductivity and the dynamic viscosity of the samples of nanofluids containing smaller size of nanoparticles (21 nm particles) were higher than those containing larger size of nanoparticles (44 nm particles).

As a benchmark study, Buongiorno et al. [16] and Venerus et al. [17] have analyzed the effect of volume fraction of nanoparticles on the thermal conductivity and dynamic viscosity of nanofluids for different samples of nanofluids in 30 different laboratories around the world using different measurement methods. The results indicated that the thermal conductivity and dynamic viscosity of nanofluids are linear functions of the volume fraction of nanoparticles for low volume fractions of nanoparticles. Therefore, the linear function of concentration of particles for conductivity and viscosity is valid only in low concentrations of nanoparticles, and for high concentration of nanoparticles non-linear relations are required.

In the present study, the results of the measured thermal conductivity and dynamic viscosities of nanofluids reported by the previous researchers [11–15] are utilized to analysis the different aspects of nanoparticles and base fluids on the convective heat transfer of nanofluids.

Rana and Bhargava [18], using a homogenous model, examined natural convection heat transfer of nanofluids over a vertical flat plate. They investigated the effect of the presence of different types of nanoparticles (silver, copper, copper oxide, alumina, and

Download English Version:

<https://daneshyari.com/en/article/10260411>

Download Persian Version:

<https://daneshyari.com/article/10260411>

[Daneshyari.com](https://daneshyari.com)