Contents lists available at ScienceDirect

Journal of Biomechanics

journal homepage: www.elsevier.com/locate/jbiomech www.JBiomech.com

Short communication

Accuracy and precision of gait events derived from motion capture in horses during walk and trot



Jenny Katrine Boye^a, Maj Halling Thomsen^a, Thilo Pfau^b, Emil Olsen^{a,b,*}

^a University of Copenhagen, Faculty of Health and Medical Sciences, Department of Large Animal Sciences, Hojbakkegaard Allé 5, 2630 Taastrup, Denmark ^b The Royal Veterinary College, Department of Clinical Sciences and Services, Hawkshead Lane, North Mymms, AL9 7TA, United Kingdom

ARTICLE INFO

Article history: Accepted 16 December 2013

Keywords: Gait analysis Equine Locomotion Method comparison Stance Hoof-on Gait event Algorithm

ABSTRACT

This study aimed to create an evidence base for detection of stance-phase timings from motion capture in horses. The objective was to compare the accuracy (bias) and precision (SD) for five published algorithms for the detection of hoof-on and hoof-off using force plates as the reference standard.

Six horses were walked and trotted over eight force plates surrounded by a synchronised 12-camera infrared motion capture system. The five algorithms (A–E) were based on: (A) horizontal velocity of the hoof; (B) Fetlock angle and horizontal hoof velocity; (C) horizontal displacement of the hoof relative to the centre of mass; (D) horizontal velocity of the hoof relative to the Centre of Mass and; (E) vertical acceleration of the hoof. A total of 240 stance phases in walk and 240 stance phases in trot were included in the assessment. Method D provided the most accurate and precise results in walk for stance phase duration with a bias of 4.1% for front limbs and 4.8% for hind limbs. For trot we derived a combination of method A for hoof-on and method E for hoof-off resulting in a bias of -6.2% of stance in the front limbs and method B for the hind limbs with a bias of 3.8% of stance phase duration.

We conclude that motion capture yields accurate and precise detection of gait events for horses walking and trotting over ground and the results emphasise a need for different algorithms for front limbs versus hind limbs in trot.

© 2013 Elsevier Ltd. All rights reserved.

1. Introduction

Objective assessment of gait is an efficacious clinical tool in human medicine (Wren et al., 2011) and is rapidly evolving in veterinary medicine as a supplement to subjective assessment of lameness (Gillette and Angle, 2008; Keegan, 2007). Current techniques for lameness evaluation use inertial sensors placed on head, trunk and sacrum. Kinematics of the distal limb could be of further potential (Moorman et al., 2012; Olsen et al., 2013). Motion capture and force plates have the potential to aid assessment of deficits in neuro-motor control on a spinal or supraspinal level because spatial and temporal characteristics are primarily controlled through the spinal and supra-spinal neural pathways (Martinez et al., 2012; Rossignol and Frigon, 2011). Classification of movement as normal, or abnormal, can be based on a combination of subjective clinical examination and objective analysis of gait (Keegan et al., 2012; Lord et al., 2013; Wren et al., 2011).

Interpretation of data from gait and locomotion requires reproducible and evidence based techniques for data processing.

E-mail address: eo@sund.ku.dk (E. Olsen).

Reproducible and uniform segmentation into spatial and temporal characteristics (Lord et al., 2013) with force plates is considered the reference standard to detect timing of hoof-contact (Olsen et al., 2012; Sutherland, 2002; Witte et al., 2004).

The use of force plate arrays to segment data into strides often restricts locomotion to a straight line and limits the number of strides. Motion capture derived kinematics can be adapted for outdoors use (Hobbs et al., 2011) and potentially also used on a circle for detailed horse locomotion.

The force plate arrays are rarely portable, and thus, there is a need for accurate and precise evidence-based and shared algorithms for the detection of gait-events and kinematic characteristics based on motion capture signals alone.

Different approaches have been investigated estimating timings for foot-on/off from motion capture for humans on a treadmill and walking over ground (Zeni et al., 2008) and humans running (Leitch et al., 2011), cats walking over ground (Pantall et al., 2012) and horses during walk (Peham et al., 1999) and trot (Galisteo et al., 2010). However, none of these algorithms have been tested and compared for horses during walk and trot on front and hind limbs.

The aim of this study was to provide evidence for gait event detection algorithms based on motion capture. The objective was to compare accuracy (bias) and precision (standard deviation of



^{*} Corresponding author at: University of Copenhagen, Faculty of Health and Medical Sciences, Department of Large Animal Sciences, Hojbakkegaard Allé 5, 2630 Taastrup, Denmark. Tel.: +1 607 280 7518.

^{0021-9290/\$ -} see front matter @ 2013 Elsevier Ltd. All rights reserved. http://dx.doi.org/10.1016/j.jbiomech.2013.12.018

bias) for three algorithms developed for use in humans (Leitch et al., 2011; Zeni et al., 2008) and two developed for use in horses (Galisteo et al., 2010; Peham et al., 1999) using force plates as the reference standard.

2. Materials and methods

2.1. Animals

Six mares of mixed breeds (height: 1.45 ± 0.11 m; body mass: 450 ± 70 kg) from the teaching herd at the Royal Veterinary College (RVC) were included in the study. The procedures were approved by the ethics and welfare committee at the RVC and complied with the European Animal (Scientific Procedures) Act of 1986.

2.2. Data acquisition

The horses were walked (1.15 \pm 0.07 m/s) and trotted (2.59 \pm 0.17 m/s) across a 25 m runway with a 4.8 m data collection area with eight seamlessly embedded force plates (type 9287BA, Kistler Instrumente AG, Switzerland) sampling at 1000 Hz and a synchronised 12-camera infrared motion capture system (Oqus 3 and 5 series, Qualisys AB, Gothenburg, Sweden) sampling at 240 Hz.

Reflective half sphere markers with a diameter of 26 mm were placed on the horses at the right and left side over the estimated centre of mass (CoM) as described by Buchner et al. (2000), on each leg over the lateral hoof wall, at the proximal and distal dorsal hoof wall, laterally over the fetlock joint and laterally over the head of the fourth metacarpal/metatarsal bone (Fig. 1).



Fig. 1. Illustration of the marker placing on a horse from the trials. The markers on the Proximal metacarpus/metatarsus, on the fetlock joint and at hoof coronet are used in algorithm B for the detection of fetlock joint angle. The marker on the lateral hoof is used in method C and D. The distal dorsal hoof marker is used in method A, B and E to detect horizontal hoof speed and vertical acceleration.

3. Data processing

The motion capture files were pre-processed using dedicated commercial software (Qualisys Track Manager, Qualisys), converted into tab delimited text files (.tsv) with separate columns for x y and z coordinates and processed in MATLAB (R2011a, The MathWorks Inc., Natick, MA, USA). Hoof-on and hoof-off were extracted from the force plates using a semi-automated custom written MATLAB script and a threshold of 50 N for beginning and end of stance phase. Strides are defined as the time from a single hoof contacts the ground until that same hoof contacts the ground again and strides were discarded if they were outside or between force plates.

Hoof-on and hoof-off were extracted from motion capture using the following algorithms A-E (for further details, see supplementary table S1): Algorithm A (Peham et al., 1999) detects the beginning and ending of stance based on horizontal velocity of the distal dorsal hoof. The algorithm defines stance as the mode of fore-aft hoof velocity during each stride cycle. Galisteo et al. (2010) suggested algorithm B for use with video-based kinematics during over ground trot. Algorithm B is a modification of algorithm A (Peham et al., 1999) where hoof-on is detected using the absolute minimal fore-aft hoof velocity as a threshold. Hoof-off is defined as the angle of fetlock extension greater than 180°. However, several horses in this study never reached that angle, and the number of detected strides markedly improved by changing the threshold angle to 190°. Algorithm C and D (Zeni et al., 2008) were based on two slightly different analyses of maximal protraction and retraction of the limbs. In algorithm C the minimum and maximum peaks in horizontal displacement of the hoof relative to the marker at the CoM defined hoof-on/off. In algorithm D, the horizontal hoof velocity relative to the horizontal velocity of the marker at the CoM defined hoof-on/off as the frame where the relative velocity changed between positive and negative (zero crossing of the relative velocity). Algorithm E. modified after Leitch et al. (2011). defined hoof-on/off as the time when vertical acceleration of the hoof changed between positive and negative.

For algorithm B (hoof-on only), A and E, the distal dorsal marker on the hoof was used because it is closer to the pivot point of the hoof during break-over (Witte et al., 2004). Method C and D used the lateral hoof marker.

3.1. Statistics

Statistics were calculated using R (R Core Team, 2013) and the package MethComp (Carstensen et al., 2012) for agreement analysis corrected for replicate measurements per horse as described by Bland and Altman (2007) and Carstensen et al. (2008) with a correction for random effects of animal. Accuracy is defined as the mean difference between motion capture and force plates (bias) and precision as the standard deviation (SD) of the mean difference between motion capture and precision is the lowest towards minimising measurement error. Stance phases were removed if the duration of stance varied more than two standard deviations from the mean.

4. Results

A total of 240 stance phases in walk and 240 stance phases in trot were included in the analyses with 10 stance phases per limb per horse. A total of 14 outlier stance phases were removed for walk and 20 outlier stance phases were removed for trot. Accuracy and precision for walk and trot are summarised in Table 1. For walk, algorithm D had the best precision in all gait events except for hind limb hoof-on. Algorithm D is the second most accurate Download English Version:

https://daneshyari.com/en/article/10432458

Download Persian Version:

https://daneshyari.com/article/10432458

Daneshyari.com