



Original papers

An IoT based smart irrigation management system using Machine learning and open source technologies

Amarendra Goap^{a,b,*}, Deepak Sharma^b, A.K. Shukla^b, C. Rama Krishna^a^a National Institute of Technical Teachers Training and Research (NITTTR), Chandigarh 160019, India^b CSIR-Central Scientific Instruments Organisation, Chandigarh 160030, India

ARTICLE INFO

Keywords:

Irrigation management system
IoT
Precision agriculture
Prediction algorithm
Machine learning
Evapotranspiration

ABSTRACT

The scarcity of clean water resources around the globe has generated a need for their optimum utilization. Internet of Things (IoT) solutions, based on the application specific sensors' data acquisition and intelligent processing, are bridging the gaps between the cyber and physical worlds. IoT based smart irrigation management systems can help in achieving optimum water-resource utilization in the precision farming landscape. This paper presents an open-source technology based smart system to predict the irrigation requirements of a field using the sensing of ground parameter like soil moisture, soil temperature, and environmental conditions along with the weather forecast data from the Internet. The sensing nodes, involved in the ground and environmental sensing, consider soil moisture, soil temperature, air temperature, Ultraviolet (UV) light radiation, and relative humidity of the crop field. The intelligence of the proposed system is based on a smart algorithm, which considers sensed data along with the weather forecast parameters like precipitation, air temperature, humidity, and UV for the near future. The complete system has been developed and deployed on a pilot scale, where the sensor node data is wirelessly collected over the cloud using web-services and a web-based information visualization and decision support system provides the real-time information insights based on the analysis of sensors data and weather forecast data. The system has a provision for a closed-loop control of the water supply to realize a fully autonomous irrigation scheme. The paper describes the system and discusses in detail the information processing results of three weeks data based on the proposed algorithm. The system is fully functional and the prediction results are very encouraging.

1. Introduction

Water scarcity is already affecting a part of the world and the situation is getting worse over time due to the increasing world population and fresh water demands. The current world population is around 7.2 billion and it is expected to be more than 9 billion by 2050 (United Nations, 2013). The agriculture sector, particularly irrigation, consumes a major portion of the freshwater. Due to lack of cost-effective intelligent irrigation systems, developing countries are consuming more water in contrast to the developed countries for achieving the same yield. For example, India has approximately 4% of world's freshwater resources to serve 17% of the world population; however, it takes 2–4 times more water for some of its major agri-produce in comparison to the other countries like China, USA (G. o. I. NITI Aayog, 2015). Therefore, there is a dire need to come up with advanced technologies based smart strategies and systems for effective utilization of fresh water.

Gubbi et al. (2013) discussed an IoT framework with cloud centric storage, processing and analysis of the data received from ubiquitous sensors along with a decision support interface. Cruz et al. (2018) suggested a reference model for an IoT middleware platform that would support intelligent IoT applications. IoT based solutions are proving very helpful in many dimensions of the agricultural landscape (Sharma et al., 2016), and these intelligent solutions could also be fruitful in smart irrigation with optimum utilization of water. Soil moisture, precipitation, and evaporation are the essential parameters for designing a smart irrigation system.

The precipitation and evaporation are important key factors, which influence the soil moisture. In geography and climatology, the wetness of soil is estimated by the proportion of annual (or monthly) precipitation and evaporation (Shang et al., 2007). Daily soil moisture can also be evaluated by the ratio of daily precipitation and evaporation in the above perspective. Precipitation is directly accessible in the routine weather reports; nonetheless, evaporation can be calculated using other

* Corresponding author at: CSIR-Central Scientific Instruments Organisation, Chandigarh 160030, India.

E-mail address: agoap@csio.res.in (A. Goap).

metrological essentials. For evaporation, we use an empirical model given by Penman (Chen and Chen, 1993)

$$E_T \propto (E_h + E_m) \quad (1)$$

The entire evaporation (E_T) depends on the thermodynamic evaporation (E_h) and the dynamic evaporation (E_m), where E_m depends upon the velocity of the land storm, air temperature, relative humidity of the air and UV radiation.

To achieve water saving, irrigation system frameworks have been proposed based on various techniques, e.g., thermal imaging, Crop Water Stress Index (CWSI), direct soil water measurements, etc. Thermal imaging is a prominent technique for irrigation management and it is based on the shade temperature distribution of the plant. In this framework, the status of the water in the plant is checked over continuous intervals and irrigation is planned in view of the shade temperature distribution of the plant (Wang et al., 2010). In addition, CWSI based framework has been proposed for irrigation scheduling of the crops for efficient use of water. The observation of CWSI was first characterized more than 30 years ago (Idso et al., 1981). O'Shaughnessy and Evett (2010) proposed an automatic irrigation scheduling based on direct soil water measurement that utilizes water proficiently over manual irrigation system. Allen et al. (1998) suggested evapotranspiration (ET) based approach, which is an important parameter to decide crop irrigation needs influenced by climate parameters, e.g., solar radiation, relative humidity, temperature, wind velocity, and crop features such as phase of the crop growth, assortment and plant density, properties of soil, nuisance, and disease control. ET-based frameworks can save water up to 42% over time-based water irrigation scheduling (Davis and Dukes, 2010). Davis et al. (2009) conducted the investigations in Florida and verified that ET-based watering scheduling controllers are more beneficial in term of cost, size and labor requirement for irrigation. ET-based irrigation system uses much less water as compared to scheduled practices. Viani et al. (2017) proposed a fuzzy logic-based decision support system based on farmer's experience with the understanding of crop condition. This system provides more water saving over single-threshold and multi-threshold based irrigation scheduling. Gutiérrez et al. (2014) proposed an automated irrigation system using a wireless sensor network and GPRS module to save water in irrigation. In this system, a network of soil moisture sensors with controller has been installed in a crop field for real-time monitoring and irrigation control. Gill et al. (2006) suggested a method for soil moisture prediction using support vector machines based on air temperature, relative air humidity and soil temperature.

Jaguey et al. (2015) developed irrigation sensor based on smart phone. For sensing soil moisture, the digital camera of smart phone is used to process RGB to gray for estimation of ratio between wet and dry area of soil. The ratio of wetness and dryness is transmitted via gateway to water motor controller. A Mobile Application (APP) is developed to control sensor activity (like wakeup) and to set sensor in sleep mode. Goldstein et al. (2017) proposed irrigation recommendations based on machine learning algorithm with support of agronomist's encysted knowledge. It was found that the best regression model was Gradient Boosted Regression Trees (GBRT) with 93% accuracy in prediction of irrigation plan/recommendation. The developed model is helpful to the agronomist's irrigation management. Roopaei et al. (2017) proposed an intelligent irrigation monitoring system based on thermal imaging. The proposed technique uses thermal imaging camera mounted on Drone. An algorithm is developed using images processing techniques for identification of water requirement, Leaf water potential, and non-uniform irrigation, which are used for irrigation monitoring.

Majority of the earlier irrigation systems do not consider the weather forecasting information (e.g., precipitation) while making irrigation decisions. It leads to a wastage of fresh water, energy and loss of crop growth (due to excess water) when a rain is followed immediately by the watering of the crop. To handle such cases, IoT based solutions can provide a better decision support for irrigation by utilizing weather forecasting information (e.g., precipitation) from the

Internet. Further, the accuracy of weather forecasting is improving due to the advancement of satellite imagery technology.

For effective and optimum utilization of fresh water in irrigation, it becomes essential to develop the smart irrigation systems based on dynamic prediction of soil moisture pattern of the field and precipitation information of upcoming days. This paper presents an intelligent system that predicts soil moisture based on the information collected from the sensors deployed at the field and the weather forecast information available on the Internet. The field data has been collected through a self-designed sensor node. The server-side software has been developed with node side connectivity along with information visualization and decision support features. A novel algorithm has been developed for soil-moisture prediction, which is based on Machine Learning techniques applied on the sensor node data and the weather forecast data. The algorithm shows improved accuracy and less error. The proposed approach could help in making effective irrigation decisions with optimum water usage.

2. Methods/Techniques used

Prediction of soil moisture is vital for effective irrigation management system. The estimation of soil moisture depends upon evapotranspiration Hargreaves and Samani (1985) developed a method based on temperature and extra-terrestrial radiation to estimate ET_0 . It is expressed as

$$ET_0 = 0.0023R_a \left(\frac{T_{max} + T_{min}}{2} + 17.8 \right) \sqrt{T_{max} - T_{min}} \quad (2)$$

where ET_0 = reference evapotranspiration (mm/day); T_{max} and T_{min} = maximum temperature and minimum temperature ($^{\circ}\text{C}$) and R_a = extra-terrestrial radiation ($\text{MJ m}^{-2} \text{ day}^{-1}$).

Ritchie developed another method for estimation of ET_0 (Jones and Ritchie, 1990) based on temperature and solar radiation. It is expressed as

$$ET_0 = \alpha_1 \cdot [3.87 \times 10^{-3} \cdot R_s \cdot (0.6T_{max} + 0.4T_{min} + 29)] \quad (3)$$

where ET_0 = reference evapotranspiration (mm/day); T_{max} and T_{min} = maximum and minimum temperature ($^{\circ}\text{C}$) and R_s = solar radiation ($\text{MJ m}^{-2} \text{ day}^{-1}$). When

$$\left. \begin{array}{ll} 5 < T_{max} \leq 35 \text{ }^{\circ}\text{C} & \alpha_1 = 1.1 \\ T_{max} > 35 \text{ }^{\circ}\text{C} & \alpha_1 = 1.1 + 0.05(T_{max} - 35) \\ T_{max} < 5 \text{ }^{\circ}\text{C} & \alpha_1 = 0.01 \exp[0.18(T_{max} + 20)] \end{array} \right\} \quad (4)$$

Cobaner (2011) developed evapotranspiration estimation method based on Neuro-Fuzzy (NF) inference and found that the NF model (based on solar radiation, air temperature, and relative humidity) exhibits better accuracy than the combination of solar radiation, air temperature and wind speed.

From state of art, it has been analyzed that prediction of soil moisture is possible using sensors placement at the field and weather forecasted data. So, we have considered evaporation of soil moisture based on air temperature, air relative humidity, soil temperature, and radiation. The parameters are considered for analyzing the soil moisture drain (change/difference) pattern based on the recorded data of soil moisture.

An IoT based architecture (Fig. 1) has been proposed to collect, transmit and process the physical parameters (soil moisture, air temperature, air relative humidity, soil temperature, and radiation) of farming land along with the weather forecast information to manage the irrigation efficiently.

An algorithm based on a combination of supervised and unsupervised machine learning techniques (block diagram shown in Fig. 3 and pseudocode is discussed in Section 3.2.1) has been developed using Support Vector Regression (SVR) and k -means clustering for estimation of difference/change in soil moisture due to weather conditions. It gives good accuracy and less Mean Squared Error (MSE) (Theobald, 1974; "Mean Squared Error, 2018") in the prediction of the soil moisture of

Download English Version:

<https://daneshyari.com/en/article/11012836>

Download Persian Version:

<https://daneshyari.com/article/11012836>

[Daneshyari.com](https://daneshyari.com)