Accepted Manuscript

Packing density of mortar containing polypropylene, carbon or basalt fibres under dry and wet conditions

L.G. Li, H.X. Zhuo, J. Zhu, A.K.H. Kwan

PII: S0032-5910(18)30841-6

DOI: doi:10.1016/j.powtec.2018.10.005

Reference: PTEC 13779

To appear in: Powder Technology

Received date: 7 May 2018
Revised date: 23 August 2018
Accepted date: 1 October 2018

Please cite this article as: L.G. Li, H.X. Zhuo, J. Zhu, A.K.H. Kwan, Packing density of mortar containing polypropylene, carbon or basalt fibres under dry and wet conditions. Ptec (2018), doi:10.1016/j.powtec.2018.10.005

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



ACCEPTED MANUSCRIPT

Packing density of mortar containing polypropylene, carbon or basalt fibres under dry and wet conditions

L.G. Li^{1*} , H.X. $Zhuo^{1}$, J. Zhu^{1} and A.K.H. $Kwan^{2}$

¹Guangdong University of Technology, Guangzhou, China.

²The University of Hong Kong, Hong Kong, China.

Download English Version:

https://daneshyari.com/en/article/11263037

Download Persian Version:

https://daneshyari.com/article/11263037

<u>Daneshyari.com</u>