

The 12th International Conference on Combustion & Energy Utilisation – 12ICCEU

Towards high-fidelity multi-scale simulation of spray atomization

L. Zhou^{1,*}, J. Xia¹, J. Shinjo¹, A. Cairns¹, L. Cruff², H. Blaxill²

*1. Department of Mechanical, Aerospace and Civil Engineering & Institute of Energy Futures,
Brunel University London, Uxbridge UB8 3PH, UK;*

2. MAHLE Powertrain LLC, 41000 Vincent Court, Novi, Michigan 48375-1921, US

Abstract

Liquid jet atomization is an important process in internal combustion engine. This paper presents a multi-scale approach coupling a Eulerian interface-tracking method and a Lagrangian particle tracking method to simulate liquid atomization processes. This method aims to capture the complete spray atomization process, particularly primary and second breakup, paving the way for high-fidelity simulation of spray atomization in the dense spray zone and spray combustion in the dilute spray zone. The Eulerian method is based on the Coupled Level-Set and Volume-of-Fluid (CLSVOF) for interface tracking, which can accurately simulate the primary breakup process. For the coupling approach, the Eulerian method only describes large droplet and ligament structures, while small-scale droplet structures are removed from the resolved Eulerian description and transformed into Lagrangian point-source droplets. The Lagrangian method is thus used to track small droplets and their further secondary breakup and collision. In this study, two-dimensional simulation of liquid jet atomization is performed. We will analyse Lagrangian-droplet formation and motion due to the coupling and the atomization characteristics using the multi-scale approach.

© 2015 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

Peer-review under responsibility of the Engineering Department, Lancaster University

Keywords: multi-scale, CLSVOF, point particle, spray atomization

1. Introduction

Liquid jet atomization plays a significant role in achieving efficient and clean combustion in internal combustion engines. It is a complex process, which can be divided into three regimes [1,2]. The first is the liquid core zone in which the liquid area is very dense and appears as a continuum fluid; the second is the dispersed flow zone where the liquid can be approximated as disperse particles; the last is the transition zone. In order to simulate accurately and efficiently the spray process in different zones, some efforts have been made in recent years and some multi-scale methods have been proposed, such as ELSA [3], the CLSVOF (or the Volume-of-Fluid method (VOF)) and Lagrangian particle-tracking methods [4-7]. Eulerian methods like VOF, Level Set and CLSVOF have been used to track or capture liquid-gas interfaces in the primary breakup regime (the liquid core zone), and the Lagrangian droplet-tracking

* Corresponding author. Tel.: +44 7404 967256

E-mail address: lei.zhou@brunel.ac.uk

method has been used to trace dispersed small droplets in the dilute spray zone. The coupling procedure between the two methods is the focus of this paper.

Proposing a multi-scale method for two-phase flow is challenging. Our main contribution of this paper is to demonstrate the achievement of the transformation of little droplets from a Eulerian structure to a Lagrangian particle and the performance of the coupled method based on the combination of CLSVOF (Eulerian) and KIVA (Lagrangian) in simulating a liquid jet process.

2. Numerical methods

2.1 Solvers

A coupled Level Set (LS) and Volume of Fluid (VOF) method CLSVOF [8] is used to capture and evolve gas-liquid interfaces. Gas-liquid interfaces are captured by the level-set method. To improve the volume conservation, a modified VOF method called the Multi-interface Advection and Reconstruction Solver (MARS) is incorporated. The detailed numerical method and its validation can be found in [8]. We use KIVA [9] as the Lagrangian solver, in which droplet velocity in the computation domain is determined by the drag force $F_{i,d}$ on the droplet, which is in turn determined by the relative velocity between the liquid droplet and the gas phase.

2.2 Eulerian-Lagrangian droplet transition

The droplet transition from a Eulerian structure to a Lagrangian particle is divided into three steps [4]. First, isolated droplets need to be identified and their mass, velocity and temperature are determined. In our work, we use a neighbour searching algorithm to identify an isolated liquid structure [4]. Second, we set up the conversion criteria for the Eulerian-Lagrangian transition. Whether or not a Eulerian structure will be transformed into a Lagrangian particle is determined by its critical volume and the critical length of a thin ligament. In this work, we use two different grids, one for CLSVOF and another for KIVA. The critical volume is set to be the KIVA cell volume in order to meet the requirement that the droplet dimension should be (much) smaller than the cell size in a Lagrangian point-particle method. Therefore the conversion criterion is $V_{eulerian} < V_{kivagrid}$, where $V_{eulerian}$ and $V_{kivagrid}$ are the Eulerian droplet volume and the KIVA grid cell volume, respectively. In order to accurately calculate the further breakup process of a largely deformed thin ligament with the Eulerian description despite that the Eulerian droplet volume meets the first criterion, the second criterion is $\alpha \geq R_{max}/\max\left[\Delta x, \left(\frac{3}{4\pi}V_{eulerian}\right)^{1/3}\right]$.

where R_{max} is the maximum distance from the edge of a Eulerian droplet structure to the centre of mass of the Eulerian droplet. The criterion parameter α is equal to 4. Third, remove the isolated droplets that meet the conversion criteria from the Eulerian description. At the same time the removed droplets are transformed to Lagrangian particles with determined droplets mass and velocity.

3. Results

In this paper, the two-dimensional computational domain is 0.6cm x 0.3cm with grid numbers 300 x 150 for CLSVOF and 150 x 75 for KIVA, respectively. The nozzle diameter is 0.016cm and the injection velocity is 100m/s. The liquid fuel is n-Heptane. Numerical results have been obtained for this case by using the Eulerian CLSVOF method [8], the Lagrangian point-particle tracking method in KIVA, and the hybrid Eulerian-Lagrangian multi-scale method developed for the present study. The Eulerian approach produces direct simulation results, which can be used as benchmark. The Lagrangian method is model based. The KH-RT breakup model is used in KIVA. The developed numerical method is a high-fidelity

Download English Version:

<https://daneshyari.com/en/article/1510807>

Download Persian Version:

<https://daneshyari.com/article/1510807>

[Daneshyari.com](https://daneshyari.com)