



Optimization of latent heat storage in solar air heating system with vacuum tube air solar collector

Ciril Arkar, Sašo Medved*

University of Ljubljana, Faculty of Mechanical Engineering, Askerčeva 6, 1000 Ljubljana, Slovenia

Received 3 May 2014; received in revised form 25 August 2014; accepted 10 October 2014

Available online 9 November 2014

Communicated by: Associate Editor Halime Paksoy

Abstract

This paper presents the design and modelling of the heat transfer of a solar air heating system, which consists of a vacuum tube air solar collector (SC) and latent heat thermal energy storage (LHTES), and a parametric analysis of the performance of this system. LHTES is a form of short-term daily storage that stores the SC heat during the day and releases it into the building during the night. Especially in low energy buildings with a high share of passive heating, this can significantly improve the utilization of solar energy for heating. The design of concentric-tube LHTES was optimized regarding the air temperature at the exit of LHTES during the day and the peak shift of heat supply. The results showed that optimal mass of PCM in LHTES is 150–200 kg/m² and the optimal air flow-rate is 40 m³/h per m² of the SC aperture area. The analysis of the system performance at different levels of daily solar irradiation has shown that 54–67% of the heat produced by solar air heating system in daytime can be delivered during the night time for building heating. © 2014 Published by Elsevier Ltd.

Keywords: Latent heat storage; Phase change material; Vacuum tube air solar collector; Solar heating

1. Introduction

A significant part of the final energy in buildings is consumed to provide adequate living comfort. In the EU, this share is close to 40%. The revised Energy Performance of Buildings Directive 2010/31/EU foresees that after 2020 almost exclusively nearly zero energy buildings (nZEB) will be built, as a result of European climate and energy policy. Energy in nZEB has to be largely provided by renewable energy sources (RES), as energy produced on the building envelope or its vicinity. Regarding heat and cold supply, solar thermal systems and free cooling systems could have a significant role in nZEB. An important element of these systems is heat storage, as it reduces the time mismatch

between the availability of energy source and the actual energy need for heating and cooling.

In recent years, a great deal of research of latent heat thermal energy storages (LHTES) in systems for free cooling of buildings has been conducted (Waqas and Ud Din, 2013). These systems utilize the coolness of ambient air during the night to cool the building during the day. Studies have shown that these systems can be very effective in reducing energy use for cooling (Takeda et al., 2004; Arkar and Medved, 2007). In energy efficient buildings built for the American Solar Decathlon competition (Rodriguez-Ubinas et al., 2012), the use of PCM and LHTES predominates in attempts to improve the energy performance of the buildings. From the presented cases, it can be identified that in these buildings different PCMs were used for both the heating and the cooling of a building. As shown by Medved and Arkar (2008), the optimum

* Corresponding author.

Nomenclature

A	cross-section (m^2)	u	surrounding wind speed (m/s)
A_{ap}	aperture area of SC (m^2)	U	thermal transmittance ($\text{W}/(\text{m}^2 \text{K})$)
Bi	Biot number (–)	\dot{V}	air volume flow-rate (m^3/h)
c_1	heat loss coefficient ($\text{W}/(\text{m}^2 \text{K})$)	x	axial coordinate (m)
c_2	temperature dependence of the heat loss coefficient ($\text{W}/(\text{m}^2 \text{K}^2)$)	<i>Greek symbols</i>	
c_3	wind speed dependence of the heat loss coefficient ($\text{J}/(\text{m}^3 \text{K})$)	θ	incidence angle ($^\circ$)
c_4	long-wave irradiance dependence of the heat loss coefficient ($\text{W}/(\text{m}^2 \text{K})$)	θ'	heating or cooling rate (K/s)
c_5	effective thermal capacity ($\text{J}/(\text{m}^2 \text{K})$)	η	instantaneous efficiency (–)
c_6	wind speed dependence of the zero loss efficiency (s/m)	η_0	zero loss SC efficiency (–)
c_{eff}	effective heat capacity ($\text{J}/(\text{kg K})$)	ϕ	daily utilizability factor (%)
COP	coefficient of performance (–)	ρ	density (kg/m^3)
c_p	specific heat ($\text{J}/(\text{kg K})$)	σ	Stefan–Boltzman constant ($\text{W}/(\text{m}^2 \text{K}^4)$)
D	tube diameter (m)	$(\tau \cdot \alpha)_{en}$	effective transmittance–absorptance product at normal incidence (–)
E	electric energy (J)	<i>Subscripts, superscripts</i>	
E_L	long-wave irradiance (W/m^2)	a	ambient
F	efficiency factor of SC (–)	b	beam
G	global solar radiation on SC plane (W/m^2)	cs	clear sky
h	heat transfer coefficient ($\text{W}/(\text{m}^2 \text{K})$)	d	diffuse
H	daily solar irradiation ($\text{kW h}/(\text{m}^2 \text{day})$)	eff	effective
k	thermal conductivity ($\text{W}/(\text{m K})$)	exp	experimental
K_θ	incidence angle modifier (–)	hs	heat storage
L	latent heat of melting or solidification (J/kg), LHTES length (m)	i	inlet, inner
m	mass (kg)	in	indoor
\dot{m}	mass flow-rate (kg/s)	m	mean
m'_{pcm}	mass of PCM per SC area (kg/m^2)	$night$	night time
P	perimeter (m)	num	numerical
Q	delivered heat (J)	o	outlet, outer
q	share of delivered heat (–)	p	peak
\dot{Q}	useful power from SC, heat flux (W)	pcm	phase change material
r	radial coordinate (m)	pos	partly overcast sky
T	temperature ($^\circ\text{C}$)	s	solid
t	time (s)	sc	solar collector
		ti	thermal insulation

PCM melting temperature in LHTES for free cooling in places with Continental and Mediterranean climate is between 22°C and 28°C , and this may also be suitable for LHTES in solar heating systems. Furthermore, in some other free cooling studies (Takeda et al., 2004; Zalba et al., 2004; Lazaro et al., 2009; Dolado et al., 2011; Raj and Velraj, 2011), the use of PCM with melting temperatures higher than 22°C can be found. As the operation time of a free-cooling system is limited to the summer time, the cost effectiveness of its main element (i.e. latent heat storage) could be improved if this element is integrated into a heating system, for example in a solar air heating system. Using LHTES for both the heating and cooling of the

building significantly improves the economics of free-cooling and solar air heating systems.

Alkilani et al. (2011) recently presented an overview of heating systems, containing air SC and heat storage. They showed that, in addition to systems for drying crops and greenhouse heating, there are many applications for heating of the buildings. They also determined that research and applications with LHTES have been prevalent in the recent period. Saman et al. (2005) presented and analysed the performance of the building heating system with roof-integrated SC and LHTES with plates of PCM. They analysed the PCM with a melting point of 28°C . They analysed the influence of different but constant inlet air

Download English Version:

<https://daneshyari.com/en/article/1549791>

Download Persian Version:

<https://daneshyari.com/article/1549791>

[Daneshyari.com](https://daneshyari.com)