

Contents lists available at ScienceDirect

Data in Brief

journal homepage: www.elsevier.com/locate/dib

Data Article

Data of cost-optimality and technical solutions for high energy performance buildings in warm climate



Ilaria Zacà^a, Delia D'Agostino^b, Paolo Maria Congedo^{a,*}, Cristina Baglivo^a

^a Department of Engineering for Innovation, University of Salento, Lecce 73100, Italy

^b Energy Efficiency and Renewables Unit, Institute for Energy and Transport (IET), Joint Research Centre (JRC),

European Commission, Ispra, Varese, Italy

ARTICLE INFO

Article history: Received 28 May 2015 Accepted 29 May 2015 Available online 12 June 2015

ABSTRACT

The data reported in this article refers to input and output information related to the research articles entitled Assessment of cost-optimality and technical solutions in high performance multiresidential buildings in the Mediterranean area by Zacà et al. (Assessment of cost-optimality and technical solutions in high performance multi-residential buildings in the Mediterranean area, in press.) and related to the research article Cost-optimal analysis and technical comparison between standard and high efficient mono residential buildings in a warm climate by Baglivo et al. (Energy, 2015, 10.1016/j.energy.2015.02.062, in press).

© 2015 Elsevier Inc. This is an open access article under the CC BY license (http://creativecommons.org/licenses/by/4.0/).

The European policy framework is focused on reducing energy consumption in the building sector. The recast of EU (European Union) Directive on EPBD (Energy Performance of Buildings) requires nZEBs (nearly zero energy buildings) as the building target from 2018 onwards and the establishment of cost optimal levels of minimum energy performance requirements in buildings.Zacà et al. [1] shows a methodology to assess energy and cost effectiveness in new buildings located in the Mediterranean

* Corresponding author. Tel.: + 39 832 297750.

DOI of original article: http://dx.doi.org/10.1016/j.enbuild.2015.04.038

E-mail address: paolo.congedo@unisalento.it (P. Maria Congedo).

http://dx.doi.org/10.1016/j.dib.2015.05.015

^{2352-3409/© 2015} Elsevier Inc. This is an open access article under the CC BY license (http://creativecommons.org/licenses/by/4.0/).

area. Several energy efficiency technical variants are applied to a multi residential reference building selected as a representative model of the national building stock.Baglivo et al. [2] presents the results of the application of a methodology to identify cost-optimal levels in new residential buildings located in a warm climate. Mono-residential buildings have been considered as virtual reference buildings in this study. Different energy efficiency measures have been selected for the envelope and the systems.

High performance of different solutions can be obtained in summertime by using lighter and thinner walls, although the superficial mass of the external wall is important to obtain the best performance in the hot-summer Mediterranean climate [3–5]. Heat transfer through windows represents a significant proportion of the energy used to cover both heating and cooling requirements [6]. Data related to building input values are supplied for mono and multi-family units and the main values of HVAC and RES systems are provided. The decision to introduce HVAC [7] and RES systems [8,9] as variants derived from the necessity to reduce energy consumption maintaining a high level of comfort in all the building rooms.

Subject area	Physics
More specific subject area	Describe narrower subject area
Type of data	Table
How data was acquired	TABULA project (Building typology brochure Italy) [10,11], technical datasheets [4], Puglia price list, market surveys, ISTAT surveys, software ProCasaClima 2015 [12]
Data format	Raw
Experimental factors	No pretreatment of samples was performed
Experimental features	Several energy efficiency technical variants are applied to residential reference buildings selected as representative model of the national building stock. Primary energy consumption and global costs are evaluated in a number of configurations to derive the cost-optimal solution.
Data source location Data accessibility	Lecce–Italy, Mediterranean climate [3] Data is provided in Supplementary materials directly with this article

Specifications table

Value of the data

- A methodology is applied to obtain cost-optimal levels in a residential reference buildings located in a warm climate.
- Energy performance is assessed for different packages of energy efficiency technical measures.
- Global costs are evaluated to identify the cost-optimal solution.

Data, experimental design, materials and methods

The data in this data article has been generated by following these main steps:

- 1) Definition of the reference buildings and characterization of its envelope and systems;
- 2) Establishment of technical variants and combinations for energy performance assessment;
- 3) Global costs calculations.

This method allowed the identification of measures able to optimize the energy performance of the selected reference buildings. Cost-optimal and cost effective levels are finally derived and discussed for the cases study.

The reference buildings are based on solutions defined within TABULA project (virtual buildings) (Table S1), including commonly used material and systems. The location is the city of Lecce—Italy, characterized by a Mediterranean climate.

Heating and cooling loads are obtained using the software ProCasaClima2015. The developed tool uses hourly weather data provided by the Italian Heat Technology Committee to implement dynamic simulations. This software is able to perform energy calculations to evaluate buildings energy

Download English Version:

https://daneshyari.com/en/article/175131

Download Persian Version:

https://daneshyari.com/article/175131

Daneshyari.com