Contents lists available at ScienceDirect

Electrochemistry Communications

journal homepage:<www.elsevier.com/locate/elecom>

Short communication

Monitoring charge transfer at polarisable liquid/liquid interfaces employing time-resolved Raman spectroelectrochemistry

D. Ibañez ^a, D. Plana ^b, A. Heras ^a, D.J. Fermín ^b, A. Colina ^{a,*}

^a Department of Chemistry, Universidad de Burgos, Pza. Misael Bañuelos s/n, E-09001 Burgos, Spain b School of Chemistry, University of Bristol, Cantocks Close, Bristol BS8 1TS, UK

article info abstract

Article history: Received 11 February 2015 Accepted 23 February 2015 Available online 3 March 2015

Keywords: Liquid/liquid interfaces Ion transfer Electron transfer In-situ Raman spectroscopy

In-situ Raman spectroscopy is implemented for the first time to monitor dynamic charge transfer processes at polarisable interfaces between two immiscible electrolyte solutions (ITIES) in real time. A custom-designed new electrochemical cell is described which allows probing the Raman signals of ferroin ions as a function of the potential applied across the water|1,2-dichlorobenzene (DCB) interface. This approach is also used for investigating the heterogeneous electron transfer reaction involving dimethylferrocene in DCB and potassium hexacyanoferrate (II/III) in the aqueous phase. The evolution of the Raman signals during potentiodynamic measurements is recorded in real-time with a resolution of a few seconds.

© 2015 Elsevier B.V. All rights reserved.

1. Introduction

In-situ spectroscopic techniques have revealed a wealth of information about the structure and reaction mechanisms taking place at polarisable interfaces between two immiscible electrolyte solutions (ITIES) [\[1\].](#page--1-0) The complexity of probing interfacial processes lies on the buried nature of these interfaces, requiring the coupling of spectroscopic signals with potential perturbations [\[2](#page--1-0)–6], or the use of non-linear optical techniques [7–[9\].](#page--1-0) Although Raman spectroscopy has already been used to probe interfacial confined species, the majority of the work has been carried out in the absence of external polarisation [\[10,11\].](#page--1-0) More recently, Raman responses as a function of the Galvani potential difference across the ITIES have been reported under stationary conditions [\[12,13\]](#page--1-0). In this report, we described the first in-situ Raman studies at the polarisable ITIES under potentiodynamic conditions in real time. A purposely built low-volume four-electrode cell is presented which enables monitoring Raman responses associated with ion transfer and heterogeneous electron transfer across the water|1,2-dichlorobenzene (DCB) interface. A clear correlation between spectroscopic and electrochemical responses is shown, demonstrating a high level of sensitivity and time-resolution.

2. Material and methods

All reagents employed were analytical grade or higher. The organic phase supporting electrolyte was bis(triphenylphosphoranylidene) am-monium tetrakis(pentafluoro) phenylborate (BTPPATPBF₂₀) [\[14\].](#page--1-0) In order to facilitate the use of low volumes, DCB electrolyte solution was gelled employing high molecular weight polyvinylchloride (PVC) following the methodology reported in [\[15\].](#page--1-0) The aqueous electrolyte solutions were prepared using high purity de-ionised water (MilliQ gradient A10 system, Millipore).

Electrochemical measurements were carried out at room temperature using an AUTOLAB PGSTAT20 potentiostat (Eco Chemie Autolab) in fourelectrode mode. The potential scale in this work corresponds to the potential difference between the reference electrode in the aqueous phase (so-called sensor electrode) and the reference electrode in the organic phase ($Δφ = E_{ref,water} - E_{ref,organic}$). Raman spectra were obtained using a Confocal Raman Voyage (BWTEK). A laser wavelength of 532 nm with a power of 15 mW was employed to obtain the spectra, using a $20\times$ objective. Further details about the dynamic spectroelectrochemical Raman system have been previously reported [\[16,17\]](#page--1-0). An XYZ piezoelectric positioner (Newport 271) controlled by a Newport motion controller (Newport, ESP 301) was used to focus the laser beam with micrometric resolution.

A schematic representation of the polytetrafluoroethylene (PTFE) built 4-electrode cell is shown in [Fig. 1.](#page-1-0) The organic phase compartment (1) was 7 mm in depth and 3 mm in diameter, while the aqueous electrolyte compartment (3) consisted of a cylindrical hole of 6 mm diameter

 C rossMark

trochemistry

Corresponding author. Tel.: +34 947258817; fax: +34 947258831. E-mail address: acolina@ubu.es (A. Colina).

Fig. 1. Schematic design of the 4-electrode cell for dynamic Raman spectroelectrochemistry, featuring: the organic gel compartment (1), O-ring (2), the aqueous electrolyte compartment (3), and quartz window (4).

and 6 mm long. The O-ring (2) was used to prevent electrolyte leakage while the reference and counter electrodes in both phases were placed through small holes at the side of the corresponding compartments. This configuration ensured a clear optical path for the laser through the quartz window (4) on top of the cell.

3. Results and discussion

3.1. [Fe(phen)₃]^{2 +} transfer across the water|DCB interface

The spectroelectrochemical cell composition used was: Ag (s) | AgCl (s) | 1 mM BTPPACl + 10 mM LiCl (aq) | 18 mM BTPPATPBF₂₀ + 2% (w/w) PVC $(DEB/THF, 50%)$ || 25 mM $[Fe(phen)_3]^2$ ⁺ + 0.1 M LiCl (aq) | AgCl (s) | Ag (s); where the double bar denotes the polarisable interface. Two consecutive linear sweep voltammograms recorded at 0.005 V s $^{-1}$, focusing the laser in the aqueous and in the organic phases, are displayed in [Fig. 2a](#page--1-0). The current peak located at $\Delta\phi \sim +0.30$ V is associated with the transfer of $[Fe(phen)_3]^2$ ⁺ from the aqueous to the organic electrolyte. Characteristic Raman spectra recorded during the potential cycle while the laser is focused in the aqueous side of the interface are shown in [Fig. 2](#page--1-0)b. The two intense Raman peaks at 1457 and 1517 cm⁻¹ correspond to in-plane stretching vibration of the phenanthroline ring [\[18\]](#page--1-0). [Fig. 2c](#page--1-0) shows a similar set of spectra but focusing the laser in the organic side of the interface. The results clearly show that as the potential is swept positively, the intensity of the Raman responses decreases in the aqueous side of the interface while concomitantly increasing in the organic side.

The interplay between the signals in the aqueous and organic phases is clearly visualised in [Fig. 2](#page--1-0)d and e. Little changes in the Raman intensity are observed at potentials more negative than 0.00 V. These results also demonstrate that the cathodic current at negative Δϕ is associated with the transfer of supporting ionic species in the background electrolyte (most probably Cl[−] from water to DCB). [Fig. 2f](#page--1-0) correlates the faradaic charge obtained from integration of the linear sweep voltammetry and the Raman intensity variation (ΔI_{Raman}) at 1457 cm⁻¹ registered when the laser was focused on the organic phase. From the slope of the trend in [Fig. 2f](#page--1-0), it can be estimated that Raman responses are capable of detecting changes in the interfacial population of $[Fe(phen)_3]^2$ ⁺ close to 4.6 × 10⁻⁹ mol/Raman intensity unit.

3.2. Heterogeneous electron transfer reaction

A second test case investigated is the heterogeneous electron transfer between hexacyanoferrate (III) and DMFC. The spectroelectrochemical cell composition used was: Ag(s) | AgCl (s) | 1 mM BTPPACl + 10 mM LiCl (aq) | 5 mM BTPPATPBF₂₀ + 25 mM DMFc + 2% (w/w) PVC (DCB/ THF, 50%) || 25 mM K₄[Fe(CN)₆] + 25 mM K₃[Fe(CN)₆] + 0.1 M LiCl (aq) $|$ AgCl(s) $|$ Ag (s). The Raman spectra shown in [Fig. 3a](#page--1-0) feature hexacyanoferrate (II) bands at 2055 and 2093 cm $^{-1}$, as well as a band at 2132 cm^{-1} associated with hexacyanoferrate (III). These bands correspond to the C≡N stretching vibration which is sensitive to the oxidation state of Fe [\[19,20\]](#page--1-0). At $\Delta\phi \leq +0.30$ V, the intensity of the Raman signals is weakly dependent on the potential difference between the two reference electrodes. As $\Delta\phi$ is increased above $+0.30$ V, a clear increase in the intensity of the bands associated with hexacyanoferrate (II) is observed concomitantly with a decrease of the hexacyanoferrate (III) response [\(Fig. 3b](#page--1-0)). These changes in the Raman signal are indicative of the heterogeneous electron transfer response involving DMFC in the organic solution. [Fig. 3c](#page--1-0) also shows a direct relationship between the band at 2132 cm^{-1} and the faradaic charge associated with the oxidation of DMFC. In this experiment Raman responses are capable of detecting changes in the interfacial population of hexacyanoferrate (III) close to 1.9×10^{-7} mol/Raman intensity unit. The spectral response was much more sensitive for the ion transfer experiment using [Fe(phen) 3^{2+} than for the electron transfer reaction using hexacyanoferrate. $[Fe(phen)₃]$ ²⁺ shows an absorption band peak at 505 nm, whereas hexacyanoferrate (III) absorbs at 420 nm. Thus, in the ion transfer experiment resonance Raman is taking place, improving the sensitivity of the technique.

4. Conclusions

A new Raman spectroelectrochemical cell has been developed that allows studying ion and heterogeneous electron transfer at polarisable ITIES in-situ and in potentiodynamic conditions. By carefully positioning the focal point of the excitation laser, the depletion of the ion probe at the aqueous side of the interface and the corresponding accumulation in the organic side can be detected in real time. Furthermore, we were able to detect changes in the C≡N stretching vibration of hexacyanoferrate (II/III) during the heterogeneous electron transfer from DMFC. This exquisite spectral-temporal resolution can be exploited in more complicated systems featuring partially solvated species as well as nanoparticle decorated ITIES.

Acknowledgements

The financial support made available by the Junta de Castilla y León (GR71, BU349-U13) and Ministerio de Economía y Competitividad (CTQ2010-17127) is gratefully acknowledged. D.I. thanks Ministerio de Economia y Competitividad for his predoctoral FPI fellowship. D.P. and D.J.F. acknowledge financial support from the EPSRC (grant EP/K007025/1).

Download English Version:

<https://daneshyari.com/en/article/178817>

Download Persian Version:

<https://daneshyari.com/article/178817>

[Daneshyari.com](https://daneshyari.com)