



Effect of vacuum or modified atmosphere packaging (MAP) in combination with a CO₂ emitter on quality parameters of cod loins (*Gadus morhua*)



Anlaug Ådland Hansen^{a,*}, Birgitte Moen^a, Marit Rødbotten^a, Ingunn Berget^a,
Marit Kvalvåg Pettersen^{a,b}

^a Nofima, Osloveien 1, N-1430 Ås, Norway

^b University of Life Sciences, N-1432 Ås, Norway

ARTICLE INFO

Article history:

Received 8 September 2015

Received in revised form 25 April 2016

Accepted 12 May 2016

Available online xxx

Keywords:

CO₂ emitter

Packaging

Bacteria

Photobacterium

Odor

ABSTRACT

Bacterial growth, microbiota and sensory quality of cod loins (farmed Atlantic cod, *Gadus morhua*) was studied during 15 days of storage (2 °C), packaged in vacuum or in modified atmosphere package (MAP, 60% CO₂/40% N₂, g/p ratio 1.6/1), with a CO₂ emitter pad or a liquid absorbent pad. The objective was to investigate how packaging with CO₂ emitter can prolong shelf life in vacuum, and in low headspace MAP. Sensory analysis showed that the initial freshness was better preserved by adding a CO₂ emitter in both vacuum and MAP. The MAP had equal antibacterial effect compared to vacuum added CO₂ emitter. 16S rDNA sequencing showed that CO₂ emitter did not alter the dominant bacterial composition and that *Photobacterium* sp. dominated all packaging methods. Vacuum packaged samples past shelf life after 7 days of storage, vacuum added a CO₂ emitter and MAP after 9 days, and MAP added a CO₂ emitter after 13 days.

© 2016 Elsevier Ltd. All rights reserved.

1. Introduction

Raw fish and especially fresh fillet products, are perishable, and initial bacterial load, packaging method and temperature prior to packaging, during transport and storage, affect bacterial growth, sensory quality and shelf life. Odor of raw fish products, which can be characterized by use of different attributes related to fresh fish odor, microbial spoilage odor and oxidized odor, is one of the most important quality parameter used to determine whether fish is acceptable for consumption or not (Ólafsdóttir, 2005). CO₂ is reported to preserve initial freshness and inhibit the formation of odor associated spoilage, evaluated by different odor attributes that correspond well to bacterial counts (Hansen, Mørkøre, Rudi, Rødbotten et al., 2009; Hansen, Rødbotten, Eie, Lea, Rudi & Mørkøre, 2012). Prediction of sensory quality of cooked fish by measuring odor of raw fillets is also reported (Rødbotten, Lea & Ueland, 2009).

It is well known that modified atmosphere packaging (MAP) by use of CO₂ inhibits bacterial growth of fresh fish products (Ashie, Smith & Simpson, 1996; Farber, 1991; Dalgaard, Gram & Huss, 1993;

Dixon & Kell, 1989; Sivertsvik, Jeksrud & Rosnes, 2002). However, the inhibitory effect of bacterial growth is proportional to the amount of dissolved CO₂ in the product. CO₂ is highly soluble in both water and fat, which makes it possible to dissolve into the fish meat. An elevated concentration of CO₂ in the headspace and high gas volume to product volume ratio (g/p ratio) increases dissolution of CO₂ in the flesh, which is due to a higher partial pressure of CO₂. At low g/p ratios the importance of CO₂ concentration is more pronounced (Dalgaard, 1995; Zhao & Wells, 1995; Devlieghere, Debevere & Van Impe, 1998; Gill & Penney, 1988; Löwenadler & Rönner, 1994). Devlieghere and Debevere (2000) showed increased concentration of dissolved CO₂ by increasing g/p ratio from 1/1 to 2/1. However, others have reported low g/p ratios of 1/1 or 0.4/1 resulted in similar bacterial inhibition as vacuum packaging of the fish (Randell, Ahvenainen & Hattula, 1995). Furthermore, the initial bacterial load of the fillet product at time of packaging in addition to the level of CO₂ (gas mixture in headspace of the package) and storage temperature, are also crucial for the effect on quality preservation of MAP (Farber, 1991). Devlieghere et al. (1998) report that increasing levels of CO₂ in headspace can compensate for decreasing g/p ratios showed by different combinations of CO₂ concentrations (60.0%, 40.2%, and 31.4%) and g/p ratios (0.97, 1.74, 4.00, respectively). On the other

* Corresponding author.

E-mail address: anlaug.hansen@nofima.no (A.Å. Hansen).

hand, an increased g/p ratio in a package of modified atmosphere can be compensated by use of a CO₂ emitter, which develops CO₂ gas after sealing the package. Studies performed on fillets from farmed Atlantic cod and Atlantic salmon have shown that a CO₂ emitter can compensate for a g/p ratio of 4/1 and 3/1, respectively (Hansen, Mørkøre, Rudi, Olsen & Eie, 2007; Hansen, Mørkøre, Rudi, Rødbotten et al., 2009). The CO₂ emitter additionally functions as a liquid absorbent pad, and it enables low g/p ratios without packaging collapse.

There is an increasing interest of packaging raw, ready-to-prepare fish products in vacuum packages and MAP with low headspace volume, which are more transport efficient. However, simultaneously it is a demand for prolonged shelf life. The aim of this study was to verify how CO₂ emitter can compensate for reduced availability of CO₂, either in a vacuum package or in a MAP with low headspace. To our knowledge, vacuum packaging added a CO₂ emitter has not been published previously. This study was performed as the first stage in order to launch a pre-packaged cod product into the Norwegian retail market.

2. Materials and methods

2.1. Packaging methods, materials and storage

Loins of farmed Atlantic cod (*Gadus morhua*), processed pre-rigor one day before packaging, were transported by airplane from processing plant in northern Norway to the packaging site at the test centre of CFS in Biedenkopf Wallau, Germany (arrival the day after). The loins (mean weight of 289 ± 55 g) were packaged for transport in expanded polystyrene (EPS) boxes without drainage, added 4 kg ice in each box with 10 kg fish. At the arrival, ice was still present in the packages, which means good chilling conditions during transport. At the packaging site four different packaging methods were used:

1. Vacuum packaging (termed "Vacuum", n=25).
2. Vacuum and a CO₂ emitter (termed "Vacuum + CO₂ emitter", n=25).
3. Modified atmosphere packaging (termed "MAP", n=25).
4. MAP and a CO₂ emitter (termed "MAP + CO₂ emitter", n=25).

The packaging gas was 60% CO₂ and 40% N₂, with g/p ratio of 1.6/1. A thermoforming machine, CFS Powerpack 430, was used (CFS; today a part of GEA Food Solutions GmbH, Düsseldorf, Germany), with the internal and external measurement of 83 × 283 mm and 100 × 300 mm, respectively, of each forming unit (Fig. 1). The volume of the vacuum packages and the modified atmosphere packages (MAP) were 211 ml and 490 ml, respectively (different drawing depths). The top web used for both methods were polyamide (PA)/ethylene-vinyl alcohol (EVOH)/polyethylene (PE) (90 μm, Wipak Oy, Valkeakoski, Finland). The bottom web was 600 μm thick for the MAP samples and 150 μm thick for the vacuum packages (both made of PE/PA/EVOH/PA/PE, Wipak Oy).

The oxygen transmission rate (OTR) of the vacuum packages and the modified atmosphere packages were measured to be 0.014 and 0.103 cm³/(package·d), respectively, at 2 °C and 100% humidity using the AOIR-method (Larsen, Kohler & Magnus, 2000). A liquid absorbent pad (SuperCore mP-2500, McAirlaid's, Steinfurt, Germany) was placed in the bottom of half of the packages while a CO₂ emitting pad was placed in the rest. The CO₂ emitters were prepared (at Nofima, Ås, Norway) by adding 0.304 g NaHCO₃ and 0.237 g citric acid to a liquid absorber pad (Absorbent Pad Dri-Loc, Friedrichsdorf, Germany) based on prior experiment (Hansen et al., 2007). Similar CO₂ emitter was used for both vacuum packages and MAP. The ingredients and the liquid absorber pad were all approved for food contact. The samples were packaged in EPS



Fig. 1. Packaging of cod loins in a thermoforming machine for modified atmosphere packaging (MAP) and vacuum packaging, using either liquid absorbing pad (picture) or a CO₂ emitter pad.

boxes added ice and sent by airplane back to Norway (Oslo), and further by truck to the lab at Ås, for storage in up to 15 days. The temperature was 1.9 ± 0.3 °C during transport and storage, measured by use of the logger Elpro-Buchs AG (Buchs, Switzerland). Five replicates per packaging method at each sampling time were used for the different analyses, analyzed after 1, 7, 9, 13 and 15 days of storage (sensory analysis only after 1, 7 and 13 days).

2.2. Analyses

2.2.1. Headspace gas analysis

The CO₂ and O₂ were analyzed at each sampling time by use of a CheckMate 9900 O₂/CO₂ analyzer (PBI Dansensor, Ringsted, Denmark).

2.2.2. Appearance of the packages

The appearance of the top web of the packages ("MAP" and "MAP + CO₂ emitter") was evaluated by using a scale from 0 to 6, where 0 = extremely under-pressure (concave), 3 = neutral/optimal, and 6 = extremely overpressure (convex), in accordance to Hansen, Høy and Pettersen (2009).

2.2.3. Analyses of bacteria (plate count)

Sampling was done by a 3 × 3 cm cut (1 cm depth), and a 1/10 dilution was attained by use of approximately 90 ml peptone water, and run in Stomacher for 60 s. Appropriate 10-fold dilutions were made and spread on Iron agar (Oxoid, Basingstoke, Hampshire, U.K.) plates, for total bacterial count and sulfide producing bacteria (SPB, black forming colonies), and on MRS (Man

Download English Version:

<https://daneshyari.com/en/article/19789>

Download Persian Version:

<https://daneshyari.com/article/19789>

[Daneshyari.com](https://daneshyari.com)