

Available online at www.sciencedirect.com

ScienceDirect

journal homepage: www.jfda-online.com

Original Article

Effects of electrode gap and electric potential on chlorine generation of electrolyzed deep ocean water

Guoo-Shyng Wang Hsu ^a, Shun-Yao Hsu ^{b,*}^a Department of Nutritional Science, Fu Jen Catholic University, Hsinchuang, New Taipei City, Taiwan, ROC^b Graduate Institute of Food Science and Technology, National Taiwan University, Taipei, Taiwan, ROC

ARTICLE INFO

Article history:

Received 8 October 2015

Received in revised form

30 December 2015

Accepted 21 January 2016

Available online 23 February 2016

Keywords:

chlorine

deep ocean water

electric efficiency

electrolyzed seawater

optimization

ABSTRACT

Electrolyzed water is a sustainable disinfectant, which can comply with food safety regulations and is environmentally friendly. A two-factor central composite design was adopted for studying the effects of electrode gap and electric potential on chlorine generation efficiency of electrolyzed deep ocean water. Deep ocean water was electrolyzed in a glass electrolyzing cell equipped with platinum-plated titanium anode and cathode. Results showed high electric efficiency at a low cell potential, and a high current density and high chlorine concentration at a high cell potential and low electrode gap. Current efficiency of the system was not significantly affected by electrode gap and electric potential. A small electrode gap reduced the required cell potential and resulted in high energy efficiency. The optimal choice of electrode gap and cell potential depends on the chlorine level of the electrolyzed deep ocean water to be produced, and a small electrode gap is preferred.

Copyright © 2016, Food and Drug Administration, Taiwan. Published by Elsevier Taiwan LLC. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

1. Introduction

Electrolyzed water is environmentally friendly, has significant disinfection effects, and can comply with food safety regulations [1]. Since most surface area of our earth is covered by seawater, it is reasonable to make sustainable applications of this resource. Electrolyzed seawater, owing to its significant disinfection effects, has been used in many antifouling systems [2,3], aquaculture, and seafood processing. For example,

Kasai et al [4,5] studied disinfectant effects of electrolyzed seawater on viable bacteria in hatchery seawater using a batch and a continuous electrolytic system. They reported a 2–4 log reduction of viable bacteria after treatment with electrolyzed seawater containing 0.5–1.0 mg/L chlorine for 1 minute. Watanabe and Yoshimizu [6] disinfected various utensils and equipment for aquaculture and reported a > 3 log reduction of viable bacteria after being treated with electrolyzed seawater containing 0.5–1.5 mg/L chlorine for 30–120 minutes. Kasai and Yoshimizu [7] studied disinfection

* Corresponding author. Graduate Institute of Food Science and Technology, National Taiwan University, No. 1, Sec. 4, Roosevelt Rd., Taipei 10617, Taiwan, ROC.

E-mail address: gfsthsu@ntu.edu.tw (S.-Y. Hsu).

<http://dx.doi.org/10.1016/j.jfda.2016.01.006>

1021-9498/Copyright © 2016, Food and Drug Administration, Taiwan. Published by Elsevier Taiwan LLC. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

of seawater from fishing port by an electrolytic apparatus and found its useful applications to sanitization of fish-holding tanks, port deck, and fishing equipment. Kimura et al [8] reared sea urchins for 2 days using electrolyzed seawater containing 0.76 mg/L chlorine and found that 90% of bacteria in sea urchins' viscera were eliminated. Kasai et al [9] used electrolyzed seawater, which contained 0.2 mg/L chlorine, to deplete contaminated oysters and found that *Escherichia coli* in the oysters was reduced to below the detection limits.

Although many applications of electrolyzed seawater had been reported in aquaculture and seafood processing, few applications were reported in agriculture or food processing industry probably due owing to its sanitary concerns. Plankton and bacteria are abundant in seawater, and certain coastal seawater had been highly polluted [10,11]. By contrast, deep ocean water (DOW) is the cold, salty seawater found deep below the surface of earth's oceans. DOW makes up about 90% of the ocean volume. DOW has a low temperature, typically from 0°C to 3°C, and a salinity of about 35 psu [12]. Although surface seawater can be contaminated by pollution or civilization, the high-pressure and low-temperature DOW has remained unpolluted for the past thousand years.

In order to develop electrolyzed seawater for food and agricultural applications, especially for postharvest cleaning and disinfection of ready-to-eat fresh produce, surface seawater, DOW, and DOW concentration products were electrolyzed, and their properties as well as storage stability were investigated in our previous studies [13,14]. In this study, for the purposes of designing better electrolysis systems and developing optimal processing conditions, a two-factor central composite design is adopted for investigating optimal electrode gap and electric potential for electrolyzing DOW.

2. Methods

2.1. Seawater samples

DOW samples used in this study were provided by the Taiwan Yes Deep Ocean Water Co., Ltd (Hualien County, Taiwan). DOW was drawn at 662 m below the Pacific Ocean at ~5.0 km off the coastline of the Hualien County in eastern Taiwan. Table 1 shows a comparison of major elements, some pollution indicators, and physical/chemical properties of the DOW

with those of surface seawater samples collected at nearby areas. Despite containing similar major elements, DOW appeared to be colder and purer than surface seawater, which contained more nitrite as well as chlorophyll and were more alkaline in its pH values.

2.2. Electrolysis

DOW samples, 1600 mL each, were electrolyzed for 2 hours in a 2.0 L glass-beaker electrolyzing cell equipped with a pair of 50 mm long × 25 mm wide anode and cathode. The anode and cathode (Model SUR-303; Surchem C&S International Corp., Taipei City, Taiwan), which were titanium mesh electrodes plated with 3.75 μm of platinum, were powered by a rectifier (Model MC48-4D; Surchem C&S International Corp.). A constant potential mode of operation was adopted in this study. The electrodes were immersed in seawater at 60 mm beneath the surface. Electrode gap and cell potential were maintained at designated levels during electrolysis (Table 2). Additional stirring was done with a 16 × 30 mm² (diameter × length) Teflon spindle-shaped magnetic stirring bar powered by a stirrer (Model PC-101; Corning Inc., Acton, MA, USA) at speed setting 1.2, which was ~200 rpm. Electrolysis parameters and electrolyte properties were monitored during the electrolysis process.

2.3. Analytical measurements

A total chlorine test kit (Model 16900; Hach Co., Loveland, CO, USA; Method 8209, which is based on the iodometric method) was used to measure total residual chlorine in the electrolyzed seawaters. The assay was verified periodically using a 100 ± 0.05 ppm chlorine standard solution (Orion Research Inc., Beverly, MA, USA). All measurements were conducted at 29 ± 1°C.

2.4. Electrolysis efficiency

Current density was calculated by dividing the electric current by the effective surface area of the anode. Current efficiency was calculated from the percentage ratio of the total chlorine production to the theoretical chlorine production based on the Faraday's laws of electrolysis [15]. Electric efficiency, which represents energy efficiency of the system, was calculated by

Table 1 – Comparison of major elements, some pollution indicative compositions, and properties of surface seawater and deep ocean water samples.^a

Category	Item	Surface seawater	Deep ocean water
Major element (mg/L or kg)	Chloride	19,060–19,860	18,840–19,510
	Sodium	11,320–11,500	11,380–11,430
	Magnesium	1327–1330	1283–1320
	Calcium	400–441	400–432
	Potassium	400–414	390–421
Composition	Nitrite (μM)	0.08–0.11	<0.03
	Chlorophyll a (μg/L)	0.12–0.19	<0.03
Property	Temperature (°C)	22.5–23.8	9.4–10.4
	pH	8.10–8.20	7.70–7.75
	Salinity (psu)	34.2–34.5	34.3–35.0

^a Data provided by the Stone and Resource Industry R&D Center, 2014 (Hualien County, Taiwan).

Download English Version:

<https://daneshyari.com/en/article/2507241>

Download Persian Version:

<https://daneshyari.com/article/2507241>

[Daneshyari.com](https://daneshyari.com)