

Contents lists available at ScienceDirect

### **Biochemical Engineering Journal**



journal homepage: www.elsevier.com/locate/bej

# Biofiltration of H<sub>2</sub>S in air–Experimental comparisons of original packing materials and modeling



Mouna Ben Jaber<sup>a,b</sup>, Annabelle Couvert<sup>a,b</sup>, Abdeltif Amrane<sup>a,b</sup>, Franck Rouxel<sup>c</sup>, Pierre Le Cloirec<sup>a,b</sup>, Eric Dumont<sup>d,\*</sup>

<sup>a</sup> Ecole Nationale Supérieure de Chimie de Rennes, CNRS, UMR 6226, 11 Allée de Beaulieu, CS 50837, 35708 Rennes Cedex 7, France

<sup>b</sup> Université Européenne de Bretagne, 5 Boulevard Laënnec, 35000 Rennes, France

<sup>c</sup> TC Plastic, Rue Benjamin Franklin, 44160, Pont-Château, France

<sup>d</sup> L'UNAM Université, École des Mines de Nantes, CNRS, GEPEA, UMR 6144, La Chantrerie, 4 rue Alfred Kastler, B.P. 20722, 44307 Nantes Cedex 3, France

#### ARTICLE INFO

Article history: Received 7 October 2015 Received in revised form 9 March 2016 Accepted 20 April 2016 Available online 23 April 2016

Keywords: Biofilters Modeling Diffusion-Reaction Waste treatment Hydrogen sulfide Odors

#### ABSTRACT

The treatment of hydrogen sulfide using a biofilter packed with expanded schist and topped with a layer of a synthetic nutritional material (UP20) was examined at a constant H<sub>2</sub>S concentration (100 ppmv). The impact of the empty bed residence time (EBRT) on process performances was clearly underlined by varying the polluted air flow from 4 to 20 m<sup>3</sup> h<sup>-1</sup> corresponding to a variation in the EBRT from 63 to 13 s. Complete H<sub>2</sub>S degradation was observed when the EBRT was higher than 51 s. Experimental data collected at various EBRTs (13–63 s) were fitted using the Ottengraf model equations. The  $\alpha_{lump}$  parameter value was found to be 26.4 g<sup>1/2</sup> m<sup>-3/2</sup> h<sup>-1</sup>. This single parameter, which enables the performance of the biofilter as a whole to be characterized whatever its composition (mixture or layers of different packing materials) and whatever the EBRT, is a powerful tool to compare packing materials and to design such bioreactors. The  $\alpha_{lump}$  value characterizing the performances of expanded schist coupled with a thin layer of UP20 was higher than the  $\alpha_{lump}$  values obtained for other packing materials (natural or synthetic) reported in previous studies.

© 2016 Elsevier B.V. All rights reserved.

#### 1. Introduction

Hydrogen sulfide (H<sub>2</sub>S) is a hazardous, toxic air pollutant. It is a colorless, corrosive and flammable gas. H<sub>2</sub>S can be problematic due to its unpleasant smell and low odor threshold. It is emitted from many industrial activities such as petroleum refining, leather, waste or wastewater treatments, food processing, anaerobic treatment of paper and pulp manufacturing. Conventionally, different processes have been used to remove H<sub>2</sub>S from waste gas streams involving chemical and physical methods. For some years, the focus has shifted toward using biofiltration. This process presents an attractive technology for treating pollutants from air due to its effectiveness, low energy consumption and minimal by-product generation. The gas stream flows through the filter bed. Pollutants are then transferred from the gas phase to the biofilm, where they are metabolized by microorganisms. The by-products of the complete biodegradation of air pollutants are CO<sub>2</sub>, water, and microbial biomass. In the case of H<sub>2</sub>S biodegradation, sulfur oxidizing bacte-

\* Corresponding author. E-mail address: eric.dumont@mines-nantes.fr (E. Dumont).

http://dx.doi.org/10.1016/j.bej.2016.04.020 1369-703X/© 2016 Elsevier B.V. All rights reserved. ria (SOB) are responsible for removing  $H_2S$  in aerobic conditions. For their maintenance and growth, SOB use  $H_2S$  as a source of energy and  $CO_2$  as the main source of carbon [1,2]. Bacteria from the genus *Thiobacillus* are responsible for the oxidation of  $H_2S$  to sulfate and/or elemental sulfur according to the operating conditions [3,4].

The biofiltration of H<sub>2</sub>S is well documented (Table 1). As this table shows, a variety of packing materials are used and biofiltration performances are disparate. These packing materials include: (i) organic materials such as soil, peat, compost and pine bark [3,5–10] and different forms of activated carbons [11,12]; (ii) inorganic materials like pozzolan, expanded schist and lava rock [13–15]; (iii) synthetic media such as a patented biofilter medium (Biosorbens<sup>TM</sup>) developed by Shareefdeen [16,17]. Nonetheless, recent studies highlighted that biofilters filled with expanded schist topped with a layer of synthetic nutritional material (UP20) were very efficient for removing high loading rates of H<sub>2</sub>S [15,18,19]. The good mechanical behavior of the expanded schist (low pressure drop) and the ability of biofilters to oxidize H<sub>2</sub>S under extreme acidic conditions for a long period confirmed the advantage of using expanded schist coupled with UP20 for industrial applications [14,15,18,20]. In biofiltration, the empty bed residence time

Nomenclature	
А	Specific area ( $m^2_{\text{biofilm}} m^{-3}_{\text{packing storial}}$ )
C	Gas concentration ( $g m^{-3} g_{as}$ )
Cr	Pollutant concentration in the biofilm $(g m^{-3}_{biofilm})$
d	Diameter (m)
D	Diffusion coefficient $(m^2_{\text{biofilm}} s^{-1})$
EBRT	Empty bed residence time (s); EBRT = $V/Q_v$
EC	Elimination capacity $(g_{H2S} m^{-3}_{packinmaterial} s^{-1});$
	$EC = (Q_v/V) (C_{in} - C_{out})$
Н	Height (m)
k	Zero order reaction rate constant $(g m^{-3}_{biofilm} s^{-1})$
LR	Loading rate (gH2S m <sup>-3</sup> <sub>packin material</sub> s <sup>-1</sup> ); LR=(Q <sub>v</sub>
	C <sub>in</sub> /V)
m	Partition coefficient (–)
Qv	Gas flow rate $(m_{gas}^3 s^{-1})$
R	Reaction rate constant (g m <sup>-3</sup> packinmaterial s <sup>-1</sup> ); R = k
	aδ
RE	Removal efficiency (%); RE = $100 (C_{in} - C_{out})/C_{in}$
U	Superficial gas velocity (m <sub>gas</sub> s <sup>-1</sup> )
V	Bed volume of packing material (m <sup>3</sup> <sub>packingmaterial</sub> )
х	Length coordinate (m)
Greek letters	
$\alpha_{lump}$	Lump parameter $(g^{1/2} m^{-3/2}_{packinmaterial} s^{-1})$ (Otten-
	graf's equations)
δ	Total biofilm thickness (m)
ε	Porosity of the packing material (–)
φ	Thiele modulus (–)
λ	Effective biofilm thickness (m)
σ	Dimensionless length coordinate in the biofilm
	(=x/δ)
Subscripts	
Crit	Critical

(EBRT) is the key parameter influencing biofilter performances. Usually, EBRTs from 20 to 60s are applied to remove H<sub>2</sub>S from air [6,16,21] but higher and lower values are reported in the literature. As illustrated in Table 1, the EBRT may be significantly different from one study to another (from 2 to 120 s, i.e. almost two orders of magnitude). Consequently, it is very difficult to compare the performance of different packing materials on the basis of the Elimination Capacity (EC in g m<sup>-3</sup> h<sup>-1</sup>) measured at different EBRTs and the Removal Efficiency (RE), which can be other than 100%. The literature results presented in Table 1 clearly illustrate that the comparison of biofilter performances is difficult. For instance, is it possible to compare the performance of peat reported by Oyarzun et al. [3] (EC = 14.8 g m<sup>-3</sup> h<sup>-1</sup> at EBRT = 120 s and RE = 100%) with that of the biofilter medium Biosorbens<sup>TM</sup> reported by Shareefdeen [16]  $(EC = 6 g m^{-3} h^{-1} at EBRT = 30 s and RE = 99\%)$ ? To overcome this problem, it would be better to base the comparison of the performances of packing materials on mathematical models. Several models have been proposed to predict the performances of biofilters and to improve biofilter design [22,23]. One of the earliest steady-state biofiltration models was developed by Ottengraf and Van den Oever [24]. Because of its mathematical simplicity, this model has been widely used for biofiltration [3,25,26]. Therefore, the objective of this work was to show that a single parameter (called  $\alpha_{lump}$ ) derived from the Ottengraf model equations can be used as a simple tool to compare the performances of different carrier materials used in H<sub>2</sub>S biofiltration whatever the configuration



Fig. 1. Substrate concentration profile in the biofilm: diffusional regime.

of the biofilter and whatever the EBRT. The Ottengraf model was therefore applied (i) to determine the  $\alpha_{lump}$  parameter experimentally in order to evaluate the performance of a biofilter filled with expanded schist topped with a layer of synthetic nutritional material (UP20) and (ii) to compare this latter with the performance of packing materials reported in the literature. To achieve these objectives, the ability of the biofilter to oxidize H<sub>2</sub>S at different EBRTs should be determined beforehand. Therefore, this paper presents a brief description of the mathematical model used and details the experimental study carried out.

#### 2. Ottengraf model equations

In order to describe the mechanisms of transfer and biodegradation in the biofilter (Fig. 1), Ottengraf and Van den Oever [24] proposed a simple model based on the theoretical model built by Jennings et al. [41]. The hypotheses are as follows:

- Biodegradation occurs in a biofilm considered to be water.
- Biofilm thickness is small compared to the packing material diameter.
- Biomass concentration is homogeneous in the reactor.
- Gas phase is ideal.
- Gas phase is a plug flow.
- Mass transfer resistance in the gas phase is negligible.
- Regime is at steady-state.
- Equilibrium occurs at the gas-biofilm interface.

Moreover, Ottengraf and Van den Oever considered that the reaction rate constant of the substrate elimination in the biofilm is of zero-order in the pollutant concentration, which assumes a very low value of the Michaelis-Menten constant in the Monod equation [24]. Zero-order kinetics are encountered at high concentrations of  $H_2S$ , which is generally the case in laboratory experiments. With these assumptions, the concentration of a nutrient component inside the biofilm ( $C_L$ ) is described using the differential equation:

$$D\frac{d^2C_L}{dx^2} - k = 0 \tag{1}$$

with the boundary conditions:

$$x = 0; C_L = \frac{C}{m} \tag{2}$$

$$x = \delta; \, \frac{dC_L}{dx} = 0 \tag{3}$$

in

out

Inlet

Outlet

Download English Version:

## https://daneshyari.com/en/article/2718

Download Persian Version:

https://daneshyari.com/article/2718

Daneshyari.com