EDITORIAL COMMENT

Snowshoe Versus Ice Skate for Scaffolding of Disrupted Vessel Wall*



Patrick W. Serruys, MD, PhD,† Pannipa Suwannasom, MD,‡ Shimpei Nakatani, MD,‡ Yoshinobu Onuma, MD, PhD‡

he advance of coronary stent technology and scaffolding devices in coronary intervention procedures aims at reducing both shortterm and long-term adverse cardiac events. However, periprocedural myocardial infarction (PMI) still occurs during the coronary procedure. In the report by Kawamoto et al. (1) in this issue of JACC: Cardiovascular Interventions, the investigators present the clinical impact of "average" abluminal strut surface area (ASSA) on PMI (based on extended historical MI definition) and long-term clinical outcome. The results from this group showed that compared with the Cypher stent (Cordis, Johnson and Johnson, Warren, New Jersey) with an ASSA of 67 mm², the Absorb device (Abbott Vascular, Santa Clara, California) has a larger ASSA of 133 mm² and is associated with PMI rates twice as high as those in Cypher group. There was no significant difference in long-term clinical outcomes between the 2 devices.

SEE PAGE 900

The results of the present study may warrant a word of caution in interpretation. First, the propensity analysis can lead to misleading statements. Previously, it has been suggested in a propensity matched nonrandomized comparison conducted by our group that Absorb bioresorbable vascular scaffold was associated with a higher incidence of post-procedural side branch occlusion (SBO) compared


*Editorials published in *JACC: Cardiovascular Interventions* reflect the views of the authors and do not necessarily represent the views of *JACC: Cardiovascular Interventions* or the American College of Cardiology.

From the †International Center for Circulatory Health, National Heart and Lung Institute, Imperial College London, London, United Kingdom; and the †Department of Interventional Cardiology, Thoraxcenter, Erasmus Medical Center, Rotterdam, the Netherlands. Drs. Serruys and Onuma are members of advisory board of Abbott Vascular. All other authors have reported that they have no relationships relevant to the contents of this paper to disclose.

with the metallic everolimus-eluting stent. The difference was more pronounced with small side branches with a reference vessel diameter ≤0.5 mm (2). However, there was no significant difference in the incidence of post-procedure creatine kinasemyocardial band elevation. The hypothesis has been tested again in the ABSORB II (ABSORB II Randomized Controlled Trial: A Clinical Evaluation to Compare the Safety, Efficacy, and Performance of Absorb Everolimus Eluting Bioresorbable Vascular Scaffold System Against Xience Everolimus Eluting Coronary Stent System in the Treatment of Subjects With Ischemic Heart Disease Caused by De Novo Native Coronary Artery Lesion) randomized control trial (3) in which all 3 cardiac biomarkers were explored and analyzed in a core lab. There was no significant difference in the normalized value for each enzyme. To our surprise, the randomized data showed that the SBO (core lab analysis) occurred more often in the metallic stent group (39 of 503 side branches [8%]) than in the bioresorbable scaffold group (52 of 998 side branches [5%]), but this difference did not reach a statistical significance, p = 0.07.

Second, despite their hypothesis that greater ASSA is associated with PMI rate, mechanical complications such as SBO were not reported. SBO should be assessed rigorously by an independent core lab using quantitative coronary angiography whenever possible (e.g., side branch diameter ≥0.5 mm, the lower limit of automated edge detection).

Finally, it is unclear whether the cardiac biomarkers were systematically obtained. Generally, the incidence of PMI depends on the availability, type of post-procedural cardiac biomarkers, and enzymatic criteria used, as well as the frequency of cardiac biomarkers sampling. PMI remains a debatable issue with a heterogeneous incidence due to a diversity of definitions. The incidence of PMI could vary from 1%



(A, E) The yellow, blue, and green vertical lines correspond to the various levels of the optical coherence tomography cross-section of Absorb (B to D) and Xience stent (F to H) showing the various degrees of embedment of the 2 respective devices. B and F demonstrate the strut width at the hinges level. The hinge strut width (yellow double-headed arrow) of the Absorb scaffold (B) can measure up to 883 μm, whereas the strut of the Xience stent (F) is only 428 μm. C and G demonstrate strut width at the ring and link level. The ring strut width is represented with blue line and link strut width is labeled by a blue bracket. E and H demonstrate strut width at the crown peak level with a green arrow, and the link strut width is labeled by a green bracket.

to 32% (3). For example, cardiac troponin T for the third universal definition can lead to overestimation of PMI. Ideally, an assessment of 3 cardiac biomarkers is recommended.

Nevertheless, the study results could put forward some new mechanical and rheological hypotheses. The implantation of a device with a large "footprint" could potentially cause small SBO and subsequent cardiac biomarkers to rise. One can speculate that the large footprint of the ABSORB (scaffold area covers 26% to 32% of the vessel wall area) could accidentally cover the ostium of small side branches, resulting in SBO. When measured using optical coherence tomography, the width of the Absorb struts at the hinge point can be as large as 800 μm (Figure 1). Therefore, a side branch with a diameter of <0.8 mm could be occluded by the device (Figure 2B). The width of the strut could also influence the embedment of the strut. When the same force is applied, a device with a smaller contact area would generate a higher pressure to the vessel wall according to the simple principle: Pressure = Force/Area (Figures 2C and 2D). Taking into account the fact that a more aggressive post-dilation was applied in the Cypher group, the Cypher stent may have been more embedded (Figure 2E) into the vessel wall than the Absorb device was (Figure 2F). Embedded struts imply penetration of the cutting edge of the metals through fibrous, calcific, and necrotic plaques. The deep penetration of the strut into the vessel wall could also disrupt and displace the edge of the ostium of a side branch, with possible reduction or occlusion of its ostium (Figure 2A); additionally injury of the necrotic core can squeeze microparticles, which results in distal embolization and rise in cardiac biomarkers (4).

On the other hand, the thick protruding strut of the Absorb disrupts the laminar flow and induces flow disturbances. In a flow simulation of a microenvironment computed by optical coherence tomography/ angiography fusion in a human coronary artery (5), the relatively high shear stress on top of the

Download English Version:

https://daneshyari.com/en/article/2940003

Download Persian Version:

https://daneshyari.com/article/2940003

<u>Daneshyari.com</u>