



Price forecasting and validation in the Spanish electricity market using forecasts as input data



María Ortiz ^{a,*}, Olatz Ukar ^a, Filipe Azevedo ^{b,c,1,2}, Arantza Múgica ^a

^a Deusto Institute of Technology – DeustoTech Energy (University of Deusto), Avenida Universidades, 24 – 48007 Bilbao, Vizcaya, Spain

^b Institute of Engineering-Polytechnic of Porto (ISEP/IPP), Rua Dr. Antonio Bernardino de Almeida, 431, 4200-072 Porto, Portugal

^c INESC TEC (Formerly INESC Porto), Rua Dr. Roberto Frias, 378, 4200-465 Porto, Portugal

ARTICLE INFO

Article history:

Received 27 May 2014

Received in revised form 27 September 2015

Accepted 8 November 2015

Available online 1 December 2015

Keywords:

Artificial neural network

Electricity markets

Price forecast

Regression model

Volatility

ABSTRACT

The electricity sector has been subjected to major changes in the last few years. Previously, there existed a regulated system where electric companies could know beforehand the amount of energy each generator would produce, hence basing their largely operational strategy on cost minimization in order to increase their profits. In Spain, from 1988 till 1997, electricity prices were established by the ‘Marco Legal Estable’ – *Stable Legal Framework* –, where the Ministry of Industry and Energy acknowledged the existence of certain generation costs related to each type of technology. It was an industrial sector with no actual competition and therefore, with very few controllable risks. In the aftermath of the electricity market liberalization competition and uncertainty arose. Electricity spot prices became highly volatile due to the specific characteristics of electricity as a commodity. Long-term contracts allowed for hedge funds to act against price fluctuation in the electricity market. As a consequence, developing an accurate electricity price forecasting model is an extremely difficult task for electricity market agents. This work aims to propose a methodology to improve the limitations of those methodologies just using historical data to forecast electricity prices. In this manner, and in order to gain access to more recent data, instead of using natural gas prices and electricity load historical data, a regression model to forecast the evolution of natural gas prices, and a model based on artificial neural networks (ANN) to forecast electricity loads, are proposed. The results of these models are used as input for an electricity price forecast model. Finally, and to demonstrate the effectiveness of the proposed methodology, several study cases applied to the Spanish market, using real price data, are presented.

© 2015 Elsevier Ltd. All rights reserved.

Introduction

Electricity is of great importance to society and essential for economic and industrial development. The main difference between electricity and other commodities is that it cannot be stored in large quantities and, thus, a constant balance between supply and demand is necessary, leading to highly volatile market prices.

The electricity sector has undergone important changes since the beginning of the deregulation process brought about by Spanish Electric Power Act 54/1997 of November 27. Since then, con-

sumers have been facing high levels of uncertainty due to price volatility.

The peculiarities of electricity as a commodity make for an extremely difficult price evolution forecast. Therefore, it is necessary to develop more accurate and robust methods to support long term contract decisions.

Marketers, producers, and end users are subject to the risk of buying or selling a fixed amount of electricity at a fixed price, without knowing the ultimate price of this asset. Therefore, this is a sector in which monetary costs resulting from an ineffective price forecast can be rather high. A procedure to increase the accuracy of electricity price forecasts can actually maximize the benefits for all market players. In this manner, there is an essential need for an efficient and robust forecasting method for these different players participating in the electricity market to maximize their profits and improve in terms of risk management.

For this reason, price forecasting has become a basic decision-making issue for power companies worldwide, though the special

* Corresponding author at: Tel.: +34 94 413 90 73/+34 94 413 90 03.

E-mail addresses: m.ortiz@deusto.es (M. Ortiz), olatz.ukar@deusto.es (O. Ukar), fta@isep.ipp.pt, filipe.azevedo@inescporto.pt (F. Azevedo), arantza.mugica@deusto.es (A. Múgica).

¹ Tel.: +351 228 340 500.

² Tel.: +351 222 094 000.

characteristics of electricity represent a challenge to achieve this task [1].

Several factors affect the price formation of electricity and determining them is of the most importance. To that end, factors included in the model, according by Gianfreda and Grossi [9] such as technology, market concentration, congestions and volumes, are relevant to forecast the final Single National Price.

There are many efforts by researchers to solve this problem. Many techniques have been employed in electricity price forecasts such as, for instance, artificial neural networks (ANNs) [10,17,14], fuzzy inference systems (FIS) [18], and support vector machines (SVMs) [6,22].

Other researchers used time series models like ARIMA [7,5] and GARCH [8] and also proved to be effective for electricity price forecast. A summary of the different methods used to predict the price of electricity is presented in Jain et al. [13] and Lawarree et al. [15].

Forecasting the hourly market-clearing price (MCP) on electricity spot markets is an essential basic task for decision-making in order to maximize benefits [19]. Many efforts have been made to accurately forecast electricity market spot prices [16]. But, in long-term planning, it makes more sense to obtain a monthly average price than just the hourly price. The goal according by Torbaghan [20] is to forecast the monthly electricity average price for Ontario and Nord Pool electricity markets, for the following 12 months.

The successful negotiation of a contract price for the participants in these markets is driven by an accurate forecast of the price of electricity, which is why developing methodologies to solve this problem is so necessary [3,4,2].

An artificial neural network (ANN) model has been used in this research. Before applying the electricity price forecasting model (MBF), it is necessary to get the input variables which can be obtained with two others models: a regression model, used to calculate the gas price (MBF-GP), and another artificial neural network to obtain the electricity load (MBF-LD). By means of those models, the monthly average price for the Spanish electricity market can be forecasted throughout different years.

Model based on forecasted data – MBF

This work presents a model based on one-year forecast data (MBF). In order to use the most recent data possibly available, it is necessary to include data forecasted with other used models.

This new model uses forecast input variables, so it is necessary to previously prepare a forecast for load and natural gas prices during the same time period. Therefore, monthly average forecast values for the year ahead are obtained (load and natural gas prices). Results which are then used as input in the electricity price forecast model. A description of the model is shown in Fig. 1.

The first step is to forecast the load and the gas price for the corresponding period. For that reason, it is necessary to develop a load forecasting model (MBF-LD) and a gas price forecasting model (MBF-GP). The results obtained are used as input data in the electricity price forecasting model (MBF).

MBF-LD

The proposed load forecasting method is a model based on artificial neural networks (ANN).

ANNs are a good learning and automatic data processing example based on how a nervous system works – a network of interconnected neurons trying to learn from the information received to later produce an output stimulus. Connections between neurons, defined as synaptic weights (w), are optimized by the learning algorithm.

The ANN has a distributed calculus structure that allows for a quick resolution of time-consuming problems when using classical computers. It also has the ability to learn tasks based on training or initial experience [11,12].

First, it is necessary to divide historical data into groups. These groups are then classified according to month, since a monthly seasonality is observed.

A set of vectors is then created in order to train and validate the neural network. The input vector for training and testing the network is shown in Eq. (1).

$$I_{ij} = [C_{i-1,j}, C_{ij-1}, C_{ij-2}] \quad (1)$$

where $C_{i-1,j}$ is the load value for month ($i-1$) and year (j), C_{ij-1} is the load value for month (i) and year ($j-1$), and C_{ij-2} is the load value for month (i) and year ($j-2$).

The target vector used for network training and validation is presented in Eq. (2).

$$T_{ij} = [C_{ij}] \quad (2)$$

The training method used is known as a Bayesian regulation backpropagation. This function updates weight and bias values according to the Levenberg–Marquardt optimization algorithm. This method follows a Bayesian regulatory process which determines the right combination, once the squared errors and the weights necessary to produce a correct network have been minimized.

Before training the network, the inputs and outputs must be scaled in a $[-1,1]$ range. Two 16-neuron hidden layers were used – a tan-sigmoid transfer function for hidden layers and a linear transfer function for the output layer – for the network to take on a [3-16-16-1] configuration. The method output is the monthly average load for one year period.

Monthly energy historical data were used and collected from OMI (Iberian Energy Market Operator) between January 2004 and December 2011. Fig. 2 presents the data within this period.

Fig. 3 shows the load distribution broken down by month, with January and December as the coldest months and June, July and August as the hottest ones. Energy demand will be consequently higher in these months, than in the temperate ones, such as April, May and September.

MBF-GP

The proposed method for the gas price forecast is based on a regression model. This regression model is a mathematical method which correlates a dependent variable Y_t , – that is, the variable to be explained – to other independent X_i variables – which are the factors influencing the formation of the variable Y –, and a random ε term representing the error term. This general model is expressed in Eq. (3).

$$Y_t = \beta_0 + \beta_1 X_1 + \beta_2 X_2 + \dots + \beta_n X_n + \varepsilon_t \quad (3)$$

where β_0, \dots, β_n are regression parameters and X_1, X_2, \dots, X_n are independent parameters.

Regression parameters (β_0, \dots, β_n) are determined by several optimization algorithms; in this case, genetic algorithms. These algorithms evolve to a population of individuals subjected to random actions imitating biological evolution. The solution is based on the survival of the strongest ones according to certain optimization criteria.

This methodology aims to figure out those regression parameters minimizing the absolute error.

Gas prices are not as highly volatile as electricity prices. Fig. 4 shows the monthly historical average gas price from January 2003 to December 2011. It can be observed that the curve has a positive trend. There are certain peaks to be found in said figure but monthly price variations do not experience dramatic changes.

Download English Version:

<https://daneshyari.com/en/article/399315>

Download Persian Version:

<https://daneshyari.com/article/399315>

[Daneshyari.com](https://daneshyari.com)