



Contents lists available at ScienceDirect

International Biodeterioration & Biodegradation

journal homepage: www.elsevier.com/locate/ibiod

Physicochemical properties of sewage sludge disintegrated with high pressure homogenization



Wei Fang^{a, b}, Panyue Zhang^{a, b, *}, Jie Ye^{a, b}, Yan Wu^{a, b}, Haibo Zhang^{a, b}, Jianbo Liu^{a, b}, Yi Zhu^{a, b}, Guangming Zeng^{a, b}

^a College of Environmental Science and Engineering, Hunan University, Changsha 410082, China

^b Key Laboratory of Environmental Biology and Pollution Control (Ministry of Education), Hunan University, Changsha 410082, China

ARTICLE INFO

Article history:

Received 27 December 2014

Received in revised form

24 February 2015

Accepted 25 February 2015

Available online 13 March 2015

Keywords:

Sewage sludge

High pressure homogenization

Particle size

Zeta potential

Apparent viscosity

Surface tension

ABSTRACT

High pressure homogenization (HPH) pretreatment can improve the sludge anaerobic digestion; however, the physical and chemical properties of homogenized sludge are completely unclear. The effect of HPH treatment on the physicochemical properties of homogenized sludge was studied. The disintegration degree and soluble chemical oxygen demand increased with the increment of homogeneous pressure and cycle, showing effective organic release from sludge solid to liquid after HPH treatment. Besides the organic, volatile fatty acid and $\text{NH}_4^+\text{-N}$ were also released. The HPH treatment significantly disrupted sludge flocs, and the median sludge size starkly decreased from 48.26 to a range of 9.375–15.54 μm . The increase of homogenization pressure and cycle led to an insignificant change of sludge particle size, but the distribution of sludge particle size obviously changed and the volume of small particles obviously increased. Zeta potential of sludge liquid obviously decreased and apparent viscosity significantly increased after HPH treatment; however, the homogenization pressure and cycle displayed insignificant influence on them. Surface tension of sludge liquid decreased with the increase of homogenization pressure and cycle. The change of sludge physicochemical properties may be mainly attributed to the extracellular polymeric substances release from sludge flocs. The results may provide deeper insights why the sludge anaerobic digestion can be effectively improved by HPH pretreatment.

© 2015 Elsevier Ltd. All rights reserved.

Introduction

At the beginning of 20th century, activated sludge method began to be applied in wastewater treatment, and now it has become one of the most widely used techniques around the world. The activated sludge processes produce a large amount of excess sludge, which may cause a serious of environmental and health issues. Cost of sludge treatment and disposal accounts for about half or even up to 60% of the total cost in wastewater treatment plants (WWTPs) (Luo et al., 2013). To minimize and utilize the excess sludge is becoming the most important and challenging problems in the field of wastewater treatment (Zhang et al., 2009). Various pretreatment techniques have been studied in laboratory, pilot and also in full-scale for sludge reduction, which mainly

include physical, chemical and mechanical methods (Tiehm et al., 1997; Rai and Rao, 2009; Kim et al., 2010; Braguglia et al., 2012).

As a well-known mechanical method for cell disruption, high pressure homogenization (HPH) treatment was mainly used for the food stabilization and dairy emulsions (Paquin, 1999). Recently, several studies have been reported that HPH was applied to sludge disintegration for improving anaerobic sludge digestion (Onyech et al., 2003; Rai and Rao, 2009; Fang et al., 2014). When the sludge is pumped through homogenization valve, the pressure increases and then is immediately released as the sludge passes through (Floury et al., 2004). Several different stresses, such as large pressure drop, highly focused turbulent eddies and strong shearing forces, work for sludge disintegration. In addition, pressure energy can be converted into heat and further be transmitted to the fluid, raising the fluid temperature (Thiebaud et al., 2003). The effectiveness of HPH is affected by several factors, such as homogenization pressure, number of homogenization cycles, and total solid content (TS), which has been investigated extensively. The increase of homogenization pressure or homogenization cycle significantly

* Corresponding author. College of Environmental Science and Engineering, Hunan University, Changsha 410082, China. Tel.: +86 15001255497; fax: +86 10 62336900.

E-mail address: zhangpanyue@hnu.edu.cn (P. Zhang).

improved the sludge disintegration, while the increase of TS lowered the sludge disintegration efficiency (Zhang et al., 2012b). HPH treatment as a disintegration method has several advantages, for example, no obviously chemical changes, high disruption efficiency and simple operation (Barjenbruch and Kopplow, 2003).

Most researchers focused on the organic conversion between sludge solid and liquid phases with a HPH pretreatment. Camacho et al. (2002) reported that the applied shear forces by HPH led to a progressive cell break up and 90% total chemical oxygen demand (TCOD) could be maximally released from sludge particulate fraction. Zhang et al. (2013) showed that both total suspended solid (TSS) and volatile suspended solid (VSS) decreased with increasing the homogenization pressure and cycle. However, there are few literatures on the change of sludge physical and chemical properties during homogeneous process, which may influence the further sludge treatment and utilization. The objective of this study is to investigate the effect of HPH on physicochemical properties of disintegrated sludge. Besides the organic release, the release of volatile fatty acid (VFA) and $\text{NH}_4^+\text{-N}$ after HPH treatment was analyzed. The effect of HPH treatment on floc structure, particle distribution and pH of sludge, and Zeta potential, apparent viscosity, surface tension of sludge liquid was investigated. The results are expected to provide deeper insights why the sludge anaerobic digestion can be effectively improved by HPH pretreatment.

Materials and methods

Sludge characterization

Sludge used in this study was collected from the secondary sedimentation tank of a municipal WWTP with an anaerobic-anoxic-oxic process in Beijing, and was stored at 4 °C for later use. The sludge had an average pH value of 7.1, an average TCOD of 8425 mg/L, an average soluble chemical oxygen demand (SCOD) of 192 mg/L and an average TSS of 6540 mg/L.

High pressure homogenization treatment

A high pressure homogenizer (JJ-30, Shengtong Inc., China) with a working pressure range of 0–100 MPa was used in this study for sludge disintegration. The sludge sample was firstly pumped through the homogenization valve by an air driven positive displacement pump, and the homogenization pressure was fixed at a certain value through adjusting the homogenization valve. When the sludge sample went through a convergent section of the homogenization valve, the sludge stream was immediately accelerated to 1000–1500 m/s. Then the high-velocity sludge stream impinged on an impact ring and the pressure suddenly dropped from high pressure to low pressure, and the sludge was disrupted and liquefied due to the combined action of pressure gradient, cavitation, turbulence, impingement, shear stresses, and extensional shear. Finally, the sludge was forced out of the homogenization valve with a lower velocity (Zhang et al., 2012b). The homogenization treatment was carried out at a given pressure (0–60 MPa) for one to three cycles. After HPH treatment, physicochemical properties of the homogenized sludge were measured.

Analytical methods

The sludge pH was obtained by pH meter (PHS-3C, Leici Co., China). The sludge particle size analysis was carried out through Malvern Mastersizer 2000 (Malvern, UK). The sludge TSS was measured based on APHA standard method (Eaton et al., 2005).

The sludge samples were centrifuged at 5000 r/min for 20 min, then the supernatant was immediately filtered through a cellulose

membrane with a pore size of 0.45 μm , and the filtrate was used for analyzing SCOD, $\text{NH}_4^+\text{-N}$, VFA, Zeta potential, apparent viscosity and surface tension. The chemical oxygen demand (COD) of filtrate was measured by potassium dichromate method according to APHA standard method (Eaton et al., 2005), and was defined as SCOD. The $\text{NH}_4^+\text{-N}$ of filtrate was measured by Nessler's reagent spectrometry by Multiparameter Bench photometer (LH5B-3(B), Lianhua Instruments Inc., China). The VFA of filtrate was determined by a gas chromatograph 3710 (Agilent, USA) equipped with a flame ionization detector and analytical column CPWAX52CB (30 m \times 0.32 mm \times 0.25 mm). The Zeta potential of filtrate was filled in capillary cell, and monitored by a Malvern Zetasizer Nano (Malvern, UK) with the refractive index value of 1.450 and the absorption of 0.001. The apparent viscosity was measured by a rotating torque cylinder at a temperature of about 20 °C, which was performed at a shear rate of 60/s to keep the sludge sample in suspension for 5 min. The surface tension was measured by a SITA pro line t15 tensiometer (SITA, Germany) with the bubble lifetime of 250 ms, and the value was the average of three measurements. The efficiency of sludge disintegration was evaluated by disintegration degree (DD_{COD}), which was calculated as Eq. (1) (Bougrier et al., 2005):

$$\text{DD}_{\text{COD}}(\%) = \frac{\text{SCOD} - \text{SCOD}_0}{\text{TCOD} - \text{SCOD}_0} \times 100\% \quad (1)$$

where SCOD_0 is the SCOD of sewage sludge before treatment.

The sludge flocs were photoed with a microphotograph (OLYMPUS, BX53) and analyzed by Image Pro Plus 6.1. Percentage of floc area (A_f) in photo was calculated as Eq. (2) (Costa et al., 2013).

$$A_f = \frac{100 \sum_{i=1}^{n_{\text{abi}}} A_i}{\text{TA}} \% \quad (2)$$

where $\sum_{i=1}^{n_{\text{abi}}} A_i$ is the total area of all sludge flocs, and TA is the glass area.

The experiments were carried out with three replicates. T-test was used to evaluate significance analysis for experimental data.

Results and discussion

Organic matter release

The sludge can be disintegrated by homogenizer. The variations of SCOD and sludge DD_{COD} under different homogenization pressures and cycles are shown in Fig. 1. The SCOD increased with the increase of homogenization pressure from 0 to 60 MPa with a single homogenization cycle. When the homogenization pressure was 60 MPa with one homogenization cycle, the DD_{COD} reached 26.55%. The results demonstrated that more sludge organic matters were released from solid phase into liquid phase at higher homogenization pressure. In addition, multiple-cycle process was more effective for sludge disintegration than the single homogenization cycle. As homogenization cycle increases from one to three at a homogenization pressure of 60 MPa, the SCOD and DD_{COD} reached 3310 mg/L and 37.87%, which was 39.19% and 11.32% higher than that of the single homogenization, respectively. That may be attributed to the release of extracellular polymeric substances (EPS) due to floc disintegration or even the release of cell components because of cell lysis (Zhang et al., 2007). Other authors reported similar results that soluble organic release increased with increasing the homogenization pressure and cycle (Nah et al., 2000; Camacho et al., 2002). The organic release will improve further sludge anaerobic digestion.

Download English Version:

<https://daneshyari.com/en/article/4364358>

Download Persian Version:

<https://daneshyari.com/article/4364358>

[Daneshyari.com](https://daneshyari.com)