

Short communication

Optimization of conditions (pH and temperature) for *Lemna gibba* production using fuzzy model coupled with Mamdani's method



Surindra Suthar*, Rashmi Verma, Shikhar Deep, Kapil Kumar

School of Environment & Natural Resources, Doon University, Dehradun 248001, Uttarakhand, India

ARTICLE INFO

Article history:

Received 20 December 2014

Received in revised form 14 June 2015

Accepted 4 July 2015

Available online 3 August 2015

Keywords:

Ecological modeling
Wastewater treatment
Duckweed
MATLAB

ABSTRACT

A fuzzy-logic-based diagnosis system was developed to determine the effect of pH and temperature on duckweed *Lemna gibba* biomass production. The measured data of variables were implemented into the fuzzy inference system (FIS) with Mamdani's method. A fuzzy rule-based model was shaped to define the essential quality parameters monitored as pH and temperature as inputs. The fuzzy modeled values of biomass gain were validated against the experimental values with a strong correlation (r^2) of 0.98.

© 2015 Elsevier B.V. All rights reserved.

1. Introduction

The volume of wastewater generated by domestic, industrial and commercial sources has been increased with reckless developmental activities and human population explosion. The proper treatment strategy can play a very crucial role in tackling wastewater management aspects (Brix and Schierup, 1989). The conventional wastewater treatment system involves a series of treatments such as, preliminary treatment (screening and grit removal); primary treatment (screening, sedimentation); secondary treatment (activated sludge process, oxidation ponds, fluidized bed reactors) and tertiary treatment (sand filters, UV lamps, chemical precipitation) based upon the various physical, chemical and biological processes (Metcalf and Eddy, 2004). But, this conventional system offers several limitations on management and technological ground (as involves huge investment, labor, energy, operating and maintenance costs). So there is need of technology with low inputs and environmentally safe mechanism. The potential of duckweed in wastewater treatment has become well evident in the recent time. The duckweed based wastewater treatment system is a low cost, less technical in maintenance and operation, user friendly and effective in terms of results and can contribute toward water sustainability (Bal Krishna and Polprasert 2008; Azeez and Sabbar, 2012; Verma and Suthar, 2014). Apart

from removing pollutants from wastewater this duckweed system offers huge quantity of plant biomass at the end which can be harvested as feedstock for animal and bioenergy production (Verma and Suthar, 2014). The remediation capacity of plant in general is linearly correlated with the biomass productivity of the system. The biomass production is directly affected by few key abiotic factors like: pH, temperature, photoperiod etc. By manipulating such parameters, the productivity of the system can be enhanced and hence, the removal potential can be improved (Papadopoulos and Tsihrintzis, 2011; Khellaf and Zerdaoui, 2013). The accumulated duckweed being rich in carbohydrate, protein and starch may be utilized as bioenergy feedstock or livestock feed (El-Shafai et al., 2007; Cheng and Stomp, 2009). The information regarding optimization of operational conditions for duckweed based wastewater treatment system and biomass production is not well described in available scientific literature.

Fuzzy modeling based on fuzzy implication and reasoning is one of the most important fields in mathematical modeling (Takagi and Sugeno, 1985; Kosko, 1992; Scannapieco et al., 2012). Fuzzy logic and fuzzy sets are effective tools for modeling complex mathematical problems with parameters that demonstrate uncertainty (Scannapieco et al., 2012; Kotti et al., 2013). This approach has proved very useful in medical diagnosis (Lascio et al., 2002), information technology (Lee, 1996), water quality (Lu et al., 1999), reliability analysis (Sadiq et al., 2004) and many other industrial applications (Lawry, 2001), where reported data are either qualitative and decision-making is performed based upon expert opinions. Fuzzy sets are the sets with boundaries that are not

* Corresponding author.

E-mail address: suthariitd@gmail.com (S. Suthar).

precise and the usage is not a matter of affirmation or denial, but rather a matter of degree. A fuzzy number describes the relationship between an uncertain quantity x and a membership function m , which ranges between 0 and 1. An element x belonging to a set A is defined as $x \in A$, an element that is not a member in A is noted as $x \notin A$. A fuzzy set A is given in Eq. (A.1).

$$A = \{(x, \mu_A(x)) \mid x \in A, \mu_A(x) \in [0,1]\} \quad (\text{A.1})$$

where $\mu_A(x)$ is a membership function belonging to the interval [0,1]. Fuzzy-based evaluation methods help in addressing deficiencies inherent in binary logic and are useful in propagating uncertainties throughout models.

Fuzzy inference systems have found a wide range of industrial and commercial control applications that require analysis of uncertain and imprecise information (Horiuchi et al., 1993; Akcayol, 2004). In this study, a fuzzy-logic-based diagnosis system was developed to study the effect of variables (inputs) on biomass production in a duckweed pond system. The information of measured variables and the expert knowledge (EK) were implemented into the fuzzy inference system (FIS) with Mamdani's method by means of a fuzzy-based rule structure. The Fuzzy Logic Toolbox of MATLAB[®] R2012a was used to create and to edit the present Fuzzy Inference System.

2. Material and method

2.1. Experimental design

The duckweed *L. gibba* was collected from a local freshwater body located nearby the University Campus. The collected material was washed in tap water to remove adhering silt and other substances and then sterilized using 1% NaClO for 3–5 min. Then plant material was transferred to pre-sterilized container with 1/10 diluted Hoagland solution for further propagations to get contamination-free second generation of plants (Penningsfeld and Kurzman, 1975; Eliasson, 1978). The composition of Hoagland's solution was (all in mg/L): KNO₃, 1515.0; KH₂PO₄, 680.0; Ca (NO₃)₂·4H₂O, 1180.0; MgSO₄·7H₂O, 492.0; ZnSO₄·7H₂O, 0.22; H₃BO₃, 2.85; Na₂MoO₄·2H₂O, 0.12; CuSO₄·5H₂O, 0.08; MnCl₂·4H₂O, 3.62; FeCl₃·6H₂O, 5.4; tartaric acid, 3.0 (Hoagland and Arnon, 1950). The culture media was renewed twice every week. The prominent and healthy plants were hand sorted to be

used for experimental trials. The duckweed culture was maintained under ambient temperature of 24 °C (SD = 2) and light/dark regime of 16/8 h. The effect of pH, temperature and light regime on duckweed growth and biomass production has been assessed. The six different ranges of pH (i.e. 2, 3, 5, 7, 9 and 11) and three different temperatures range (10 °C, 25 °C and 35 °C) were taken to design different experimental set-ups. The pH of the media was adjusted using 1N solution of HCl and NaOH. The experimental set-ups were prepared using glass beakers of 500 ml capacity. The Hoagland's media were used as growth medium to support the growth of duckweed (0.5 g) that was inoculated in each experimental set-up. The influence of experimental condition on plant growth was assessed at the end of seventh day considering frond number and biomass gain. All experimental set-ups were established in triplicates and average of all the three observations was used to express the result.

2.2. Analytical methods

The frond number of *L.gibba* was calculated manually using strainer. The final weight was determined by weighing harvested duckweed at the end of seventh day. Experiments were carried out in triplicates and data were averaged with standard deviation (SD). SPSS[®] statistical package (Window Version 13.0) was used for data analysis. All statements reported in this study are at the $p < 0.05$ levels. The further optimization has been done using Fuzzy Logic Toolbox of MATLAB[®] R2012a.

2.3. Model structure and configuration

A general fuzzy system has basically four components: membership function (fuzzification), fuzzy rule base, defuzzification and fuzzy outputs. In fuzzification, numerical inputs and output variables are converted into linguistic terms or adjectives and the corresponding degrees of the one or more several membership functions are determined (Altunkaynak et al., 2005). Akkurt et al. (2004) have reported that fuzzy inference engine takes into account all the fuzzy rules in the fuzzy rule base and learns how to transform a set of inputs to corresponding outputs. Two kinds of inference operators, minimization (min) and product (prod), which are widely used in set theory (union and intersection), are basically employed in this step. The union and




Fig. 1. Fuzzy model structure

Download English Version:

<https://daneshyari.com/en/article/4388896>

Download Persian Version:

<https://daneshyari.com/article/4388896>

[Daneshyari.com](https://daneshyari.com)