

Available online at [www.sciencedirect.com](http://www.sciencedirect.com)

ScienceDirect

[www.elsevier.com/locate/jes](http://www.elsevier.com/locate/jes)

**JES**  
 JOURNAL OF  
 ENVIRONMENTAL  
 SCIENCES  
[www.jesc.ac.cn](http://www.jesc.ac.cn)

# Characterization of natural organic matter in water for optimizing water treatment and minimizing disinfection by-product formation

Qi Zheng<sup>1,2,\*</sup>, Xiaoqiu Yang<sup>1,2</sup>, Wenchao Deng<sup>1</sup>, X. Chris Le<sup>3</sup>, Xing-Fang Li<sup>3,\*</sup>

1. Key Laboratory of Optoelectronic Chemical Materials and Devices, Ministry of Education, School of Chemical and Environmental Engineering, Jiangnan University, Wuhan 430056, China. E-mail: [zq\\_1101@sina.com](mailto:zq_1101@sina.com)

2. Institute of Environment and Health, Jiangnan University, Wuhan 430056, China

3. Division of Analytical and Environmental Toxicology, University of Alberta, Edmonton, Alberta T6G 2G3, Canada

## ARTICLE INFO

Available online 23 March 2016

### Keywords:

Disinfection by-products (DBPs)  
 Dissolved organic carbon (DOC)  
 Dissolved organic matter (DOM)  
 Fluorescence  
 Natural organic matter (NOM)  
 Nitrification  
 Size exclusion chromatography  
 Total organic carbon (TOC)

## Introduction

Natural organic matter (NOM) present in source water has significant impact on water treatment processes and on the quality of drinking water. NOM is a complex mixture of diverse groups of organic compounds, humic and fulvic acids, proteins, peptides, carbohydrates, and heterogeneous materials decayed from terrestrial vegetation and aquatic organisms (Edwards, 1997; Barrett et al., 2000; Hwang et al., 2000). The presence of NOM in source water is a critical factor in the determination of both coagulant and disinfectant doses for water treatment (Edzwald, 1993; Matilainen et al., 2010; Rakruam and Wattanachira, 2014; Huang et al., 2015). NOM can act as a carbon source for the growth of microorganisms in water distribution systems (Edwards, 1997; Zhao et al., 2014). In

addition, many classes of organic compounds in NOM can react with disinfectants to form various disinfection by-products (DBPs). The type and amount of DBPs produced during water disinfection are highly dependent on the concentration and constituents of NOM in the source water (Barrett et al., 2000; Hua and Reckhow, 2007a; Krasner et al., 2006; Bull et al., 2011; Richardson and Postigo, 2012; Wang et al., 2016). Therefore, characterization of NOM in water is important for optimizing processes of water treatment and for minimizing the formation of toxic DBPs.

## 1. Techniques for the characterization of NOM

Examination of water color and turbidity, measurements of absorbance at an ultraviolet (UV) wavelength (e.g., 254 nm), and determination of dissolved organic carbon (DOC) can offer limited information about NOM in a water sample (Bennett and Drikas, 1993; APHA et al., 1998; Matilainen et al., 2011). Advanced instrumental techniques, such as gas chromatography mass spectrometry (GC–MS) (e.g., pyrolysis GC–MS), nuclear magnetic resonance (NMR) (e.g., <sup>13</sup>C solid state NMR), infrared spectroscopy (e.g., diffuse reflectance infrared Fourier transform), fluorescence spectroscopy, high performance size exclusion chromatography (HPSEC), and liquid chromatography with high resolution mass spectrometry (Vuoria et al., 1998; Her et al., 2003; Allpike et al., 2005; Chow et al., 2008; Peleato and Andrews, 2015; Tang et al., 2016; Richardson and Postigo, 2016), can provide further information on the composition of NOM.

In a recent study by Huang et al. (2016), the authors combined HPSEC separation with multi-wavelength absorption

\* Corresponding authors. E-mail: [xingfang.li@ualberta.ca](mailto:xingfang.li@ualberta.ca) (Xing-Fang Li).

detection to characterize dissolved organic matter (DOM) in a live water distribution system. The high performance size exclusion chromatography enabled the separation of DOM on the basis of apparent molecular weight (AMW) (Fig. 1). Absorbance detection simultaneously at multiple UV wavelengths, e.g., 210, 230, and 254 nm, provided complementary detection of DOM classes that may or may not contain aromatic moieties. Applications of this technique contributed to the characterization of molecular size fractions of DOM.

## 2. Characterization of DOM in a live water distribution system

While previous studies (Liu et al., 2010; Xing et al., 2012) have used HPSEC to characterize various organics related to the drinking water supply, Huang et al. (2016) applied the method to examine a drinking water distribution system in South Australia. From the water treatment plant to the consumers' water taps, the water supply distribution system consisted of a single long trunk main with branches to several remote communities. The source water was from River Murray. The main steps of the conventional treatment were coagulation, flocculation, sedimentation, filtration, UV disinfection, and chloramination. Chloramine was used as the secondary disinfectant to ensure that disinfectant residuals reached the end of the long distribution system and to provide protection against microbial contamination. The authors collected water samples from 17 sampling points across the water treatment plant and throughout the water distribution system. These samples from a live water distribution system allowed for the characterization of the changes of DOM, disinfectant residuals, and microbial cell counts. These measures also made it possible to study the associations between DOM and other water quality parameters.

The high performance size exclusion chromatography-ultraviolet (HPSEC-UV) analyses of raw water (Fig. 1a) and

treated water (Fig. 1b) show two broad peaks, corresponding to apparent molecular weight (AMW) of approximately 200–300 and 1000–1300 Da. The lower intensity of the higher AMW fraction (1000–1300 Da) in the treated water (Fig. 1b) as compared to the raw water (Fig. 1a) suggests that the water treatment processes were able to remove or destroy some of the higher molecular weight DOM. However, the treatment processes did not result in a decrease of the lower AMW (200–300 Da) DOM. In general, across treatment processes in the water treatment plant, changes were observed in the higher AMW fraction (1000–2000 Da). Along the water distribution system, changes were observed in the lower AMW fraction (200–300 Da). A comparison of the signals obtained from the detection at different wavelengths (210, 230, and 254 nm) also suggests that the treatment processes preferentially removed or destroyed the aromatic fraction of DOM (absorbance at 254 nm). These results are consistent with previous findings (Korshin et al., 2009; Xing et al., 2012).

## 3. Determination of microbial cells in the water distribution system

Huang et al. (2016) also measured the changes in microbial levels of water in the water treatment plant and in the distribution system. This was done by using flow cytometry analysis of fluorescently stained bacteria with SYTO-9 and with a bacterial viability kit (Hoefel et al., 2005). They found that the active bacterial concentration in the raw water was  $1 \times 10^7$  cells/mL. This was significantly decreased following the steps of water treatment and disinfection. Specifically, with the conventional water treatment (before disinfection), the active bacterial concentration was reduced to  $1 \times 10^6$  cells/mL. The subsequent disinfection process further reduced the active bacterial concentration to  $1 \times 10^4$  cells/mL. Thus, the overall water treatment processes resulted in a total of 3 log removal of the active bacterial cells.




Fig. 1 – Chromatograms obtained from the high performance size exclusion chromatography (HPSEC)-ultraviolet (UV) analyses of raw water (left graph) and treated water (right graph). Apparent molecular weight (AMW) was calibrated against the retention time response from polystyrene sulfonate standards. UV absorbance (Abs) was detected at 210, 230, and 254 nm. The vertical axis on the right shows the difference between the absorbance at 230 nm and the absorbance at 254 nm ( $A_{230} - A_{254}$ ). Reproduced with permission from Huang et al., 2016.

Download English Version:

<https://daneshyari.com/en/article/4453783>

Download Persian Version:

<https://daneshyari.com/article/4453783>

[Daneshyari.com](https://daneshyari.com)