



Production of high degree polymerized chitooligosaccharides in a membrane reactor using purified chitosanase from *Bacillus cereus*

Yu-Wei Lin, Yi-Chien Hsiao, Been-Huang Chiang *

Institute of Food Science and Technology, National Taiwan University, P.O. Box 23-14, Taipei, Taiwan, ROC

ARTICLE INFO

Article history:

Received 4 January 2009

Accepted 16 June 2009

Keywords:

Bacillus cereus
Chitosanase
Chitooligosaccharides
Chitohexaose
Membrane reactor

ABSTRACT

Crude chitosanase from *Bacillus cereus* NTU-FC-4 was separated by a cation exchanger to three fractions named CBCI, CBCII, and CBCIII. The CBCI hydrolyzed chitosan to yield dimers. The primary hydrolytic products of CBCII were low degree polymerized (DP) chitooligosaccharides. The CBCIII had the fastest reaction rate and yielded high DP chitooligosaccharides (heptamer and higher DP oligomers). When CBCIII was used in the ultrafiltration membrane reactor with enzyme/substrate ratio 0.06 unit/mg and 100 min of residence time (RT), the concentration of high DP oligomers was 9.78 mg/mL which occupied ca. 48% of total oligomers in the final product as compared to ca. 29% resulted from the crude enzyme. Decrease of RT to 50 min and 33 min, the high DP oligomers in the products were ca. 61% and 69%, respectively. This system could be operated for at least 24 h and kept a constant permeate flux and product output rate.

© 2009 Elsevier Ltd. All rights reserved.

1. Introduction

Chitooligosaccharides, formed with 2 to 10 glucosamines by β -(1 → 4) glycoside linkage, can be manufactured by hydrolyzing chitosan with chitosanase. Chitosanases are produced by many microorganisms, including fungi, actinomycetes, and bacteria (Boucher, Dupuy, Vidal, Neugebauer & Brzezinski, 1992; Fenton & Eveleigh, 1981; Izume, Nagae, Kawagishi, Mitsutomi, & Ohtakara, 1992; Seino, Tsukud, & Shimasue, 1991; Yamasaki et al., 1993; Yoshihara, Hosokawa, Kubo, Nishiyama & Koba, 1993). The bacterial chitosanases are especially useful for industrial applications because the enzyme can be easily prepared (Akiyama et al., 1999). However, most chitosanases from microorganism tended to hydrolyze chitosan and yield dimers, trimers and tetramers, rather than high degree polymerized (DP) oligomers (Park et al., 1999). For instance, chitosanase from *Matsuebacter chitosanotabidus* 3001 was able to hydrolyze chitosan to yield monomer to trimer (Park et al., 1999) and chitosanase from *Acinetobacter* sp. strain CHB101 yielded dimer and trimer (Shimosaka, Nogawa, Wang, Kumehara, & Okazaki, 1995). But it is known that high DP oligomers, such as chitopentaose, chitohexaose and chitoheptaose are more biologically active than the low DP ones (Suzuki et al., 1986; Suzuki, Tokoro, Okawa, Suzuki & Suzuki, 1986; Tokoro et al., 1989).

Among the bacteria, the *Bacillus* sp. is particularly useful for the chitosanase production. Chitosanases with different activities and characteristics were produced by *Bacillus* sp. isolated from plants

and soil, including *Bacillus cereus* S1 (Kurakake, Yo-u, Nakagawa, Sugihara, & Komaki, 2000), *Bacillus* sp. strain KFB-C108 (Yoon, Ha, Lim, & Cho, 1998), *Bacillus subtilis* KH-1 (Omumasaba, Yoshida, Sekiguchi, Kariya, & Ogawa, 2000), *B. subtilis* IMR-NK1 (Chiang, Chang, & Sung, 2003), *Bacillus* sp. strain KCTC 0377BP (Choi, Kim, Piao, Yun, & Shin, 2004), *B. subtilis* TKU007 (Wang & Yeh, 2008) and *B. cereus* D-11 (Gao, Ju, Jung, & Park, 2008). The major concerns of selection of bacteria for the production of chitosanase are always the high specificity activity and good yield of high DP chitooligomers because they are very important for industrial application.

Besides selection of bacteria for chitosanase production, there are other methods which may be used to increase specific activity of enzyme and the yield of high DP chitooligomers. The crude enzyme can be purified to increase its specific activity and to remove the fractions which are not suitable for the production of high DP oligomers. In addition, a proper reactor which can control the progress of hydrolysis reaction may also facilitate the high DP oligomers production. Ming and coworkers used an immobilized enzyme bioreactor for high DP chitooligomers production. By removing the immobilized enzyme from the reaction mixture when the target pentamers and hexamers reached a maximum, the yield of high DP oligomers was increased in the batch reaction (Ming, Kuroiwa, Ichikawa, Sato, & Mukataka, 2006). Kuo, Chen, and Chiang (2004) demonstrated that chitooligomers could be produced by a continuous membrane reactor (Kuo et al., 2004). In the continuous membrane bioreactor, enzyme is recycled and reused while the product of enzymatic hydrolysis is continuously withdrawn as permeate. The membrane reactor separates the products (oligomers) from enzyme during processing thus preventing the high DP oligomers being further hydrolyzed by

* Corresponding author. Tel.: +886 2 33664120; fax: +886 2 23620849.

E-mail address: bhchiang@ntu.edu.tw (B.-H. Chiang).

the enzyme. Therefore, the yield of high DP oligomer might be increased if the bioreactor was operated at a proper residence time.

This study aimed to investigate the characteristics of the chitosanases purified from the crude enzyme of *B. cereus* NTU-FC-4, and the possibility of using the purified enzyme in the membrane reactor for producing high DP chitooligosaccharides.

2. Materials and methods

2.1. Raw materials

Chitosan with 95% deacetylation was obtained from the Lytone Enterprise Inc. (Taipei, Taiwan). Both of chitin and glucosamine were purchased from the Sigma Chemical Co. (St. Louis, MO, USA). The soytone and yeast extract were from Difco Laboratories (Detroit, MI, USA). Acetonitrile was purchased from the Tedia Co. (Fairfield, OH, USA). Pure chitooligosaccharides, including dimer, trimer, tetramer, pentamer, and hexamer, were purchased from the Seikagaku Co. (Tokyo, Japan). CM-Sepharose Fast Flow gel was obtained from Pharmacia (Uppsala, Sweden).

2.2. Preparation of crude enzyme

The crude enzyme was extracted from the *B. cereus* NTU-FC-4, which was cultured in a pH 6.24 broth medium, containing 0.3% colloidal chitin, 0.5% yeast extract, 0.5% soytone, 0.1% sodium dihydrogen phosphate and 0.05% magnesium sulfate. After incubation at 30 °C for 2 days in a shake incubator, the culture was centrifuged at 4 °C and 6200 rpm for 30 min to remove bacteria and colloidal chitin. The crude enzyme was precipitated by 70% acetone and dried by lyophilization (FLEXI-DRY™, FTS system Co., New York, USA) (Kuo et al., 2004).

2.3. Separation of chitosanase by ion-exchange chromatography and gel electrophoresis

The crude enzyme was applied to a CM-Sepharose Fast Flow column (2.6 cm × 20 cm) which had been equilibrated with 20 mM acetate buffer (pH 5.0). The adsorbed proteins were eluted by a linear gradient of NaCl from 0 to 1 M in 20 mM acetate buffer (pH 5.0) at a flow rate of 66 mL/h. Fractions containing the major chitosanase activity were collected and dried by lyophilization. SDS–polyacrylamide gel electrophoresis using 12.5% acrylamide was performed and stained by Coomassie blue-R250. The sheets were destained with a destaining solution (acetic acid/methanol/water, 1/3/6, v/v). A pre-stained protein standard (SeeBlue Plus2, Invitrogen Co. Carlsbad, CA) was used during SDS–PAGE for determining the molecular weights of the separated proteins.

2.4. Enzymatic reaction pattern in bulk aqueous system

An amount of 15 unit of enzyme was dissolved in 1 mL acetate buffer solution (50 mM, pH 5.0) and mixed with 5 mL of 10 mg/mL chitooligomer standards which was dissolved in the same buffer. The mixture was incubated at 40 °C in a reciprocating shaker bath (100 rpm), and the NANOSEP (Pall Gelman Sci., MI, USA) was employed to remove the enzyme to stop the enzymatic reaction. At various time intervals, samples (1 mL) were taken, and then centrifuged for 10 min using NANOSEP micro-concentrator. The concentrations of chitooligomers in the filtrate were analyzed by HPLC.

2.5. Membrane reactor system

A hollow fiber UF membrane module (AG Technology, MA, USA) with molecular weight cut-off 3000 dalton and 0.042 m² effective

membrane area was coupled with a 1 L jacked glass stirred tank to build the membrane reactor. A peristaltic pump was installed between membrane and reaction tank to circulate solution through the system. Warm water from a water bath flowed continuously through the jacked of tank to maintain a constant reaction temperature at 45 °C. For the substrate preparation, proper amount of chitosan was dissolved in 0.2 M acetate buffer at pH 5.0 to obtain a 20 mg/mL of chitosan solution. During operation, the chitosan solution was charged to the reaction tank along with proper amount of enzyme. The enzymatic reaction was first proceed for 5 min in the reaction tank to reduce the viscosity of the chitosan solution; then the pump was turned on to pump the mixture in the reaction tank through the membrane module. The permeate was diverted to a collection vessel and the retentate was returned to the reaction tank for further reaction. The substrate solution (chitosan solution) was continuously fed to the reaction tank from a substrate tank at a rate equals to the permeation rate to maintain a constant volume and substrate concentration of the mixture in the reactor (Kuo et al., 2004).

2.6. Enzyme assay methods

Chitosanase activity was determined by adding 1 mL of 1% (W/V) chitosan solution and 3.5 mL of 0.2 M acetic buffer at pH 5.0 to 0.5 mL of the enzyme solution. After shaking (100 rpm) the mixture at 45 °C for 30 min, the sample was boiled for 15 min to stop enzyme reaction and analyzed its reducing sugar content. One unit of chitosanase activity was defined as the amount of enzyme needed to hydrolyze 1% (W/V) chitosan solution and produce 1 μmol reducing sugar per minute at 45 °C. The method suggested by Imoto and Yagishita (1971) was used to determine the reducing sugar content and the glucosamine as standard. Lowry method (Lowry, Rosebrough, Farr, & Randall, 1951) was used to analyze the protein content for determining the specific activity of the enzyme.

2.7. HPLC analytical methods

An ICI HPLC system (LC1100 pump, Australia) equipped with RI detector was used for analyzing chitooligosaccharides content. The chitooligosaccharides were separated on a HYPERSIL HS APS column (Thermo Instrument Systems Inc., Runcorn, UK, 25 cm × 4.6 mm), eluted by acetonitrile and distilled water (60/40) mixture with a flow rate of 0.8 mL/min at 40 °C. The retention time and concentration of each individual peak in the sample was compared to the peak of standard chitooligosaccharides with DP 1–6. However, the pure compounds of heptamer and octamer were not available, therefore, the higher DP chitooligomers were identified by the sequence of peaks appeared in the HPLC chromatogram, and the concentrations of these chitooligomers were estimated based on the standard curve of hexamer.

3. Results and discussion

3.1. Purification of chitosanases from crude enzyme extract

For purification, the crude enzyme was first precipitated by acetone. The acetone precipitation could eliminate nearly 90% of the non-chitosanase protein, thus the specific activity of chitosanase increased from 0.46 unit/mg to 3.69 unit/mg and the yield of total enzyme activity was 81.37%. The crude enzyme was then separated by CM-Sepharose ion-exchange column using sodium chloride gradient from 0 to 1 M, and the three fractions obtained were named CBCI, CBCII and CBCIII (Fig. 1). It appeared that CBCII was a minor enzyme as compared to CBCI and CBCIII. The three fractions of

Download English Version:

<https://daneshyari.com/en/article/4562794>

Download Persian Version:

<https://daneshyari.com/article/4562794>

[Daneshyari.com](https://daneshyari.com)