



Utilisation of broken rice and cocoyam flour blends in the production of biscuits

L.C. Okpala*, P.N. Ekwu

Department of Food Science and Technology, Ebonyi State University, Abakaliki, Ebonyi State, Nigeria

Available online 23 May 2015

Abstract

Biscuits were produced from five broken rice and cocoyam flour blends which were: (1) 100% cocoyam flour, (2) 25% cocoyam flour:75% broken rice flour, (3) 50% cocoyam flour: 50% broken rice flour, (4) 75% cocoyam flour: 25% broken rice flour and (5) 100% broken rice flour. Biscuits made with 100% wheat served as the control. Functional properties of the flour blends were analysed while proximate composition, physical properties and sensory quality of the biscuits produced were also determined. Significant differences ($p < 0.05$) in the functional properties existed among the flour blends. Proximate content ranged as follows: protein: 7.18–10.54%; ash: 1.46–1.75%; fat: 11.17–18.52%; moisture: 6.56–7.89%; fibre: 1.15–1.23% and carbohydrates: 58.71–65.97%. Biscuits made with wheat flour did not differ significantly ($p > 0.05$) from those made with 50% cocoyam and 50% broken rice flour blend with respect to the physical properties and sensory quality.

© 2015 Association of Vice-Chancellors of Nigerian Universities. Production and hosting by Elsevier B.V. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

Keywords: Wheat; Physical properties; Sensory quality

1. Introduction

Biscuits are one of the most popular bakery products made from cereals that are consumed by nearly all people in the world. They are snacks produced from palatable dough that is transformed into an appetising product through the application of heat in the oven (Kure et al., 1998). They are made from flour, sugar, milk, fat, flavouring agents and other chemical additives. Sometimes bakery products are used as vehicles for the incorporation of different nutritionally rich ingredients (Sudha et al., 2007).

Wheat flour, the main ingredient for biscuit production is imported by countries with unfavourable climates for growing wheat. This importation has placed a considerable burden on the foreign exchange reserves of the economies of such importing countries. This has led to the development and use

of composite flours for production of biscuits, bread and pastry products. Composite flour has been defined as a mixture of several flours obtained from roots and tubers, cereals, legumes etc. with or without the addition of wheat flour (Adeyemi and Ogazi, 1985).

Rice is a cereal which is used mainly for human food. The milling process of rice causes some loss of nutrients and breakage of some rice resulting in “broken rice.” Little attention has been paid to the use of broken rice in Nigeria. Indeed, it is underutilised and often referred to as “poor man’s food” in some societies because it is cheaper than unbroken rice and purchased mainly by those who cannot afford unbroken rice. Bean et al. (1983) reported that rice is free from allergens and is widely used in baby foods and other products. The use of flour from broken rice in products could significantly increase the utilisation of broken rice grains; thereby reducing losses that are normally incurred with the locally processed rice grains in Nigeria.

Cocoyam is an edible root crop grown in the tropics of which Nigeria is a major producer. The flour has been used in baking and its fine granular starch improves binding and reduces breakage of

*Corresponding author.

E-mail address: lcokpala@yahoo.com (L.C. Okpala).

Peer review under responsibility of Association of Vice-Chancellors of Nigerian Universities.

snack products (Huang, 2005). *Xanthosoma* sp of cocoyam, like broken rice grains is underutilised in Nigeria.

This work seeks to use flour blends produced from *Xanthosoma* spp of cocoyam and broken rice to produce biscuits with the aim of reducing complete dependence on the importation of wheat.

2. Materials and methods

Cocoyam (*Xanthosoma* sp.), wheat flour and other ingredients used for baking were purchased from a retail outlet in Abakaliki, Ebonyi State, Nigeria. Broken rice grains were procured from Ebony Agro Industries, Ikwo L.G.A., Ebonyi State, Nigeria.

2.1. Sample preparation

2.1.1. Cocoyam flour (CF) preparation

Cocoyam flour was produced as described by Okpala et al. (2013). The corms were washed, peeled, sliced and blanched at 80 °C. They were sun dried and milled in a hammer mill (Stedman, Model 20 × 12) to pass through a 40-mesh sieve (British standard). Flour was stored in airtight plastic containers at room temperature (28 °C; 24% R.H.) until needed.

2.1.2. Broken rice flour (BRF) preparation

The broken rice grains were cleaned by manually removing extraneous materials. The rice grains were washed with potable water; sun dried and milled using a hammer mill to pass through a 40-mesh sieve. Flour was stored in airtight plastic containers at room temperature until needed.

2.1.3. Formulation of flour blends

Five blends were prepared by mixing CF with BRF in the percentage proportions of 100:0, 75:25, 50:50, 25:75 and 0:100 respectively. Hundred per cent (100%) wheat flour formulation was served as the control.

2.1.4. Biscuit preparation

The ingredients used were: flour: 46.7%; vegetable fat: 18.7%; sugar: 11.7%; egg: 14.6%; milk: 7.0%; nutmeg: 0.1%; vanilla: 0.2%; salt: 0.5% and baking powder: 0.5%. Fat and sugar were creamed using an electric hand mixer (Kenwood HM 220) at medium speed for 5 min. Eggs and milk were added while mixing and then mixed for a total of about 30 min. Vanilla, nutmeg, flour, baking powder and salt were mixed thoroughly and added to the cream mixture where they were all mixed together to form a dough. The dough was rolled and cut using a circular shaped cookie cutter of 5 cm diameter. Baking was carried out in an electric oven (Gallenkamp oven 300 plus series) at 185 °C for 20 ± 5 min. Biscuit samples were cooled and stored in airtight containers until needed. Biscuits were made from wheat to serve as a control.

2.2. Proximate analysis

Protein, fat, moisture, fibre and ash were determined using methods described by AOAC (2000). Carbohydrate content was determined by difference.

2.3. Functional properties of flour blends

Water and oil absorption capacities were determined according to the methods described by Beauchat (1977). Bulk density and emulsion capacity were determined using methods described by Onwuka (2005).

2.4. Physical properties

Weight of biscuits was determined using an analytical weighing balance (Mettler MS 104S). Spread ratio was expressed as diameter/thickness (McWatters et al., 2003). Break strength of the biscuits was determined as described by Okaka and Isieh (1990) with slight modifications. Biscuit from each formulation was placed centrally between two parallel wooden bars. Another wooden bar was placed on the biscuit. Weights were then placed incrementally on the bar until the biscuit fractured. Break strength of the biscuit was regarded as the least weight that caused the breaking of the biscuit.

2.5. Sensory evaluation

Sensory evaluation was carried out using twenty semi-trained panellists (students of the Ebonyi State University, Abakaliki) who were regular consumers of biscuits and were not allergic to any food. Samples were scored for appearance, taste, texture, crispness and general acceptability on a 9-point hedonic scale with 1 representing dislike extremely, 5, neither like nor dislike and 9 like extremely (Ihekoronye and Ngoddy, 1985).

2.6. Statistical analysis

The data collected were subjected to analysis of variance (ANOVA). Means were separated using Duncan's new multiple range test (DNMRT) using the Statistical Package for the Social Sciences (SPSS) version 17.0 (SPSS Inc., Chicago, IL, USA).

3. Results and discussion

3.1. Functional properties of flour blends

Functional properties of the flour samples are presented in Table 1. Bulk density of the flour samples ranged from 0.66 to 0.91 g/cm³. Sample from 100% wheat (100W) had the highest value of 0.91 g/cm³ while the blend of 75% cocoyam: 25% broken rice flour (75CF:25BRF) had the least value of 0.66 g/cm³. There was no significant difference ($p > 0.05$) in the bulk density of the blends. Bulk density gives an indication of the relative volume and type of packaging material required (Udensi and Okoronkwo, 2006). Oil absorption capacity of the samples were high and ranged from 2.24 to 2.96 g/g with the control having the highest

Download English Version:

<https://daneshyari.com/en/article/4565656>

Download Persian Version:

<https://daneshyari.com/article/4565656>

[Daneshyari.com](https://daneshyari.com)