

Accepted Manuscript

Drawing down the remaining copper inventory in a leach pad by way of subsurface leaching

Dale F. Rucker, Robert J. Zaebst, Jim Gillis, Joseph C. Cain, Bruce Teague



PII: S0304-386X(16)30662-4
DOI: doi: [10.1016/j.hydromet.2017.02.024](https://doi.org/10.1016/j.hydromet.2017.02.024)
Reference: HYDROM 4530
To appear in: *Hydrometallurgy*
Received date: 20 September 2016
Revised date: 23 February 2017
Accepted date: 27 February 2017

Please cite this article as: Dale F. Rucker, Robert J. Zaebst, Jim Gillis, Joseph C. Cain, Bruce Teague , Drawing down the remaining copper inventory in a leach pad by way of subsurface leaching. The address for the corresponding author was captured as affiliation for all authors. Please check if appropriate. Hydrom(2017), doi: [10.1016/j.hydromet.2017.02.024](https://doi.org/10.1016/j.hydromet.2017.02.024)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Drawing down the remaining copper inventory in a leach pad by way of subsurface leaching

Dale F. Rucker^{1*}, Robert J. Zaebst², Jim Gillis³, Joseph C. Cain IV¹, Bruce Teague²

¹hydroGEOPHYSICS, Inc., Tucson, AZ USA

drucker@hgiworld.com

druck8240@gmail.com

²Carlota Copper Company, Miami, AZ, 85539, USA

³Metallurgical Consultant, Miami, AZ, 85539, USA

*Corresponding Author

Keywords: copper, leach, inventory, modeling, monitoring

Abstract

A significant amount of metal inventory can reside in a leach pad due to unfavorable metallurgical and hydraulic conditions. Continued leaching using surface irrigation will likely be unsuccessful at recovery in any reasonable time frame. In this work, we investigate how subsurface leaching (SSL), using wells to facilitate the delivery of barren solution, could potentially increase recovery and drawdown the inventory in a shorter period of time. An initial characterization campaign of the leach pad using drilling and assaying along with geophysical methods showed that inventory was high because the ore remained dry from compaction. Other areas were also shown to have preferential flow paths as a means to drain solution out of the leach pad. Assaying results taken from sonic coring and auger cuttings, and extrapolated across the leach pad, revealed a potential of 37×10^6 kg of acid soluble copper.

Our investigation covers the first 1000 days of SSL, with 110 PVC wells distributed across five main areas. During this time, we estimate production at 2.26×10^6 kg of copper based on the amount of solution introduced through the wells multiplied by the average copper grade from a number of sources, including monitoring wells and newly formed side slope seeps. Some areas performed better than others, especially where assays revealed that acid soluble copper was greater than 50% of total copper. The SSL program is expected to continue for at least another 1000 days, and we expect an additional 7×10^6 to 15×10^6 kg will be withdrawn from inventory.

Download English Version:

<https://daneshyari.com/en/article/4769349>

Download Persian Version:

<https://daneshyari.com/article/4769349>

[Daneshyari.com](https://daneshyari.com)