



Available online at www.sciencedirect.com

ScienceDirect



Procedia Computer Science 79 (2016) 781 - 784

7th International Conference on Communication, Computing and Virtualization 2016

DDoS Attack Analyzer: Using JPCAP and WinCap

Pankaj Shinde^a, Thaksen J. Parvat^b,

Computer Engineering
Sinhgad Institute of Technology, Lonavala
S.P.Pune University, (M.S) INDIA- 410401

apankaj.mb.shinde@gmail.com.bpthaksen.sit@sinhgad.edu

Abstract

Nowadays, Computers and their Networks leads to being complex and diverse systems that communicate with speed and flexible. There is always room for sophisticated and highly specific network/Packet analyzing tool. Network traffic monitoring is not as straight as they written in theory but also leads to many trends changing changes. Tools are also able to provide the statics and graphic representation of risk and reports. While developing the tools, it is highly important to understand the intrusion attacks conditions, network protocols and systems behavior, the intension of user and user conformability. We are proposing the network traffic detection and analyzing tools that mainly focus on the DDoS attack. We are using JPCAP packet capturing library with WinCap for Detection and analysis of network traffic on a prime target of DDoS Attack.

© 2016 The Authors. Published by Elsevier B.V. This is an open access article under the CC BY-NC-ND license (http://creativecommons.org/licenses/by-nc-nd/4.0/).

Peer-review under responsibility of the Organizing Committee of ICCCV 2016

Keywords: Sniffer; Packet Capture; Jpcap; WinCap; Intrusion Detection; DDoS Attacks.

Packet Analyzer or sniffer for the collecting the data [request and response]which traverse the network among the various network devices as well end user systems.[11] These sniffers work on the different protocol data. As data streams flow across the network, the sniffer captures each packet and, if needed, decodes the packet's raw data, showing the values of various fields in the packet, and analyzes its content according to the appropriate RFC or other specifications[3][2]. While analyzing, sniffers encountered packages that should not be part of data or which additionally holding in data for of intrusion, viruses, misbehaviors or any policy violation. Those include network statistics tools, intrusion detection, port knocking daemons, password sniffers, ARP poisoners, trace routers, etc.[1].

* Corresponding author. Tel.: +91 989-001-2124; E-mail address: Pankaj.mb.shinde@gmail.com

Peer-review under responsibility of the Organizing Committee of ICCCV 2016 doi:10.1016/j.procs.2016.03.103

A Distributed Denial of Service (DDoS) attack is an attempt to make an online service unavailable by overwhelming it with traffic from multiple sources.[10][5] They target a wide variety of significant resources, from banks to news websites and present a major challenge to making sure people can publish and access relevant information. [4]. This paper is arranged in section I as an Understanding of WinCap and Jpcap, Section II for proposed algorithm and Section III Experimental Details, followed by Section IV presents results of experiments.

1. WinCap and Jpcap

Windows Packet Capture provides the facility to access low-level network in Windows operating environment. It can transmit network traffic along with protocol stack and process. It allows kernel-level packet filtering. It is windows network utility drivers, which offers low-level network access along with control of kernel of doing it. It been used commercially for many systems as well it also having UNIX version as libcap. As the tools protocol analyzer, traffic analyzer, network traffic monitor, intrusion detection system and mainly in sniffers are integrated by WinCap.[13][14][6]

Java based open source library that implemented in C and Java for access network traffic like capturing and sending over the network. It is mainly used in Java based application along with the WinCap [Windows]/libcap[UNIX]. Jpcapcaptures Ethernet, TCP, and UDP, IPv4, IPv6, ICMP, ARP/RARP packets, etc. It has been tested on Microsoft Windows (98/2000/XP/Vista), Linux (Fedora, Ubuntu), Mac OS X (Darwin), FreeBSD, and Solaris [9] with successful results.[12]

Jpcap is the collection of java class and interfaces. This collection hides unnecessary details from the user of network traffic capturing, sending across a network, abstracting in protocols. Jpcap is internally handling by many network class and interfaces along with their binding. Java native interface plays a vital role in the binding of all collection of class as interfaces together as the component.[8]

Jpcap on the Java side is made up of several Java classes. These classes peer with native C structures provided by libpcap.[7] So for example, when user retrieves an instance of Pcap object, the object contains a memory pointer to a C pcap_t structure.[7] When any non-static method call on the Java class, will use the stored reference to the native C structure to execute the requested function. Same thing applies to all other structures such as Pcap, If and the remaining. They are all peered and retain a memory reference to their corresponding C structure.[7] For safety purposes and Java protections, the reader is not allowed to access these C structures directly, and all the corresponding *libpcap* library functions are provided as Java methods. Therefore, the is a very close relationship between each Java object and its corresponding native C structure, the same applies to *libpcap* functions and their corresponding Java methods.

We are using the WinCap to get traffic into the system to analyze and to detect particular DDoS. At the functional level, jpcap will analyze the packets by checking out threshold value that likely decides the income packages are suspicious, or they be normal traffic.

2. Proposed Algorithm

1. Obtain and open the network.

NetworkInterface[] device = jpcapCaptor.getDeviceList(); captor=JNetPcapCaptor.openDevice(device[index], snaplen, promics, timeout); where snaplen= Maximum number of bytes, promics= mode to get traffic, timeout=timeout values in milliseconds.

2. Set the traffic type wireless or Ethernet.

It will allow the user to monitor traffic type either of wireless or Ethernet LAN.

3. Set threshold or it will calculate by default.

4. Check incoming traffic

Download English Version:

https://daneshyari.com/en/article/484264

Download Persian Version:

https://daneshyari.com/article/484264

<u>Daneshyari.com</u>