

Accepted Manuscript

Effect of bottom ash at different ratios on hydraulic transportation of fly ash during mine fill

Radha Rani, Manish Kumar Jain

PII: S0032-5910(17)30313-3
DOI: doi:[10.1016/j.powtec.2017.04.025](https://doi.org/10.1016/j.powtec.2017.04.025)
Reference: PTEC 12489

To appear in: *Powder Technology*

Received date: 27 September 2016
Revised date: 22 March 2017
Accepted date: 5 April 2017



Please cite this article as: Radha Rani, Manish Kumar Jain, Effect of bottom ash at different ratios on hydraulic transportation of fly ash during mine fill, *Powder Technology* (2017), doi:[10.1016/j.powtec.2017.04.025](https://doi.org/10.1016/j.powtec.2017.04.025)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

**EFFECT OF BOTTOM ASH AT DIFFERENT RATIOS ON HYDRAULIC
TRANSPORTATION OF FLY ASH DURING MINE FILL**

Radha Rani and Manish Kumar Jain

Department of Environmental Science and Engineering, Centre of Mining
Environment, Indian School of Mines, Dhanbad, Jharkhand, 826004, India

Corresponding Author - Email: radharani@ese.ism.ac.in

Download English Version:

<https://daneshyari.com/en/article/4910600>

Download Persian Version:

<https://daneshyari.com/article/4910600>

[Daneshyari.com](https://daneshyari.com)