



Research and application of a hybrid wavelet neural network model with the improved cuckoo search algorithm for electrical power system forecasting



Liye Xiao^a, Wei Shao^{a,*}, Mengxia Yu^a, Jing Ma^b, Congjun Jin^b

^aSchool of Physical Electronics, University of Electronic Science and Technology of China, Chengdu, China

^bScience and Technology on Special System Simulation Laboratory, Beijing, China

HIGHLIGHTS

- Propose a hybrid model that can be used to forecast the complex electrical power system.
- Enhance the speed of local convergence and the accuracy of finding the optimal solution of CS.
- Use more accurate metrics to assess the forecasting performance of the proposed model.

ARTICLE INFO

Article history:

Received 3 November 2016

Received in revised form 11 April 2017

Accepted 15 April 2017

Keywords:

Electrical power system

Hybrid model

Improved cuckoo search algorithm

Short-term electricity price forecasting (STEPF)

Short-term load forecasting (STLF)

Short-term wind speed forecasting (STWSF)

ABSTRACT

Electricity forecasting plays an important role in the operation of electrical power systems. Many models have been developed to obtain accurate forecasting results, but most of them focus more on a single forecasting indicator, such as short-term load forecasting (STLF), short-term wind speed forecasting (STWSF) or short-term electricity price forecasting (STEPF). In this paper a new hybrid model based on the singular spectrum analysis (SSA) and modified wavelet neural network (WNN) is proposed for all the short-term load forecasting, short-term wind speed forecasting and short-term electricity price forecasting. In this model, a new improved cuckoo search (CS) algorithm is proposed to optimize the initial weights and the parameters of dilation and translation in WNN. Case studies of half-hourly electrical load data, 10-min-ahead wind speed data and half-hourly electricity price data are applied as illustrative examples to evaluate the proposed hybrid model, respectively. Experiments show that the hybrid model resulted in 46.4235%, 31.6268% and 25.8776% reduction in the mean absolute percentage error compared to the comparison models in short-term load forecasting, short-term wind speed forecasting and short-term electricity price forecasting, respectively.

© 2017 Elsevier Ltd. All rights reserved.

1. Introduction

In energy systems, short-term load forecasting (STLF), short-term wind speed forecasting (STWSF) or short-term electricity price forecasting (STEPF) plays an important role in electrical power system operation [1]. Accurate forecasting of them seems to be a difficult task due to many unavoidable factors (e.g., activities, climate, weather and season).

Up to now most of the forecasting models focus more on the forecasting of a single indicator, STLF, STWSF or STEPF. Actually, STLF yields the basic information for scientific operations of an electrical power system, STWSF directly influences the electricity

generation from wind power [2], and STEPF provides price reference for market participants [3].

In recent decades, many studies on STLF, STWSF and STEPF have been presented, and the forecasting methods can be divided into three categories [4]: (a) statistical models; (b) artificial neural networks (ANNs); and (c) hybrid forecasting models.

Statistical models are built based on statistical equations to get the potential change rule from history data sampling [4–10]. However, these models cannot address special and nonlinear events effectively because of their own weaknesses [11,12], and certain hypotheses must be developed based on the characteristics of the load data prior to forecasting. Overestimation of the future load pattern can cause the start-up of additional or unnecessary generating units, resulting in increased costs for reserves and operation. Underestimation of the future load pattern will result in an inability to provide the required operating reserves and to maintain the

* Corresponding author at: School of Physical Electronics, University of Electronic and Technology of China, Chengdu 610000, China.

E-mail address: weishao@uestc.edu.cn (W. Shao).

Nomenclature

α	step size of CS	y_n	observed value of the n th datum
a_j	scaling factor of the wavelet basis function	\hat{y}_n	predicted value of the n th datum
A_n	forecasting accuracy of the n th datum	Y	predicted output of WNN
b_j	translation factor of the wavelet basis function	$Z_{\alpha/2}$	upper (or positive) z -value
C	input of WNN	$-Z_{\alpha/2}$	under (or negative) z -value
δ	convergence tolerance of BFGS	Abbreviation	
d_t	search direction of BFGS	AA	adaboost algorithm
DM	statistic value	ANN	artificial neural network
D_t	symmetric matrix at x^t	BPNN	back propagation neural network
ε_n	forecasting error of the n th datum	BFGS	Broyden-Fletcher-Goldfarb-Shanno
F_i	fitness function of nest i	CPSO	chaotic particle swarm optimization
g	current iteration number of CS	CS	cuckoo search
Gen_{Max}	maximum number of iterations	CS-WNN	cuckoo search-optimized wavelet neural network
h_j	wavelet basis function	DM	Diebold-Mariano
$h(j)$	output of the j th hidden layer node	EA	evolutionary algorithm
H	continuous function	EEMD	ensemble empirical mode decomposition
$Iter_{max}$	maximum number of iterations of BFGS	EMD	empirical mode decomposition
K	number of lagged vectors	FEEMD	fast ensemble empirical mode decomposition
K^*	maximum between L and K	FVD	forecasting validity degree
L	windows length	GA	genetic algorithm
L^*	minimum between L and K	GABPNN	genetic-algorithm-optimized back propagation neural network
m^k	k th-order forecasting effectiveness unit	MAE	mean absolute error
M	number of repetitions of each trial	MAPE	mean absolute percentage error
λ_t	step length of BFGS	MSE	mean square error
n	number of host nests	PSO	particle swarm optimization
N	length of a time series	RBFNN	radical basis function neural network
p_a	parameters of the cuckoo search algorithm	SA	simulated annealing
t	current iteration number of BFGS	STEPF	short-term electricity price forecasting
w_{ij}	connection weights between the input layer and hidden layer	STLF	short-term load forecasting
x_i^t	cuckoo i at iteration t	STWSF	short-term wind speed forecasting
x_i	nest i	WNN	wavelet neural network
X	trajectory matrix		
y	expectation of the observed values		

stability of the system, likely triggering a breakdown of the power system network [13]. Recently, ANNs with high adaptability to nonlinear series have attracted the interest of researchers in the areas of STLFL, STWSF and STEPF [14–19].

Meanwhile, to decrease the negative influences that are intrinsic to individual models, many hybrid approaches that combine the advantages of individual ones have been proposed [20–24].

To achieve higher forecasting accuracy, some data-processing algorithms, such as empirical mode decomposition (EMD) [25], the ensemble empirical mode decomposition (EEMD) algorithm [26] and the fast ensemble empirical mode decomposition (FEEMD) algorithm [27], have been employed in ANNs to build hybrid models. The data decomposition, which could reduce the non-stationary feature of the original data, promotes the forecasting performance indirectly.

Moreover, intelligent optimization algorithms including the chaotic particle swarm optimization (CPSO) [28], the genetic algorithm (GA) [29], the particle swarm optimization (PSO) [30], the evolutionary algorithm (EA) [31] and the adaboost algorithm (AA) [32], have been utilized to determine the initial weights and thresholds of ANNs. In 2009, Yang proposed a meta-heuristic cuckoo search (CS) algorithm that integrates the Lévy flight observed in certain species of birds with cuckoo breeding behavior [33]. In various fields [34–40], CS has been demonstrated to successfully solve optimization problems. Simultaneously, the superior availability of CS over other optimization algorithms such as PSO and GA has been proven with benchmark functions [41,42]. Yang and Deb analyzed the causes of the efficiency of CS in [33].

Based on the outstanding features of CS (including broad applicability, quick convergence, robustness to dynamic changes, ease of implementation, conceptual simplicity, ease of hybridization with other methods, and the ability to solve problems with no definite solutions), a combined forecasting model with weight coefficients determined by CS provides more accurate results than other individual models [43].

For a whole electrical power system, different forecasting models to obtain corresponding indicators possibly result in inconvenience and inefficiency for planning and management of grids. Thus, it is required to build a widely applicable model to achieve accurate results for STLFL, STWSF and STEPF. Among various ANN models, the wavelet neural network (WNN) is a good choice to achieve high convergence rates and accurate results [44]. In this paper, a modified WNN model with the singular spectrum analysis (SSA), which is used to decompose the original data, is proposed for all of STLFL, STWSF and STEPF. In the modified WNN model, an improved CS algorithm, which is on the basis of Broyden-Fletcher-Goldfarb-Shanno (BFGS) quasi-Newton method to speed up the local convergence in the late period of optimization, is introduced to optimize the initial weights and the parameters of dilation and translation.

To evaluate the proposed model, the half-hourly electric load and electricity price data from New South Wales, the State of Queensland and the State of Victoria in Australia and the wind data from four wind power stations in Penglai, China for multi-step forecasting are used as test data, respectively. The main contributions in this paper are demonstrated as follows.

Download English Version:

<https://daneshyari.com/en/article/4911087>

Download Persian Version:

<https://daneshyari.com/article/4911087>

[Daneshyari.com](https://daneshyari.com)