

## Accepted Manuscript


Title: Suspended timber ground floors: heat loss reduction potential of insulation interventions

Authors: S. Pelsmakers, C.A. Elwell

PII: S0378-7788(17)31135-0  
DOI: <http://dx.doi.org/doi:10.1016/j.enbuild.2017.07.085>  
Reference: ENB 7825

To appear in: *ENB*

Received date: 30-3-2017  
Revised date: 21-7-2017  
Accepted date: 28-7-2017



Please cite this article as: S.Pelsmakers, C.A.Elwell, Suspended timber ground floors: heat loss reduction potential of insulation interventions, Energy and Buildings <http://dx.doi.org/10.1016/j.enbuild.2017.07.085>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

# Suspended timber ground floors: heat loss reduction potential of insulation interventions

Pelsmakers, S.<sup>1\*</sup>, Elwell, C.A.<sup>2</sup>

1. Sheffield School of Architecture, University of Sheffield, Western Bank, Sheffield, S10 2TN, UK

2. UCL Energy Institute, 14 Upper Woburn Place, London WC1H 0NN, UK

\* Corresponding author: s.pelsmakers@sheffield.ac.uk

## Abstract

There are approximately 10 million suspended timber ground floor constructions in the UK and millions more globally. However, it is unknown how many of these floors are insulated and their performance has not been widely investigated. This study investigates the impact of retrofitting insulation on the thermal performance of suspended timber ground floors through the detailed investigation of a UK case study dwelling. Practical and buildable interventions were undertaken: fully-filling the floor void with EPS beads, and 100mm woodfibre insulation between the joists. The performance of both interventions was monitored by high-resolution in-situ heat-flow monitoring in 27 floor locations, allowing for comparison with the uninsulated floor and with modelled results. While floors often remain uninsulated due to the disruption of retrospective works, this study highlighted potentially significant heat loss reductions: the mean whole floor U-value dropped by 65% for woodfibre insulation and 92% for bead-insulation which also benefited from sealed airbricks. A disparity between the in-situ measured and modelled performance was observed; this gap reduced the better insulated the floor was. The findings have implications for policy, retrofit decision-making and carbon emission reduction stock models, especially given the modelled underestimation of floor heat loss, impact of interventions and assumed financial payback for this study.

**Keywords:** *in-situ U-values; pre-1919 housing; retrofit; suspended timber ground floors; thermal performance; insulation interventions*

Nomenclature	
U, U <sub>mean</sub> , U <sub>p</sub> , U <sub>wf</sub> , U <sub>avg</sub>	Thermal transmittance or U-value, Wm <sup>-2</sup> K <sup>-1</sup> ; U <sub>mean</sub> is the estimated in-situ U-value obtained from a mean of ratios of point U-values (U <sub>p</sub> ). U <sub>p</sub> is a point U-value and is the term used as a generic description of the small area-based in-situ U-value measurement on a certain location on the floor. U <sub>wf</sub> is the in-situ estimated whole floor U-value derived from area-weighted U <sub>p</sub> -values. U <sub>avg</sub> is the in-situ estimated whole floor U-value derived from a simple average of all U <sub>p</sub> -values.
HF1, HF2,...	Heat flux sensor location 1, 2,...

Download English Version:

<https://daneshyari.com/en/article/4919006>

Download Persian Version:

<https://daneshyari.com/article/4919006>

[Daneshyari.com](https://daneshyari.com)