
## Accepted Manuscript

Title: Time-Averaged Ventilation for optimized control of Variable-Air-Volume systems

Author: Soazig Kaam Paul Raftery Hwakong Chen Gwelen Paliaga



PII:	S0378-7788(16)31712-1
DOI:	http://dx.doi.org/doi:10.1016/j.enbuild.2016.11.059
Reference:	ENB 7174
To appear in:	ENB
Received date:	8-9-2016
Accepted date:	28-11-2016

Please cite this article as: Soazig Kaam, Paul Raftery, Hwakong Chen, Gwelen Paliaga, Time-Averaged Ventilation for optimized control of Variable-Air-Volume systems, Energy and Buildings http://dx.doi.org/10.1016/j.enbuild.2016.11.059

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

## Time-Averaged Ventilation for optimized control of Variable-Air-Volume systems

The authors are (in order):

Soazig Kaam(1), Paul Raftery (1)(\*), Hwakong Chen (2), Gwelen Paliaga (3)

\* Corresponding author (p.raftery@berkeley.edu<mailto:p.raftery@berkeley.edu>,

research@paulraftery.com<mailto:research@paulraftery.com>)

(1) Center for the Built Environment, University of California Berkeley, CA 94720, USA

(2) Taylor Engineering, 1080 Marina Village Parkway, Suite 501, Alameda, CA 94501, USA

(3) TRC, 436 14th Street, Suite 1020, Oakland, CA 94612, USA

## 1 Highlights

- We developed a control sequence that alternates each zone VAV damper between open and closed.
- We tested it in a Variable Air Volume system building with single-max control logic and high minimum flow rates.

Download English Version:

## https://daneshyari.com/en/article/4919341

Download Persian Version:

https://daneshyari.com/article/4919341

Daneshyari.com