

Contents lists available at ScienceDirect

Fusion Engineering and Design

journal homepage: www.elsevier.com/locate/fusengdes

Post examination of tungsten monoblocks subjected to high heat flux tests of ITER full-tungsten divertor qualification program



Fusion Engineering and Design

Zhaoxuan Sun^{a,b}, Qiang Li^{a,*}, Wanjing Wang^a, Ji-Chao Wang^{a,b}, Xingli Wang^{a,b}, Ran Wei^{a,b}, Chunyi Xie^a, Guang-nan Luo^{a,b,c,d}, T. Hirai^e, F Escourbiac^e, S. Panayotis^e

^a Institute of Plasma Physics, Chinese Academy of Sciences, Hefei, 230031, China

^b Science Island Branch of Graduate School, University of Science & Technology of China, Hefei, 230031, China

^c Hefei Center for Physical Science and Technology, Hefei, 230022, China

^d Hefei Science Center of Chinese Academy of Sciences, Hefei, 230027, China

e ITER Organization, Route de Vinon sur Verdon, CS 90 046 13067 Saint Paul lez Durance Cedex, France

HIGHLIGHTS

• ASIPP manufactured six W monoblock mock-ups that were tested at IDTF for full-tungsten divertor qualification program.

- Ultrasonic test was performed to investigate the defects of interface.
- Destructive test was performed on three mock-ups to analysis the damage.
- FEA was performed to study the temperature and stress distribution of monoblocks.

ARTICLE INFO

Article history: Received 21 December 2016 Received in revised form 30 March 2017 Accepted 6 June 2017

Keywords: ITER Tungsten Divertor High heat flux Monoblock

ABSTRACT

In 2015, as part of ITER Full-Tungsten Divertor Qualification Program, Institute of Plasma Physics Chinese Academy of Sciences (ASIPP) manufactured six small-scale Tungsten (W) monoblock mock-ups that were tested at the electron beam facility, ITER Divertor Test Facility (IDTF, St Petersburg, RF). The high heat flux (HHF) tests consisted of 5000 cycles at 10 MW/m², followed by 300 cycles at 20 MW/m² and additional 700 cycles at 20 MW/m². All mock-ups fulfilled the requirements of high heat flux performance successfully. One (WTC-5) of the six mock-ups was then selected to carry out critical heat flux (CHF) test with local heat flux up to 37–39 MW/m². After HHF test, ultrasonic test (UT) and destructive tests were performed to characterize the damages of monoblocks. The debonding of the Cu/CuCrZr interface was detected by both nondestructive and destructive tests. Intergranular rupture of W was observed by Scanning Electron Microscope (SEM). The recrystallization was found in the W monoblocks and the recrystallized depth were analyzed by metallography and Vickers hardness measurement.

© 2017 Published by Elsevier B.V.

1. Introduction

Full tungsten (W) divertor qualification program have been established to develop and validate the performance of W monoblock technology for W divertor in November 2011 [1–3]. Upon the two years of efforts on engineering and physics aspects, the ITER Council endorsed the proposal to start ITER operation with full-W divertor in November 2013. Domestic Agencies in Japan and Europe have succeeded to demonstrate high heat flux (HHF) performance of W monoblocks for a full-tungsten divertor in col-



Fig. 1. Tungsten monoblock mock-ups with swirl tapes before HHF testing.

^{*} Corresponding author. *E-mail address:* liqiang577@ipp.ac.cn (Q. Li).

http://dx.doi.org/10.1016/j.fusengdes.2017.06.009 0920-3796/© 2017 Published by Elsevier B.V.



Fig. 2. IR-pictures of average absorbing heat flux at (a)-24.7 MW/m^2 , (b)-25.5 MW/m^2 , (c)-26 MW/m^2 .



Fig. 3. Possible distribution made by the simulation.

laboration with the ITER Organization (IO) [4,5]. In China, Institute of Plasma Physics Chinese Academy of Sciences (ASIPP) has set up to develop W monoblocks technology since 2010 and applied it to the upper divertor on the EAST Tokamak. In 2015, as a part of qualification of tungsten (W) monoblock technology for ITER divertor, ASIPP and Advanced Technology and Materials Co., Ltd (AT&M) manufactured six small-scale W monoblock mock-ups that were sent to



Fig. 4. Average temperature of each monoblock gained by IR-camera of WTC-2 HHF testing: (a)-5000 cycles at 10 MW/m², (b)-300 cycles at 20 MW/m², (c)-additional 700 cycles at 20 MW/m².

Download English Version:

https://daneshyari.com/en/article/4921042

Download Persian Version:

https://daneshyari.com/article/4921042

Daneshyari.com