Accepted Manuscript

A homogenization model for porous ductile solids under cyclic loads comprising a matrix with isotropic and linear kinematic hardening

L. Cheng, K. Danas, A. Constantinescu, D. Kondo

 PII:
 S0020-7683(17)30235-4

 DOI:
 10.1016/j.ijsolstr.2017.05.024

 Reference:
 SAS 9586

To appear in: International Journal of Solids and Structures

Received date:2 February 2017Revised date:30 April 2017Accepted date:17 May 2017

Please cite this article as: L. Cheng, K. Danas, A. Constantinescu, D. Kondo, A homogenization model for porous ductile solids under cyclic loads comprising a matrix with isotropic and linear kinematic hardening, *International Journal of Solids and Structures* (2017), doi: 10.1016/j.ijsolstr.2017.05.024

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



A homogenization model for porous ductile solids under cyclic loads comprising a matrix with isotropic and linear kinematic hardening

L. Cheng^{a,*}, K. Danas^a, A. Constantinescu^a, D. Kondo^b

^aLaboratoire de Mécanique des Solides, École Polytechnique, Université Paris-Saclay, Palaiseau, France ^bInstitut Jean Le Rond d'Alembert, UMR 7190 CNRS, Université Pierre et Marie Curie, 4 place Jussieu, F75005 Paris, France

Abstract

In this work, we propose an semi-analytical micromechanical model to study the elastoplastic response of porous materials subjected to cyclic loading with isotropic and linear kinematic hardening at finite strains. To this end, we use an approximate but numerically efficient decoupled homogenization strategy between the elastic and plastic parts. The resulting effective back stress in the porous solid, similar to the macroscopic stress and plastic strain, has non-zero hydrostatic terms and depends on the porosity, the void shape and orientation as a result of the homogenization process. Subsequently, a complete set of equations is defined to describe the evolution of the microstructure, i.e., void volume fraction (porosity), (ellipsoidal) void shape and orientation both in the elastic and the plastic regimes. The model is then numerically implemented in a general purpose user-material subroutine. Full field finite element simulations of multi-void periodic unit cells are used to assess the predictions of the proposed model. The latter is found to be in good qualitative and quantitative agreement with the finite element results for most of the loading types, hardening parameters and porosities considered in this study, but is less accurate for very small porosities. The combined analytical and numerical study shows that elasticity is an important mechanism for porosity ratcheting in addition to strain hardening. Specifically, in order to recover the main qualitative features of porosity ratcheting for all cyclic loads considered in the present study, it is shown to be critical to take into account the evolution of the microstructure not only during the plastic loading, as is the usual hypothesis, but also during elastic loading. Finally, the effect of isotropic and linear kinematic hardening is found to be highly non-monotonic and non-trivial upon porosity ratcheting for most cases considered here.

Keywords: Cyclic loading, Porous ductile material, Porosity ratcheting, Non-linear homogenization, Strain hardening, Elasto-plasticity

Preprint submitted to Elesvier

^{*}Corresponding author.

Email addresses: cheng@lms.polytechnique.fr (L. Cheng), kdanas@lms.polytechnique.fr (K. Danas)

Download English Version:

https://daneshyari.com/en/article/4922315

Download Persian Version:

https://daneshyari.com/article/4922315

Daneshyari.com