

## Author's Accepted Manuscript

The Possibility of Enhancing Some Properties of Self-Compacting Concrete by Adding Waste Plastic Fibers

Abdulkader Ismail Al-Hadithi, Nahla Naji Hilal



PII: S2352-7102(16)30068-7  
DOI: <http://dx.doi.org/10.1016/j.job.2016.06.011>  
Reference: JOBE146

To appear in: *Journal of Building Engineering*

Received date: 20 November 2015  
Revised date: 17 June 2016  
Accepted date: 17 June 2016

Cite this article as: Abdulkader Ismail Al-Hadithi and Nahla Naji Hilal, The Possibility of Enhancing Some Properties of Self-Compacting Concrete by Adding Waste Plastic Fibers, *Journal of Building Engineering* <http://dx.doi.org/10.1016/j.job.2016.06.011>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting galley proof before it is published in its final citable form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

# **The Possibility of Enhancing Some Properties of Self-Compacting Concrete by Adding Waste Plastic Fibers**

**Prof. Dr. Abdulkader Ismail Al-Hadithi, Dr. Nahla Naji Hilal**

**Dams and Water Resources Engineering Department, College of Engineering, University of Anabr, Ramadi,  
ANBAR , IRAQ.**

**al\_hadithi2000@yahoo.com**

**nahla\_naji2007@yahoo.com**

## **Abstract:**

An attempt was carried out to develop some properties of self-compacted concrete (SCC) by adding waste plastic fibers (WPF) resulting from cutting beverage bottles. Many tests were conducted to investigate the effect of adding WPF on the fresh properties, whereas other tests were applied on that kind of concrete to study the effect of this type of waste on hardened properties. For this reason, different self-compacting concrete mixtures were designed at constant water-to-binder ratio of 0.35 and 490 kg/m<sup>3</sup> of binder content. The class F fly ash was replaced with cement as 25% by weight. The eighth designated plastic fiber contents of 0, 0.25, 0.5, 0.75, 1, 1.25, 1.5, 1.75 and 2% by volume. The workability properties of self-compacting concrete mixtures were performed to slump flow diameter, T<sub>50</sub> slump flow simultaneously, V-funnel flow at the same time, and L-box height ratio. The 7,14 and 28-day compressive strengths of self-compacting concretes were also measured. Moreover, the 7, 14 and 28-day flexural strengths of concretes were also measured. The test results showed that the plastic fibers have adverse effect on the fresh properties of self-compacting concrete and improvement by hardened properties.

Download English Version:

<https://daneshyari.com/en/article/4923204>

Download Persian Version:

<https://daneshyari.com/article/4923204>

[Daneshyari.com](https://daneshyari.com)