

Author's Accepted Manuscript

Hygrothermal performance of a straw bale building: in situ and laboratory investigations

Omar Douzane, Geoffrey Promis, Jean-Marc Roucoult, Anh-Dung Tran Le, Thierry Langlet



PII: S2352-7102(16)30217-0
DOI: <http://dx.doi.org/10.1016/j.job.2016.10.002>
Reference: JOBE181

To appear in: *Journal of Building Engineering*

Received date: 12 May 2016
Revised date: 5 October 2016
Accepted date: 5 October 2016

Cite this article as: Omar Douzane, Geoffrey Promis, Jean-Marc Roucoult, Anh Dung Tran Le and Thierry Langlet, Hygrothermal performance of a straw bale building: in situ and laboratory investigations, *Journal of Building Engineering* <http://dx.doi.org/10.1016/j.job.2016.10.002>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting galley proof before it is published in its final citable form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Hygrothermal performance of a straw bale building: in situ and laboratory investigations

Omar Douzane*, Geoffrey Promis, Jean-Marc Roucoult, Anh-Dung Tran Le, Thierry Langlet

Innovative Technologies Laboratory (LTI), University of Picardie Jules Verne, Avenue des Facultés, 80 025 Amiens Cedex 1, France

*Corresponding author. Tel: +33(0)322534043, fax: +33(0)322951751.
omar.douzane@u-picardie.fr

ABSTRACT

This paper focuses on the assessment of the hygrothermal performance of a straw bale house in the Picardie, a region of France. The house was built using a wooden load bearing frame filled with straw bales. Laboratory and *in situ* tests were carried out in this study.

In the first part, the thermal conductivity of straw bales was measured in relation to the orientation of the straw fibers. The thermal resistance of a wall built in the laboratory, respecting the real construction parameters, was assessed. The obtained U-value was compared to those of different walls used in civil field engineering.

The second part of this paper continues with an assessment of the hygrothermal performance of a real straw bale house. Temperature and relative humidity measurements were recorded during more than one year, using sensors that were placed in indoors and outdoors, and at various depths of the walls and floors.

Finally, this paper is completed by a dynamic thermal simulation of the house, based on experimental laboratory investigations. During winter the simulated heating requirements are estimated at 59 kWh/m². Moreover, the simulation under summer conditions shows the major influence of the building envelope on the thermal comfort. Thus, straw bale walls seems to provide significant thermal inertia in summer.

Keywords

Straw bale house, Straw bale wall, U-value, Hygrothermal performance, Thermal inertia, Moisture content

1. Introduction

Download English Version:

<https://daneshyari.com/en/article/4923210>

Download Persian Version:

<https://daneshyari.com/article/4923210>

[Daneshyari.com](https://daneshyari.com)