

Accepted Manuscript

Measuring reliability of hybrid photovoltaic-wind energy systems: A new indicator

Luceny Guzmán Acuña, Ricardo Vasquez Padilla, Alcides Santander Mercado

PII: S0960-1481(16)31154-5

DOI: [10.1016/j.renene.2016.12.089](https://doi.org/10.1016/j.renene.2016.12.089)

Reference: RENE 8426

To appear in: *Renewable Energy*


Received Date: 13 June 2016

Revised Date: 4 November 2016

Accepted Date: 29 December 2016

Please cite this article as: Acuña LG, Padilla RV, Mercado AS, Measuring reliability of hybrid photovoltaic-wind energy systems: A new indicator, *Renewable Energy* (2017), doi: 10.1016/j.renene.2016.12.089.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



1 Measuring reliability of hybrid photovoltaic-wind energy
2 systems: A new indicator

3 Luceny Guzmán Acuña^{a,*}, Ricardo Vasquez Padilla^{b,1}, Alcides Santander
4 Mercado^{a,2}

5 ^a*Department of Industrial Engineering. Universidad del Norte, Barranquilla, Colombia*

6 ^b*School of Environment, Science and Engineering. Southern Cross University, Lismore,*
7 *NSW, 2480, Australia*

8 **Abstract**

9 The integration of renewable energy systems has increased in the last decades
10 because of the need for new energy sources freely available and environmen-
11 tal friendly. In this sense, photovoltaic-wind hybrid energy systems are an
12 attractive solution, especially in places with good sun and wind resources.
13 However, due to the stochastic and intermittent behavior of these sources,
14 it is necessary to analyze systems' reliability. In this paper, a new reli-
15 ability indicator is proposed, based on the minimum hourly electric power
16 obtained from the wind and solar radiation using a probabilistic approach.
17 This indicator is compared with other indicators and the results showed that
18 it increases system reliability by maximizing the use of renewable sources.

19 *Keywords:* Hybrid systems, reliability, photovoltaic, wind, probability
20 distributions, indicator

21 **1. Introduction**

22 Increased energy consumption in the world has caused an increase in the
23 exploitation and use of main fossil fuels (oil, gas and coal) adding to environ-
24 mental problems in the planet. BP Energy Outlook 2030, reported that the
25 total energy consumption will increase by 50% in 2030 compared to 2011,
26 and it is expected an 82% of dependence on fossil resources in 2030 [1].

27 The renewable energy sources are considered part of the solution to mitigate
28 environmental problems caused by the use of conventional energy sources.
29 Their average annual growth were estimated in 7.6 % being the installation
30 and use of solar and wind fastest growing [1]. The photovoltaic solar energy

*Correspondance author.Email: lguzman@uninorte.edu.co

¹E-mail: Ricardo.VasquezPadilla@scu.edu.au

²E-mail: asantand@uninorte.edu.co

Download English Version:

<https://daneshyari.com/en/article/4926376>

Download Persian Version:

<https://daneshyari.com/article/4926376>

[Daneshyari.com](https://daneshyari.com)