

Accepted Manuscript

Hierarchically Linked Infinite Hidden Markov Model based Trajectory Analysis and Semantic Region Retrieval in a Trajectory Dataset

Yongjin Kwon , Kyuchang Kang , Junho Jin , Jinyoung Moon , Jongyoul Park

PII: S0957-4174(17)30108-2
DOI: [10.1016/j.eswa.2017.02.026](https://doi.org/10.1016/j.eswa.2017.02.026)
Reference: ESWA 11134



To appear in: *Expert Systems With Applications*

Received date: 9 November 2016
Revised date: 14 February 2017

Please cite this article as: Yongjin Kwon , Kyuchang Kang , Junho Jin , Jinyoung Moon , Jongyoul Park , Hierarchically Linked Infinite Hidden Markov Model based Trajectory Analysis and Semantic Region Retrieval in a Trajectory Dataset, *Expert Systems With Applications* (2017), doi: [10.1016/j.eswa.2017.02.026](https://doi.org/10.1016/j.eswa.2017.02.026)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Highlights

- A novel model for trajectories and semantic regions (sest-hiHMM) is proposed.
- A sticky version of sest-hiHMMs is proposed for reducing redundant semantic regions.
- An extended definition of semantic regions covers actual regions, not sets of points.
- Our models concern the temporal dependency of observations in a trajectory.
- Our models retrieve reasonable semantic regions from a real trajectory dataset.

ACCEPTED MANUSCRIPT

Download English Version:

<https://daneshyari.com/en/article/4943603>

Download Persian Version:

<https://daneshyari.com/article/4943603>

[Daneshyari.com](https://daneshyari.com)