Accepted Manuscript

Risk assessment of oil and gas pipelines with consideration of induced seismicity and internal corrosion

Oleg Shabarchin, Solomon Tesfamariam

PII: S0950-4230(17)30212-7

DOI: 10.1016/j.jlp.2017.03.002

Reference: JLPP 3442

To appear in: Journal of Loss Prevention in the Process Industries

Received Date: 5 August 2016

Revised Date: 1 March 2017

Accepted Date: 1 March 2017

Please cite this article as: Shabarchin, O., Tesfamariam, S., Risk assessment of oil and gas pipelines with consideration of induced seismicity and internal corrosion, *Journal of Loss Prevention in the Process Industries* (2017), doi: 10.1016/j.jlp.2017.03.002.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



Risk Assessment of Oil and Gas Pipelines with

Consideration of Induced Seismicity and Internal Corrosion

Oleg Shabarchin¹ and Solomon Tesfamariam^{2*}

ABSTRACT

Over the last decade, unconventional oil and gas production has increased due to use of hydraulic fracturing and second oil recovery techniques. However, this activity is followed by prevalence of induced seismicity and has the potential to damage pipelines. The integrity of these pipelines is essential for oil and gas companies, regulator organizations, and stakeholders due to adverse environmental consequences and significant financial losses. Therefore, it is important to investigate a potential impact of the induced seismicity on the pipeline infrastructure in order to enhance informed decision making (e.g. permitting decisions). To accomplish this task, this paper presents a probabilistic seismic risk assessment approach, which has been used for pipeline infrastructure located in the Northeast of British Columbia, Canada. Spatial clustering analysis is used for earthquakes, previously registered in the region, to delineate areas, which are particularly prone to the induced seismicity. The state-of-the-art ground motion prediction equation for induced seismicity is applied in Monte Carlo simulation to obtain a stochastic field of the seismic intensity. Based on the pipelines' seismic fragility formulations as well as its mechanical characteristics and corrosion conditions, spatial and probabilistic distributions of the repair rate and probability of failure have been obtained and visualized with the aid of the Geospatial Information System.

KEYWORDS: induced seismicity, seismic hazard, spatial clustering, oil and gas pipelines.

¹ MASc Student, School of Engineering, The University of British Columbia, Okanagan Campus, 3333 University Way, Kelowna, BC, Canada, V1V 1V7

² Associate Professor, School of Engineering, The University of British Columbia, Okanagan Campus, 3333 University Way, Kelowna, BC, Canada, V1V 1V7, Tel: (250)-807-8185, E-mail: <u>solomon.tesfamariam@ubc.ca</u> **Corresponding author*

Download English Version:

https://daneshyari.com/en/article/4980495

Download Persian Version:

https://daneshyari.com/article/4980495

Daneshyari.com