

Pressure dependent wall slip of wood flour filled polymer melts

Valentina Mazzanti , Francesco Mollica

PII: S0377-0257(17)30166-0  
DOI: [10.1016/j.jnnfm.2017.07.002](https://doi.org/10.1016/j.jnnfm.2017.07.002)  
Reference: JNNFM 3911



To appear in: *Journal of Non-Newtonian Fluid Mechanics*

Received date: 18 April 2017  
Revised date: 4 July 2017  
Accepted date: 14 July 2017

Please cite this article as: Valentina Mazzanti , Francesco Mollica , Pressure dependent wall slip of wood flour filled polymer melts, *Journal of Non-Newtonian Fluid Mechanics* (2017), doi: [10.1016/j.jnnfm.2017.07.002](https://doi.org/10.1016/j.jnnfm.2017.07.002)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

## Highlights

- Mooney procedure cannot be applied properly to natural fiber filled polymer melts because of non-perfect linearity in the experimental data points.
- Non-linearity of pressure vs. axial position plots can be explained on the basis of pressure dependent wall slip.
- Using a pressure dependent slip model it is possible to approximate the experimental data in a satisfactory way.
- Rheological characterization of natural fiber filled polymers is very challenging due to ineffectiveness of off-line methods and limited gap size choice for in-line methods.

Download English Version:

<https://daneshyari.com/en/article/4995597>

Download Persian Version:

<https://daneshyari.com/article/4995597>

[Daneshyari.com](https://daneshyari.com)