



ELSEVIER

Contents lists available at ScienceDirect

## Engineering Fracture Mechanics

journal homepage: [www.elsevier.com/locate/engfracmech](http://www.elsevier.com/locate/engfracmech)

# Micromechanical boundary element modelling of transgranular and intergranular cohesive cracking in polycrystalline materials

G. Geraci <sup>\*</sup>, M.H. Aliabadi*Department of Aeronautics, Imperial College London, London SW7 2AZ, UK*

## ARTICLE INFO

*Article history:*

Received 2 July 2016

Received in revised form 15 February 2017

Accepted 12 March 2017

Available online xxx

*Keywords:*

Transgranular

Intergranular

Polycrystalline

Cohesive microfracture

Boundary element method

## ABSTRACT

In this paper a cohesive formulation is proposed for modelling intergranular and transgranular damage and microcracking evolution in brittle polycrystalline materials. The model uses a multi-region boundary element approach combined with the dual boundary element formulation. Polycrystalline microstructures are created through a Voronoi tessellation algorithm. Each crystal has an elastic orthotropic behaviour and specific material orientation. Transgranular surfaces are inserted as the simulation evolves and only in those grains that experience stress levels high enough for the nucleation of a new potential crack. Damage evolution along (inter- or trans-granular) interfaces is then modelled using cohesive traction separation laws and, upon failure, frictional contact analysis is introduced to model separation, stick or slip. This is the first time inter- and trans-granular fracture are being modelled together by BEM, and DBEM is being extended to include cohesive approach for anisotropic materials. Finally numerical simulations are presented to demonstrate the validity of the proposed formulation in comparison with experimental observations and literature results.

© 2017 Elsevier Ltd. All rights reserved.

## 1. Introduction

Polycrystalline materials are commonly used in many engineering applications. It is then of high technological interest to study how the macroscopic properties of materials such as metals, alloys and ceramics can be enhanced or optimized for specific applications through knowledge of microscopic features. In this work attention is focused on failure mechanisms of brittle polycrystalline materials such as ceramics, where the features and properties of the microstructure play a pivotal role in the elastic response of the whole structure and eventually in its failure. As pointed out by Crocker [1], “even though conceptually a simple process, the description of fracture in materials within ductile or brittle regimes is complex”.

Models for describing damage nucleation and growth can be considered over different ranges of length scale: atomistic models are at the lower scale and homogeneous materials at the other extreme [1].

Real fracture processes depend on many synergistic factors. The main features include: grain elastic properties, level of anisotropy and grain orientation, their morphology, grain size distribution within the aggregate, stiffness and toughness mismatch [2]. It is also well recognised that material’s crystallography structure affects the initiation of micro-cracking: (1) adjacent grains of non cubic phases can experience differential expansion due to thermal expansion anisotropy (TEA); (2) phase transformation (e.g. tetragonal to monoclinic) can also cause micro-cracking; (3) strain differences due to elastic anisotropy

\* Corresponding author.

E-mail addresses: [giorgio.geraci13@imperial.ac.uk](mailto:giorgio.geraci13@imperial.ac.uk) (G. Geraci), [m.h.aliabadi@imperial.ac.uk](mailto:m.h.aliabadi@imperial.ac.uk) (M.H. Aliabadi).

**Nomenclature**

<b>A</b>	sub-matrix of kernel integrals (unknown field)
<i>b</i>	orthotropic parameter
<b>B</b>	sub-matrix of kernel integrals (known field)
<b>C</b>	compliance tensor
<i>d</i>	damage parameter
<b>D</b>	strain kernel tensor
<i>E</i>	Young modulus
<b>G</b>	matrix of traction kernels
<b>H</b>	matrix of displacement kernels
<i>H</i>	generic grain
<b>I</b>	identity matrix
<i>l</i>	side length of square microstructure
<b>L</b>	matrix of strain kernels
<b>M</b>	matrix of stress kernels
<i>r</i>	distance from crack apex
<b>R</b>	rotation matrix
<b>S</b>	stress kernel tensor
<i>t</i>	traction
<b>T</b>	traction kernel tensor
<i>u</i>	displacement
<b>U</b>	displacement kernel tensor
<b>x</b>	field point
$\alpha$	cohesive parameter
$\beta$	cohesive parameter
$\varepsilon$	strain
$\theta$	angular direction from crack apex
$\lambda$	loading factor
$\mu$	friction coefficient
$\nu$	Poisson's ratio
$\sigma$	stress
$\tau$	shear stress
$\phi$	interface angle
$\Phi$	cohesive potential
$a_{1,2}$	orthotropic parameter
$A_{1,2}$	orthotropic parameter
$\bar{A}_{gr}$	average grain area
$C_{ij}$	Cauchy principal value free term
$\delta \mathbf{u}$	displacement jump
$\delta \mathbf{u}_{n,t}^{crit}$	critical component of displ. jump
$\delta_{ij}$	Kronecker delta
$\delta \lambda$	loading factor increment
$\theta_{1,2}$	orthotropic parameter
$\mu_{1,2}$	eigenvalues of charact. equation
$\sigma_{crit}$	critical tensile stress
$\tau_{crit}$	critical shear stress
$\Phi_0$	energy of separation
<i>ASTM G</i>	grain size index
<b>C'</b>	plane strain/stress tensor
<b>C<sup>coh</sup></b>	sub-matrix of cohesive laws
$\bar{d}_{gr}$	average grain size
$E_{1,2}$	modulus of elasticity
$\bar{f}$	transgranular damage
$G(\phi)$	work of separation
$G_n$	norm. work of separation
$G_t$	tang. work of separation
$G_{I,II}$	energy release rates
$G_{Ic}$	critical energy release rate
$K_{IC}$	fracture toughness
$\bar{L}^f$	average element length

Download English Version:

<https://daneshyari.com/en/article/5013919>

Download Persian Version:

<https://daneshyari.com/article/5013919>

[Daneshyari.com](https://daneshyari.com)