

Accepted Manuscript

A micromechanical-based constitutive model for fibrous fine-grained composite soils

Hesam Dejaloud, Yaser Jafarian

PII: S0749-6419(16)30289-3

DOI: [10.1016/j.ijplas.2016.11.008](https://doi.org/10.1016/j.ijplas.2016.11.008)

Reference: INTPLA 2127

To appear in: *International Journal of Plasticity*

Received Date: 27 July 2016

Revised Date: 6 November 2016

Accepted Date: 18 November 2016

Please cite this article as: Dejaloud, H., Jafarian, Y., A micromechanical-based constitutive model for fibrous fine-grained composite soils, *International Journal of Plasticity* (2016), doi: 10.1016/j.ijplas.2016.11.008.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



A Micromechanical-Based Constitutive Model for Fibrous Fine-Grained Composite Soils

Hesam Dejaloud^a, Yaser Jafarian^{a*}

^a Geotechnical Engineering Research Center, International Institute of Earthquake Engineering and Seismology (IIEES), Tehran, Iran

ABSTRACT

Composite soils such as municipal solid wastes (MSWs), peats, and reinforced soils are generally composed of multiple phases with different properties. Numerical modeling of these soils which takes the individual constituents into account might be impractical as it requires great computational efforts. Hence, geotechnical practitioners may prefer to treat a representative material which accounts for the whole mechanical aspects of the composite soil. In the current study, a constitutive model has been developed which treats the fine-grained composite soils in two general phases: matrix (paste) and fiber. To represent the behavior of these phases, two distinct constitutive models are used: (1) an anisotropic critical state-based constitutive model for matrix phase and (2) a Von-Mises type model for fiber phase. In order to consider the composite soil as a single phase homogeneous material, a volumetric homogenization procedure is used based on the micromechanical theories. Accordingly, strain concentration tensor is developed which determines the equivalent stiffness tensor for the homogenized soil. Based on the hypotheses derived from the experimental observations, the basic model is gradually enhanced in order to account for some important aspects of composite matters including fibers orientation,

* Correspondence to Yaser Jafarian, International Institute of Earthquake Engineering and Seismology (IIEES), Tehran, Iran;
Email: yjafarianm@iiees.ac.ir

Download English Version:

<https://daneshyari.com/en/article/5016795>

Download Persian Version:

<https://daneshyari.com/article/5016795>

[Daneshyari.com](https://daneshyari.com)