

Accepted Manuscript

Loading rate effect on the debonding phenomenon in fiber reinforced cementitious matrix-concrete joints

Cristian Carloni, Salvatore Verre, Lesley H. Sneed, Luciano Ombres



PII: S1359-8368(16)31446-9

DOI: [10.1016/j.compositesb.2016.09.087](https://doi.org/10.1016/j.compositesb.2016.09.087)

Reference: JCOMB 4579

To appear in: *Composites Part B*

Received Date: 28 July 2016

Accepted Date: 28 September 2016

Please cite this article as: Carloni C, Verre S, Sneed LH, Ombres L, Loading rate effect on the debonding phenomenon in fiber reinforced cementitious matrix-concrete joints, *Composites Part B* (2016), doi: 10.1016/j.compositesb.2016.09.087.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Loading rate effect on the debonding phenomenon in fiber reinforced cementitious matrix-concrete joints

Cristian Carloni^{a,1}, Salvatore Verre^b, Lesley H. Sneed^c, and Luciano Ombres^d

^a *Department of Civil, Chemical, Environmental, and Materials Engineering, University of Bologna,
Viale Risorgimento 2, 40126 Bologna, Italy, christian.carloni@unibo.it, +39 051-2093492*

^b *Department of Civil Engineering, University of Calabria, Via P. Bucci Cubo 39B, 87036 Arcavacata di
Rende, Cosenza, Italy, salvatore.verre@unical.it, +39 0984-496951*

^c *Department of Civil, Architectural and Environmental Engineering, Missouri University of Science and
Technology, 1401 North Pine Street, Rolla, MO, 65409, USA, sneedlh@mst.edu, +1 573-3414553*

^d *Department of Civil Engineering, University of Calabria, Via P.Bucci Cubo 39B, 87036 Arcavacata di
Rende, Cosenza, Italy, luciano.ombres@unical.it, +39 0984-494045*

ABSTRACT

This paper presents the results of an experimental study conducted to examine the effect of loading rate on the response of direct-shear tests of fiber reinforced cementitious matrix (FRCM)-concrete joints. Seven rates were used in this study, as well as two different types of control referred to as global slip control and machine stroke control. The experimental results indicate that a change in the rate results in a variation in peak load. In addition, a comparison between load responses obtained from tests carried out using different control variables indicates that the shape of the load response and its peak load are influenced by both the rate and the variable used to control the test. The out-of-plane displacement of the composite determined at the peak load increases with increasing rate for both control types.

Keywords: A. Fabrics/textiles; B. Adhesion; B. Fibre/matrix bond; D. Mechanical testing.

¹ Corresponding author.

Download English Version:

<https://daneshyari.com/en/article/5021696>

Download Persian Version:

<https://daneshyari.com/article/5021696>

[Daneshyari.com](https://daneshyari.com)