



Available online at www.sciencedirect.com



Procedia Engineering 190 (2017) 619 - 626

Procedia Engineering

www.elsevier.com/locate/procedia

## Structural and Physical Aspects of Construction Engineering

# Overview of Progressive Evaluation Methods for Monitoring of Heat Production and Distribution

Ivan Čorný<sup>a,\*</sup>

<sup>a</sup>Technical University of Košice, Faculty of Manufacturing Technologies with a seat in Prešov Bayerova 1, 080 01 Prešov, Slovakia

### Abstract

The contribution describes the specific approach to the monitoring and evaluation of heat production and supply/distribution. The approach is based on application of progressive evaluation methods such as computational intelligence techniques. The proposal consists of data collecting module and monitoring/evaluation module. It is clear that to collect a large amount of data concerning heat production and distribution is a relatively simple task. It depends on selection of parameters, application of sensors and meters. The measured values are read with SCADA-type software. Following step is of a higher complexity: a decision, what to do with the data. The useful data processing is focused on efficiency, predictability, optimization of processes, and possibly on synergistic effects.

© 2017 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (http://creativecommons.org/licenses/by-nc-nd/4.0/).

Peer-review under responsibility of the organizing committee of SPACE 2016

Keywords: Heat production; heat distribution; monitoring; computational intelligence;

### 1. Introduction

A substantial part of the primary energy resources is consumed in buildings due to the heating/air-conditioning requirements. This consumption results in increased greenhouse gases emissions and negative environmental impact. In the context of sustainable development, the required heat should be produced and distributed with an account to the limited natural resource use and low environmental impact.

Total energy required for the particular energy service is often indicated as primary energy consumption. It includes all energy/fuel inputs, and potential energy losses along the energy distribution net. The primary energy use, e.g. operating buildings, thus depends mostly on energy/heat production and distribution processes. To

<sup>\*</sup> Corresponding author. Tel.: +421 55 602 6391; fax: +421 51 773 3453. *E-mail address:* ivan.corny@tuke.sk

determine the primary energy use, it is necessary to identify the energy efficiencies of the involved processes. However, minimizing the amount of purchased energy does not mean that the natural resources use or the building life cycle emissions are also minimized [1, 2].

Minimizing of primary energy use can be achieved by several ways. Besides a common approach of improving the performance of the buildings (better insulation, progressive HVAC systems) also monitoring, modeling/simulation and prediction of energy systems behavior on various levels are getting more attention. Advanced models can be applied not only for monitoring and data storing but also as state-of-the-art control tools. To achieve this goal, however, the control systems have to be based on verified, reliable models. It is likely that such models are based on the newest top-notch computational methods such as artificial intelligence and computational intelligence. These terms may raise a lot of questions concerning the precise meaning of "intelligence", nevertheless, it is obvious that these approaches have found their way into numerous human activities that require processing of large amount of data, and decision making based on these data. [1, 3, 4].

#### 2. Data Acquisition for Monitoring of Heat Production and Distribution

The heat monitoring data provide necessary input for the evaluation models. The data sets consist of several parameters measured in particular time intervals. The most typical parameters are: external and internal temperature, heat consumption, gas/electricity consumption, heating medium temperature and flow rate, possibly also wind speed and sun irradiation values if applicable [5, 6].

The monitoring data are usually acquired by SCADA (Supervisory Control and Data Acquisition) system. SCADA system is a type of industrial control system. SCADA is a system for remote monitoring and control, it operates with coded signals over communication channels.

SCADA systems provide data sets of monitored parameters; however, they do not contain higher level evaluation units. Typical data acquisition with SCADA includes meter readings and equipment status reports. Example of SCADA system user interface is shown on Fig. 1.

0 = 03_2 Menu	Ś		D i Iživater Info	O aplikácii		10	0:30:56		
Śkoły	03_28			2	Ś	_			
Kotolňa	l≊Záznam Teplota vonku					Export do	📇 Tlač		
OÚK1 OÚK2	Prehľad	🖵 Denný 🔽	Dátum	Tvon7hod [*C]	Tvon14hod ["C]	Tvon21hod [*C]	TvonPriemer [*C]		
	Prentad p	Cientry	15.08.2016 21:00	16.24	1V0014000 [*C] 20.01	16.72	TvonPriemer [PC]		
Contra Statistics	Začiatok	16. 07. 2016	14.08.2016 21:00	12.41	25.87	19.47	19.31		
ÚK5 <b>S</b> ÚK6	Mantan	17. 08. 2016	13.08.2016 21:00	11.08	22.36	17.48	17.10		
ύκτ 🗊τν	Koniec	17. 08. 2016	12.08.2016 21:00	6.58	19.44	13.77	13.39		
		Načítaj	11.08.2016 21:00	12.05	18.12	12.60	13.89		
T vonku			10.08.2016 21:00	14.53	21.40	12.29	15.13		
Merače tepia Posledný záznam:		nam:	09.08.2016 21:00	11.58	26.50	19.54	19.29		
			08.08.2016 21:00	9.86	24.22	17.44	17.24		
Spotreba	15. 08. 2016 21:00		07.08.2016 21:00	13.53	22.36	16.71	17.33		
Dennostupne			06.08.2016 21:00	17.94	21.34	16.57	18.11		
			05.08.2016 21:00	17.23	27.17	21.11	21.65		
Prevádzkový dennik			04.08.2016 21:00	13.99	28.32	21.74	21.45		
Alarmy			03.08.2016 21:00	14.33	25.45	18.78	19.33		
Alarmy			02.08.2016 21:00	15.74	23.30	18.30	18.91		
			01.08.2016 21:00	17.64	21.11	19.26	19.32		
			31.07.2016 21:00	16,91	28.73	19.27	21.05		
			30.07.2016 21:00	15.93	26.37	20.37	20.76		
			29.07.2016 21:00	17.63	23.32	18.52	19.50		
			28.07.2016 21:00	18.16	19.88	18.22	18.62		
			27.07.2016 21:00	19.07	23.04	19.63	20.34		
			26.07.2016 21:00	18.37	29.20	20.44	22.13		
			25.07.2016 21:00	18.49	24.08	19.63	20.46		
			24.07.2016 21:00	16.68	28.02	20.36	21.35		
			23.07.2016 21:00	14.93	28.07	20.76	21.13		
¥			Prepočet	Tvon7hod [°C]	Tvon14hod ["C]	Tvon21hod [°C]	TvosPriemer [*C]		
Kvit			min	6.58	13.78	12.29	13.39		
			max	19.07	29.28	21.74	22.43		
			Priemer	14.78	23.20	18.00	18.50		

Fig. 1. SCADA system user interface.

Download English Version:

https://daneshyari.com/en/article/5027255

Download Persian Version:

https://daneshyari.com/article/5027255

Daneshyari.com