

Enzyme-Polyelectrolyte Multilayer Assemblies on  
Reduced Graphene Oxide Field-Effect Transistors  
for Biosensing Applications

Esteban Piccinini, Christina Bliem, Ciril Reiner-  
Rozman, Fernando Battaglini, Omar Azzaroni,  
Wolfgang Knoll



[www.elsevier.com/locate/bios](http://www.elsevier.com/locate/bios)

PII: S0956-5663(16)31050-8  
DOI: <http://dx.doi.org/10.1016/j.bios.2016.10.035>  
Reference: BIOS9257

To appear in: *Biosensors and Bioelectronics*

Received date: 12 August 2016  
Revised date: 28 September 2016  
Accepted date: 18 October 2016

Cite this article as: Esteban Piccinini, Christina Bliem, Ciril Reiner-Rozman, Fernando Battaglini, Omar Azzaroni and Wolfgang Knoll, Enzyme-Polyelectrolyte Multilayer Assemblies on Reduced Graphene Oxide Field-Effect Transistors for Biosensing Applications, *Biosensors and Bioelectronics* <http://dx.doi.org/10.1016/j.bios.2016.10.035>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting galley proof before it is published in its final citable form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

# ***Enzyme-Polyelectrolyte Multilayer Assemblies on Reduced Graphene Oxide Field-Effect Transistors for Biosensing Applications***

Esteban Piccinini<sup>a1</sup>, Christina Bliem<sup>b1</sup>, Ciril Reiner-Rozman<sup>c</sup>, Fernando Battaglini<sup>d</sup>, Omar Azzaroni<sup>a,\*</sup>, Wolfgang Knoll<sup>c</sup>

<sup>a</sup>Instituto de Investigaciones Fisicoquímicas Teóricas y Aplicadas (INIFTA) – Departamento de Química, Facultad de Ciencias Exactas, Universidad Nacional de La Plata – CONICET, Suc. 4, CC 16, La Plata, Argentina.

<sup>b</sup>Centre of Electrochemical Surface Technology (CEST), Viktor-Kaplan-Straße 2, 2700 Wiener Neustadt, Austria.

<sup>c</sup>AIT Austrian Institute of Technology, Donau City Straße 1, 1220 Vienna, Austria.

<sup>d</sup>INQUIMAE, Departamento de Química Inorgánica, Analítica y Química Física, Facultad de Ciencias Exactas y Naturales, Universidad de Buenos Aires, Ciudad Universitaria, Buenos Aires, Argentina.

\*Corresponding author: azzaroni@inifta.unlp.edu.ar (O.A.)

## **Abstract**

We present the construction of layer-by-layer (LbL) assemblies of polyethylenimine and urease onto reduced-graphene-oxide based field-effect transistors (rGO FETs) for the detection of urea. This versatile biosensor platform simultaneously exploits the pH dependency of liquid-gated graphene-based transistors and the change in the local pH produced by the catalyzed hydrolysis of urea. The use of an interdigitated microchannel resulted in transistors displaying low noise, high pH sensitivity (20.3  $\mu\text{A}/\text{pH}$ ) and transconductance values up to 800  $\mu\text{S}$ . The modification of rGO FETs with a weak polyelectrolyte improved the pH response because of its transducing properties by electrostatic gating effects. In the presence of urea, the urease-modified rGO FETs showed a shift in the Dirac point due to the change in the local pH close to the graphene surface. Markedly, these devices operated at very low voltages (less than 500 mV) and were able to monitor urea in the range of 1-1000  $\mu\text{M}$ , with a limit of detection (LOD) down to 1  $\mu\text{M}$ , fast response and good long-term stability. The urea-response of the transistors was enhanced by increasing the number of bilayers due to the increment of the enzyme surface coverage onto the channel. Moreover, quantification of the heavy metal  $\text{Cu}^{2+}$  (with a LOD down to 10 nM) was performed in aqueous solution by taking advantage of the urease specific inhibition.

Graphical abstract

Keywords: Graphene, Field-effect transistors, Chemical sensors, Biosensors.

## **1. Introduction**

Graphene, a two-dimensional zero band gap semiconducting material, has gained vast interest in material science, energy storage and sensor technology, due to its remarkable electronic and mechanical properties (Choi and Lee, 2012). Its high carrier mobility and ambipolar field effect (Cai et al., 2014), together with a great sensitivity towards changes in environmental conditions makes graphene perfectly suitable as transducing material for the use in chemical sensors. Graphene based field effect transistors (FETs) have been applied for pH sensing (Ohno et al., 2009; Sohn et al., 2013), DNA (Dong et al., 2010) and protein

<sup>1</sup> These authors contributed equally to this work and should be considered as co-first authors.

Download English Version:

<https://daneshyari.com/en/article/5031653>

Download Persian Version:

<https://daneshyari.com/article/5031653>

[Daneshyari.com](https://daneshyari.com)