Relationships between spray parameters, microstructures and ultrasonic cavitation erosion behavior of HVOF sprayed Fe-based amorphous/nanocrystalline coatings

Lei Qiao, Yuping Wu, Sheng Hong, Jianfeng Zhang, Wei Shi, Yugui Zheng

PII: S1350-4177(17)30169-4
DOI: http://dx.doi.org/10.1016/j.ultsonch.2017.04.011
Reference: ULTSON 3646

To appear in: *Ultrasonics Sonochemistry*

Received Date: 21 January 2017
Revised Date: 7 April 2017
Accepted Date: 8 April 2017

Please cite this article as: L. Qiao, Y. Wu, S. Hong, J. Zhang, W. Shi, Y. Zheng, Relationships between spray parameters, microstructures and ultrasonic cavitation erosion behavior of HVOF sprayed Fe-based amorphous/nanocrystalline coatings, *Ultrasonics Sonochemistry* (2017), doi: http://dx.doi.org/10.1016/j.ultsonch.2017.04.011

Relationships between spray parameters, microstructures and ultrasonic cavitation erosion behavior of HVOF sprayed Fe-based amorphous/nanocrystalline coatings

Lei Qiao[a], Yuping Wu[a,b*], Sheng Hong[a,c*], Jianfeng Zhang[a], Wei Shi[a], Yugui Zheng[b]

[a] College of Mechanics and Materials, Hohai University, 8 Focheng West Road, Nanjing 211100, PR China

[b] Key Laboratory of Nuclear Materials and Safety Assessment, Institute of Metal Research, Chinese Academy of Sciences, 62 Wencui Road, Shenyang 110016, PR China

[c] Material Corrosion and Protection Key Laboratory of Sichuan Province, 180 Xueyuan Street, Zigong 643000, PR China

[*] Corresponding author: Tel:+86-25-83787233; fax: +86-25-83787233

E-mail address: wuyuping@hhu.edu.cn (Y.P. Wu), hongsheng1988@126.com (S. Hong).