


## Accepted Manuscript

A novel hybrid magnetorheological elastomer developed by 3D printing

A.K. Bastola, H.T. Vinh, L. Li

PII: S0264-1275(16)31392-2  
DOI: doi: [10.1016/j.matdes.2016.11.006](https://doi.org/10.1016/j.matdes.2016.11.006)  
Reference: JMADE 2442  
To appear in: *Materials & Design*  
Received date: 3 October 2016  
Revised date: 28 October 2016  
Accepted date: 1 November 2016



Please cite this article as: A.K. Bastola, H.T. Vinh, L. Li , A novel hybrid magnetorheological elastomer developed by 3D printing. The address for the corresponding author was captured as affiliation for all authors. Please check if appropriate. *Jmade*(2016), doi: [10.1016/j.matdes.2016.11.006](https://doi.org/10.1016/j.matdes.2016.11.006)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

## A novel hybrid magnetorheological elastomer developed by 3D printing

A. K. Bastola, H. T. Vinh, L. Li<sup>1</sup>

School of Mechanical and Aerospace Engineering, Nanyang Technological University,

50 Nanyang Avenue, Singapore 639798

### ABSTRACT

In this study, a novel magnetorheological (MR) hybrid elastomer has been developed using a 3D printing method. In such an MR hybrid elastomer, a controlled volume of an MR fluid was encapsulated layer by layer into an elastomer matrix by means of a 3D printer and each layer was a composite structure consisting of an MR fluid and an elastomer. Similar to current MR fluids and MR elastomers, mechanical properties of 3D printed MR hybrid elastomers could be controlled via an externally applied magnetic field. The experimental results showed that the relative change in the damping capability of the new MR elastomer was more pronounced than the change in its stiffness when exposed to an external magnetic field. The study demonstrated that the 3D printing technique is feasible for fabrication of MR elastomers with controlled microstructures including magnetic particles or MR fluids. The 3D printed MR hybrid elastomer is also a potential material as a tunable spring-damper element.

*Keywords:* MR elastomer; 3D printing; magnetic field; stiffness; damping

---

<sup>1</sup> Corresponding author.

Download English Version:

<https://daneshyari.com/en/article/5148831>

Download Persian Version:

<https://daneshyari.com/article/5148831>

[Daneshyari.com](https://daneshyari.com)