

Accepted Manuscript

Title: Mechanical properties and fractal analysis of the surface texture of sputtered hydroxyapatite coatings

Author: Mirosław Bramowicz Laurentiu Braic Funda Ak Azem Sławomir Kulesza Isil Birlik Alina Vladescu



PII: S0169-4332(16)30827-3
DOI: <http://dx.doi.org/doi:10.1016/j.apsusc.2016.04.077>
Reference: APSUSC 33078

To appear in: *APSUSC*

Received date: 25-1-2016
Revised date: 25-3-2016
Accepted date: 11-4-2016

Please cite this article as: Mirosław Bramowicz, Laurentiu Braic, Funda Ak Azem, Sławomir Kulesza, Isil Birlik, Alina Vladescu, Mechanical properties and fractal analysis of the surface texture of sputtered hydroxyapatite coatings, *Applied Surface Science* <http://dx.doi.org/10.1016/j.apsusc.2016.04.077>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Mechanical properties and fractal analysis of the surface texture of sputtered hydroxyapatite coatings

Mirosław Bramowicz¹, Laurentiu Braic², Funda Ak Azem³, Sławomir Kulesza⁴, Isil Birlik³, Alina Vladescu^{2*} alinava@inoe.ro

¹University of Warmia and Mazury in Olsztyn, Faculty of Technical Sciences, Oczapowskiego 11, 10-719 Olsztyn, Poland

²National Institute for Optoelectronics, 409 Atomistilor, 077125, Magurele, Romania

³Dokuz Eylül University, Engineering Faculty, Metallurgical and Materials Engineering Department, Tinaztepe Campus, 35397, Izmir, Turkey

⁴University of Warmia and Mazury in Olsztyn, Faculty of Mathematics and Computer Science, Słoneczna 54, 10-710 Olsztyn, Poland

* Corresponding author. Tel./Fax:+4-021-457.57.59

Graphical Abstract

Highlights

- Hydroxyapatite were prepared at temperatures in the range from 400 to 800 °C.
- The coatings prepared at 800 °C is closer to the stoichiometric hydroxyapatite.
- Hardness and elastic modulus decreased with increasing deposition temperature.
- The surface morphology strongly depends on the deposition temperature.

Download English Version:

<https://daneshyari.com/en/article/5347661>

Download Persian Version:

<https://daneshyari.com/article/5347661>

[Daneshyari.com](https://daneshyari.com)