

Author's Accepted Manuscript

Functionally graded aluminum foam consisting of dissimilar aluminum alloys fabricated by sintering and dissolution process

Yoshihiko Hangai, Tomoaki Morita, Takao Utsunomiya



PII: S0921-5093(17)30528-2
DOI: <http://dx.doi.org/10.1016/j.msea.2017.04.070>
Reference: MSA34971

To appear in: *Materials Science & Engineering A*

Received date: 10 March 2017
Revised date: 15 April 2017
Accepted date: 17 April 2017

Cite this article as: Yoshihiko Hangai, Tomoaki Morita and Takao Utsunomiya, Functionally graded aluminum foam consisting of dissimilar aluminum alloy fabricated by sintering and dissolution process, *Materials Science & Engineering A*, <http://dx.doi.org/10.1016/j.msea.2017.04.070>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting galley proof before it is published in its final citable form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain

Functionally graded aluminum foam consisting of dissimilar aluminum alloys fabricated by sintering and dissolution process

Yoshihiko Hangai^{a*}, Tomoaki Morita^a, Takao Utsunomiya^b

^aFaculty of Science and Technology, Gunma University, Kiryu 376-8515, Japan

^bDepartment of Mechanical Engineering, Shibaura Institute of Technology, Tokyo 135-8548, Japan

*Corresponding author. Tel: +81-277-30-1554. E-mail: hanhan@gunma-u.ac.jp

Abstract

Functionally graded (FG) aluminum (Al) foam, which consists of multilayers of different Al foams, is expected to exhibit higher functionality than ordinary uniform Al foam. In this study, uniform Al foams and two kinds of two-layered FG Al foams with different types of Al were fabricated by a sintering and dissolution process. From X-ray computed tomography (CT) inspection of the obtained foams, it was confirmed that NaCl was completely removed from the foams by dissolution. In addition, the FG Al foams in each layer had almost constant porosity (NaCl volume fraction, V_f) with seamless bonding between the layers. From the static compression tests of uniform foams, it was shown that the compression properties can be controlled by varying the type of Al, which is a similar tendency to the mechanical properties of the bulk materials. In addition, the compression properties can be controlled by varying V_f , regardless of the type of Al. From the static compression tests of FG Al foams, the foams exhibited multiple compression properties corresponding to the deformation of each layer for various V_f and different types of Al, which were similar to those of the corresponding uniform foams. In addition, the width of the plateau regions of FG Al foams can be controlled by controlling the height ratio between the layers. The advantage of varying the type of Al is that the mechanical properties of foams can be

Download English Version:

<https://daneshyari.com/en/article/5456045>

Download Persian Version:

<https://daneshyari.com/article/5456045>

[Daneshyari.com](https://daneshyari.com)