

Accepted Manuscript

The effect of solution flow rate and substrate temperature on structural and optical properties of TiO₂ films deposited by spray pyrolysis technique

K. Farhadian Azizi, M.- M. Bagheri- Mohagheghi

PII: S0040-6090(16)30795-7
DOI: doi: [10.1016/j.tsf.2016.11.040](https://doi.org/10.1016/j.tsf.2016.11.040)
Reference: TSF 35642

To appear in: *Thin Solid Films*

Received date: 27 January 2016
Revised date: 19 November 2016
Accepted date: 24 November 2016



Please cite this article as: K. Farhadian Azizi, M.-M. Bagheri- Mohagheghi, The effect of solution flow rate and substrate temperature on structural and optical properties of TiO₂ films deposited by spray pyrolysis technique, *Thin Solid Films* (2016), doi: [10.1016/j.tsf.2016.11.040](https://doi.org/10.1016/j.tsf.2016.11.040)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Title:

The effect of solution flow rate and substrate temperature on structural and optical properties of TiO₂ films deposited by spray pyrolysis technique

Authors:

K. Farhadian Azizi ^a, M.- M. Bagheri- Mohagheghi ^b

^a Young Researchers Club, Babol Branch, Islamic Azad University, Babol, Iran

^b School of Physics and Center for Solid State Physics Research, Damghan University,

Damghan, Iran

***Corresponding author:**

K. Farhadian Azizi

Mail address: kh.farhadian87@gmail.com

Tel: +981132376954

Download English Version:

<https://daneshyari.com/en/article/5466415>

Download Persian Version:

<https://daneshyari.com/article/5466415>

[Daneshyari.com](https://daneshyari.com)