



Contents lists available at ScienceDirect

## Nuclear Instruments and Methods in Physics Research B

journal homepage: [www.elsevier.com/locate/nimb](http://www.elsevier.com/locate/nimb)

# Role of conductivity for the production of charge patches by ions guided in capillaries

N. Stolterfoht<sup>a,\*</sup>, P. Herczku<sup>b</sup>, Z. Juhász<sup>b</sup>, S.T.S. Kovács<sup>b</sup>, R. Rácz<sup>b</sup>, S. Biri<sup>b</sup>, B. Sulik<sup>b</sup>

<sup>a</sup> Helmholtz-Zentrum Berlin für Materialien und Energie, 14109 Berlin, Germany

<sup>b</sup> MTA Institute for Nuclear Research (Atomki), H-4001 Debrecen, Pf. 51, Hungary

## ARTICLE INFO

## Article history:

Received 8 November 2016

Received in revised form 5 February 2017

Accepted 18 March 2017

Available online xxxx

## Keywords:

Ion transmission

Highly charged

Guiding

Nanocapillaries

Polymers

## ABSTRACT

Guiding of 3-keV  $\text{Ne}^{7+}$  ion through nanocapillaries in highly insulating polymers was studied. By means of simulations it is made evident that oscillations of the ion emission angle after transmission through capillaries reveals charge patches within the capillaries. The creation and removal of the charge patches depend on the conductivity of the capillaries so that a relationship of the conductivity and the oscillatory structure of the mean ion emission angle can be established. Experimentally significant differences were found in the ion fractions transmitted through capillaries prepared in polycarbonate (PC) and polyethylene terephthalate (PET). For PC the ion fraction decreases with inserted charge indicating blocking effects on the transmitted ions whereas for PET the ion transmission was found to be almost constant even for long term irradiation. The observed differences were attributed to different conductivities of the capillaries in the polymer materials. This attribution was supported by additional measurements concerning the oscillatory structures of the ion emission angles.

© 2017 Elsevier B.V. All rights reserved.

## 1. Introduction

Since ion guiding through insulating capillaries with a diameter of hundred nanometer has been observed [1], the subject received considerable interest. Ion guiding in nanocapillaries is supported by charge patches produced by the deposition of ions within the capillary interior. The outstanding property of ion guiding is the self-organizing process, which governs the charge patch formation and the corresponding ion deflection.

Initial studies of ion guiding phenomena in insulating materials have been conducted by means of capillaries in polyethylene terephthalate (PET) [1,2]. Subsequently, several laboratories performed similar experiments using PET [3–5], polycarbonate (PC) [6,7], and other materials [8,9]. Moreover, ion guiding within single glass capillaries was observed [10–12]. Apart from the experimental work, simulations of capillary guiding [13,14] have provided additional insights into the charge patch formation. Overviews over the field studying ions and other projectiles are given in recent reviews [15,16].

In the past, particular attention has been devoted to the time evolution of the ion emission angle which revealed oscillatory structures when measured as a functions of the inserted charge

[8,17]. The oscillations can be associated with the formation of secondary charge patches temporarily created in addition to the dominant charge patch within the entrance region. It is evident that secondary charge patches can only be formed and maintained when the charge removal is limited. Thus, the charge patch formation provides information about the conductivity of the capillary material.

In general, the ion transmission rises with a time delay to a maximum where stationary (equilibrium) conditions are reached involving a constant fraction of the transmitted ions [1,2]. Only recently, experiments with PC capillaries have shown that after reaching a maximum the transmitted ion fraction decreases with charge insertion [6,7], which has been referred to as ion blocking. Additional experiments with PET capillaries [18] have shown that ion blocking increases with the areal density of the capillaries. For high densities, the neighbor capillaries create a repulsive field in a given capillary, which is responsible for the ion blocking.

Recent experimental studies, comparing PET capillaries from different laboratories, have revealed significant differences in long-term ion transmission [19]. The PET capillaries, which showed blocking [18], were prepared at the GSI Helmholtz-Zentrum in Darmstadt (Germany) [20] whereas new measurements with capillaries from the Flerov Laboratory of Nuclear Reaction (FLNR) in Dubna (Russia) [21] showed stable transmission

\* Corresponding author.

E-mail address: [nico@stolterfoht.com](mailto:nico@stolterfoht.com) (N. Stolterfoht).

[19]. These different transmissions were associated to differences in the conductivity at the surface and bulk of the PET samples.

The present work is devoted to the comparison of transmitted ion fractions through capillaries prepared in different materials. We measured guiding of 3-keV  $\text{Ne}^{7+}$  through FLNR PET capillaries in view of the previous results obtained with the PC capillaries from GSI [6]. Significant differences were observed in the ion transmission through PET and PC capillaries, which were again attributed to different conductivities of the materials involved. This conclusion was found to be consistent with additional experiments comparing the oscillatory time dependence of the mean ion emission angle.

### 1.1. Trajectories and charge distributions

Before presenting the experiments, we show a few results from simulations of 4.5  $\text{Ar}^{7+}$  ions guided through a single macrocapillary. The simulations were described in detail previously [22] so that no details about the theoretical method are given here. The capillary shape and the tilt angle were chosen in accordance with previous experiments [12]. The outstanding feature of those experiments is the control of the temperature of the macrocapillary which, in turn, allows a controlled change of its conductivity. Thus, we can demonstrate the relationship between the variation of the ion emission angle and the conductivity of the capillary material.

Such temperature variation is difficult to perform with the nanocapillaries used in the present experiments. Hence, the parameters of the calculations are not the same as those used in the present experiments. However various theoretical and experimental studies have shown that the general features of the capillary guiding through macrocapillaries and nanocapillaries are quite similar [15,16].

Fig. 1 is composed of two groups of results, which correspond to capillary bulk conductivities differing by more than an order of magnitude, i.e.,  $1.45 \times 10^{-16}$  S/cm for the upper group and  $24.6 \times 10^{-16}$  S/cm for the lower group. The labels (a) to (f) refer to the increase of the ion charge  $Q_{in}$  deposited into the capillary. The left-hand and middle columns depict, respectively, ion trajectories and deposited charges within the capillary. The right-hand column shows the mean angle of the ions emitted from the capillary exit relative to the incident beam direction.

Let us first consider the upper group in Fig. 1. In panel (b) the ion trajectories are deflected by the entrance patch so that they are directly transmitted to the capillary exit. Fig. 1(c)–(f) show that the ions follow oscillatory trajectories along the capillary to the exit where they leave under varying emission angles. This can clearly be seen from the corresponding mean emission angles in the right hand column. In Fig. 1 the middle column shows the distributions of deposited charges, which allows for the distinction of the entrance patch from three additional charge patches. These charge patches are responsible for the oscillations of the ion emission angle.

Next, consider the lower group of graphs corresponding to a bulk conductivity increased by more than an order of magnitude. Fig. 1(b)–(f) shows that the ion trajectories do not change much with increasing charge insertion. The ions are deflected by the entrance charge patch directly to the capillary exit and are emitted essentially under the same angles as can be seen from the corresponding mean emission angle in the right hand column. This behavior is consistent with the middle panels, which show that no charge patches are created apart from the entrance patch. The missing charge patches are attributed to the relatively high conductivity, which rapidly depletes the deposited charges. Therefore, Fig. 1 demonstrates that the variation of the ion emission angle provides information about the conductivity of capillaries.

## 2. Experimental results

The experiment was carried out at the Institute of Nuclear Research of the Hungarian Academy of Sciences (ATOMKI), Debrecen. The experimental arrangement has been described in Refs. [5,19] so that only a few details shall be given here. Highly charged ions were provided by an electron cyclotron resonance (ECR) ion source [23], from which 3 keV  $\text{Ne}^{7+}$  were extracted. The beam of typically 100 pA was collimated by two diaphragms of 0.5 mm diameter spaced 20 cm apart involving a beam divergence of  $\sim 0.2^\circ$  FWHM (full width at half maximum). The final charge state of the ion that passed through a capillary, could be selected using an electric deflection field in front of the ion detector.

In the experiments, capillaries in a PET sample from FLNR were used with a diameter of 200 nm and an areal densities of  $1 \times 10^8 \text{ cm}^{-2}$ . These PET samples were initially prepared in Dubna by producing ion tracks by 250 MeV Kr ions and further treated at the Ionenstrahl-Labor (ISL) in Berlin by etching the ion tracks in a NaOH solution. In the previous experiments [6] with PC samples, the capillaries were prepared at GSI in Darmstadt by 2.2 GeV gold ion irradiation [20] and etching. Thus, capillaries with a diameter of  $\sim 165$  nm and a density of  $6 \times 10^7 \text{ cm}^{-2}$  were obtained.

The capillary samples were mounted on a goniometer, which allowed for an alignment in three axial dimensions and around one rotational axis. The PET membranes were spanned on a circular frame with an inner diameter of 7 mm. In the experimental chamber the incident ions were transmitted through the capillaries and observed using a multi channel plate detector (MCP). Previous studies [2] have shown that the experimental results scale with the inserted charge so that this parameter was used to display the measured results in the following.

### 2.1. Total yield of the transmitted ions

The total yield  $Y_t$  for the transmission of 3-keV  $\text{Ne}^{7+}$  ions was determined by summing up the counts within an image measured by the MCP detector. The total yield was normalized by the number of incident ions  $Y_{in}$  to obtain the fraction  $f_t = Y_t/Y_{in}$  of transmitted ions. In Fig. 2 the fraction  $f_t$  for the present measurements with PET capillaries is compared with previous results obtained with PC capillaries [6]. The density of the PC capillaries ( $6 \times 10^7 \text{ cm}^{-2}$ ) is relatively high so that blocking effects due to the influence of neighbor capillaries are expected. Indeed, in Fig. 2 (a) the ion fraction exhibit an increase at the beginning of the charge insertion and after reaching a maximum the transmission curve starts to decrease by about a factor of two as  $Q_{in}$  rises from 13 to 40 fC. This decrease can be considered as the partial blocking of the ions.

In Fig. 2(b) and (c) the present results for the PET capillaries are shown. The important feature of the PET samples is that the transmission curves increase rather than decrease with increasing charge insertion, i.e., they remain stable for a charge insertion as large as  $Q_{in} = 38$  fC. Hence, no blocking effects were observed for the PET capillary even for the relatively large areal density of  $10^8 \text{ cm}^{-2}$ . This feature for the PET capillaries differs from the corresponding results for the PC samples.

To search for an explanation, one notes that the capillary types somewhat differ in diameter, density, and tilt angle. The diameters of the PC and PET capillaries are nearly equal (165 nm and 200 nm) so that it is not expected that the capillary diameter plays an important role. However, blocking effects on PC capillaries have been found to increase with decreasing capillary tilt angle [6]. Therefore, we investigated the ion transmission through the FLNR capillaries for two different tilt angles. As seen from Fig. 2(b) and

Download English Version:

<https://daneshyari.com/en/article/5467341>

Download Persian Version:

<https://daneshyari.com/article/5467341>

[Daneshyari.com](https://daneshyari.com)